



PRELIMINARY FOUNDATION INVESTIGATION AND DESIGN REPORT
for
REPLACEMENT OF MATTAWISHKWIA RIVER BRIDGE
HIGHWAY 11, SITE NO. 39W-033
GWP 154-98-00
TOWN OF HEARST, DISTRICT OF NEW LISKEARD

PETO MacCALLUM LTD.
165 CARTWRIGHT AVENUE
TORONTO, ONTARIO
M6A 1V5
Phone: (416) 785-5110
Fax: (416) 785-5120
Email: toronto@petomaccallum.com

3 cc: Stantec Consulting Ltd. for distribution to MTO,
Project Manager + one digital copy
1 cc: Stantec Consulting Ltd. for distribution to MTO, PML Ref.: 08TF031
Pavements and Foundations Section + one digital copy Index No.: 020FIDR
1 cc: Stantec Consulting Ltd. + one digital copy GEOCRES No.: 42G-29
1 cc: PML Toronto July 3, 2009



TABLE OF CONTENTS

PART A – PRELIMINARY FOUNDATION INVESTIGATION REPORT

1. INTRODUCTION	1
2. SITE DESCRIPTION AND GEOLOGY	1
3. INVESTIGATION PROCEDURES	3
4. SUMMARIZED SUBSURFACE CONDITIONS	5
4.1 General	5
4.2 Topsoil	5
4.3 Pavement Fill	6
4.4 Fill	6
4.5 Silty Clay	7
4.6 Silt Till / Silt and Sand Till	7
4.7 Sand/Silty Sand Till	8
4.8 Sand and Gravel Till	8
4.9 Cobbles and Boulders	9
5. Groundwater	9
6. MISCELLANEOUS	9

PART B – PRELIMINARY FOUNDATION DESIGN REPORT

7. ENGINEERING RECOMMENDATIONS	10
7.1 General	10
7.2 Foundations	12
7.2.1 General	12
7.2.2 Deep Foundations	13
7.2.2.1 General	13
7.2.2.2 Conventional and Semi-Integral Abutments	14
7.2.2.3 Integral Abutment Considerations	15
7.2.2.4 Bridge Piers	16
7.2.2.5 Lateral Resistances	16



7.2.3	Shallow Foundations.....	17
7.2.3.1	Spread Footings on Native Soil	17
7.2.3.2	Spread Footings On Structural Fill.....	19
7.3	Lateral Earth Pressures	20
7.4	Comparison of Foundation Alternatives	21
7.5	Approach Embankments	23
7.6	Construction Considerations	24
7.6.1	Excavation.....	24
7.7	Overview of Alternatives	25
8.	ADDITIONAL STUDIES	25
9.	CLOSURE	26

Table 1 – List of Standard Specifications Referenced in Report

Table 2 – Gradation Specification for Sand Fill in Pre-augered Holes at Integral Abutments

Table 3 – Overview of Alternatives

Figures GS-1 to GS-6 – Particle Size Distribution Charts

Figures PC-1 & PC-2 – Plasticity Charts

Figure 1 – Abutment on Compacted Fill Showing Granular A Core

Explanation of Terms Used in Report

Record of Borehole Sheets

Drawing 1 – Borehole Locations

Drawings 2 and 3 – Soil Strata

Appendix A – Record of Borehole Sheets and Foundation Drawing
(Foundation Investigation Report Contract No. 82-213)

PART A
PRELIMINARY FOUNDATION INVESTIGATION REPORT

for
Replacement of Mattawishkwia River Bridge
Highway 11, Site No. 39W-033
GWP 154-98-00
Town of Hearst, District of New Liskeard

1. INTRODUCTION

This report summarizes the results of the preliminary foundation investigation carried out for the reconstruction of the Mattawishkwia Bridge on Highway 11 in the east outskirts of the Town of Hearst, Ontario. Peto MacCallum Ltd. (PML) conducted the preliminary foundation investigation for Stantec Consulting Ltd. (Stantec) on behalf of the Ministry of Transportation of Ontario (MTO).

The proposed new bridge will carry the Highway 11 eastbound and westbound traffic over the Mattawishkwia River. The Ontario Northland Railway (ONR) crossing the Mattawishkwia River runs parallel and about 20 m south of Highway 11.

The data from a 1982 report for previous bridge repairs at the site was used for the current investigation (Ref. "Foundation Investigation Report for Mattawishkwia River Bridge" dated March 1982, GEOCREC No. 42G-016, Contract No. 82-213).

This preliminary report pertains to the bridge structure and approach embankments and is considered to be suitable for planning and preliminary design purposes and should not be used for detail design.

2. SITE DESCRIPTION AND GEOLOGY

The site is located at the existing crossing of the Mattawishkwia River Bridge on Highway 11 in the Town of Hearst, Ontario.

Land use in the vicinity of the site comprises the existing transportation corridor of Highway 11 and (ONR) which is running parallel and south of Highway 11. The local topography of the structure site is generally flat with a gentle down gradient to the north. In the immediate vicinity of the site the land is used mainly for industrial and commercial purposes with some residential housing.



According to the 1982 report, the Mattawishkwia River at the structure site is relatively slow flowing and approximately 60 m in width and 1.5 m in depth. The stream bed is covered with scattered large boulders. The river banks at some locations are up to 6 m in height and near vertical.

The existing bridge over the Mattawishkwia River is a continuous, four span reinforced concrete 'T' beam superstructure with an asphalt wearing surface. According to the original structural plans, the supporting concrete piers are founded on spread footings. Both end spans are cantilevered, therefore, no abutments are present.

The east and west piers have tilted toward the river, whereas the centre pier shows no sign of movement. According to field observations described in the Request for Proposals for the project, the east pier has a tilt of 1 horizontal to 18 vertical (1H:18V) with the top of the pier exhibiting a forward movement of about 380 mm. The west pier is tilted at 1H:30V with a movement of about 178 mm at the top. Cracks of up to 19 mm wide were observed in the diaphragms between the 'T' beams and pier.

The east approach fill beneath the cantilevered end span includes a gabion wall which was originally installed away from the pier but has slid forward against the pier and are buckling upward near the centre of the slope. Approximately 2.7 m of fill is being retained by the east pier.

According to data in the 1982 report, sheetpile-and-tieback systems were installed at both ends of the bridge. The sheetpiles were driven to elevations 229.6 and 230.7 m at east and west ends, respectively. Deadman anchors were provided at both ends about 18 m away from the sheetpiles.

The surface of the west approach fill includes a mixture of sand, gravel and clayey silt with the occasional boulder. The height of fill behind the west pier is about 2.7 m when measured from the stream bed.



The study area site is located within the Abitibi Uplands, part of the Canadian Shield physiographic region. The soil cover in the region typically comprises ground moraine of varying thicknesses. The soils generally comprise Cochrane Till which is described as a non-sorted, non-stratified silty clay, silty clay loam or silt loam. This deposit locally contains lenses, clasts or blocks of clay and silt and granular materials, cobbles and boulders. (Sado, E.V. Fullerton, D.S., and Farrand, W.R., Quaternary Geologic Map of the Lake Nipigon 4° x 6° Quadrangle, USA and Canada, 1994).

3. INVESTIGATION PROCEDURES

The field work was carried out in November 2008. Sixteen sampled boreholes were put down at the site. Four boreholes designated 101 through 104 were drilled along the approximate centreline of the highway (alignment 1), six boreholes designated 201 through 206 were drilled about 12 m to the south of the centreline (alignment 2) and six boreholes designated 301 through 306 were drilled 18 to 35 m to the north of the centreline (alignment 3). The boreholes were drilled to practical refusal or to competent ground at depths of 4.7 and 10.2 m. Locally, one borehole was drilled to 0.6 m, where auger refusal was met on probable cobbles and boulders. The borehole locations are shown on the attached Drawing 1.

The locations of boreholes were selected by PML and the ground surface elevations at the boreholes in the field were surveyed by Stantec. Some of the boreholes were relocated due to interference from overhead and underground utilities or drilling access constraints.

The boreholes were advanced using continuous flight hollow stem augers and NW washboring, powered by a truck-mounted CME-75 drill rig, supplied and operated by a specialist drilling contractor, working under the full-time supervision of a member off our engineering staff. Rotary diamond drilling was also utilized to advance the boreholes through cobbles and boulders.



Representative soil samples were recovered using a split spoon sampler in conjunction with standard penetration tests. Penetrometer testing was also performed to further assess the undrained shear strength of the cohesive soils. It is noted that the results of penetrometer tests may be lower than the actual values due to sample disturbance.

The groundwater conditions at the borehole locations were assessed during drilling by visual examination of soil, the sampler and drill rods as the samples were retrieved and, when appropriate, by measurement of the water level in the open boreholes. The water level observations are noted on the attached Record of Borehole Sheets.

Upon completion of augering, the boreholes were backfilled with auger cuttings and Holeplug bentonite to the ground surface in accordance with current Regulation 903 and MTO guidelines.

Soils were identified in the field in accordance with the MTO Soil Classification procedures. Recovered soil samples were returned to our laboratory for detailed visual examination, soil classification and laboratory testing. The laboratory testing program comprised the following tests:

- Natural moisture content determinations (88)
- Grain size analyses (25)
- Atterberg limits (3)

The results of the laboratory natural moisture content determinations, grain size analyses and Atterberg limits are shown on the Record of Borehole sheets. The grain size distribution charts are presented on Figures GS-1 to GS-6. The Atterberg limits results are presented on Figures PC-1 and PC-2.



4. SUMMARIZED SUBSURFACE CONDITIONS

4.1 General

Refer to the attached Record of Borehole Sheets for the details of the subsurface conditions including soil classifications, inferred stratigraphy, soil strata and groundwater observations.

The borehole locations and the plan of the existing Mattawishkwia River Bridge are presented on the attached Foundation Drawing 1.

The subsurface stratigraphy revealed in the boreholes generally consisted of the typically 1500 mm thick pavement fill of the Highway 11 or 200 to 600 mm topsoil elsewhere, over 0.3 to 5.3 m thick fill units which were placed over 2.6 to 7.6 m thick compact to very dense heterogeneous cohesionless till deposits. A 1.5 to 2.4 m thick firm to very stiff silty clay deposit was found below fill units in boreholes 201, 203 and 301. A 0.4 m thick layer of cobbles and boulders was contacted in borehole 205 at depth of 0.2 m, extended to 0.6 m depth where auger refusal was encountered. Cobbles and boulders were also encountered in the lower zone of the till in boreholes 303 and 304. The soil conditions encountered in the boreholes previously drilled for the bridge site (March 1982 report) are consistent with those encountered in the boreholes recently drilled for this investigation.

4.2 Topsoil

Surficial topsoil layers 200 to 600 mm thick were encountered in boreholes 201, 202, 203, 204, 205, and 303 through 306. The topsoil extended to depths ranging from 0.2 to 0.6 m, elevations 232.3 to 237.3 m. One N value of 1 was obtained.



4.3 Pavement Fill

Asphaltic concrete of 100 mm thickness was found in boreholes 101, 102, 103, 104 and 206 overlying 1400 mm thick granular base materials. This pavement structure extended to 1.5 m in depth, elevations 235.7 to 235.8 m. The granular base contains sand trace to some gravel some silt. Cobbles were mixed with the pavement fill matrix in borehole 104.

The laboratory moisture content of the pavement fill was 3 and 8%. The grain size distribution charts of representative samples of granular base are shown on Figure GS-1.

4.4 Fill

A 1.2 to 5.3 m thick fill layer was encountered at a uniform to 1.5 m depth, elevations 235.7 to 235.8 m, beneath the pavement fill in boreholes 101, 102, 103, 104 and 206. Below the topsoil in boreholes 201, 202, 203, 204, 303, 304, 305 and 306, the fill was encountered at depths ranging from 0.2 to 0.6 m and extended to depths ranging from 0.6 to 2.1 m, elevations 230.4 and 234.8 m. Fill was found surficially in boreholes 301 and 302 and extended to 0.6 and 1.5 m depths, elevations 235.1 to 235.5 m. The fill units were heterogeneous and included sand, silty sand, sand and gravel, sandy silt, silty clay and clayey silt. N values typically ranged from 3 to 14 with one localized higher N value of 35 in borehole 102.

The grain size distribution charts of two silty clay fill samples are presented in Figure GS-2. The Atterberg plasticity limits are shown in Figure PC-1. The liquid limits of the samples were 36 and 43 and the plastic limits were 18 and 22, with plasticity index values of 18 and 21. Moisture contents determined on the fill samples typically ranged from 4 to 30% with a single higher value of 86% which was obtained on a silt sample containing organics from borehole 103.



4.5 Silty Clay

Beneath the fill units at 0.6 to 1.5 m depths (elevations 234.2 to 236.9 m), a discontinuous 1.5 to 2.4 m thick firm to very stiff silty clay layer was encountered in boreholes 201, 203 and 301. The silty clay deposit extended to an underlying silt till at depths of 2.3 to 3.0 m (elevations 232.5 to 234.5 m). Penetrometer test values obtained ranged from 36 to 138 KPa. N values ranged between 5 and 11.

The charts from grain size distribution and Atterberg limits testing conducted on a silty clay sample are presented in Figures GS-3 and PC-2, respectively. The Atterberg liquid and plastic limits were 40 and 20, respectively, with a plasticity index of 20. The moisture content of the representative sample was 33%.

4.6 Silt Till / Silt and Sand Till

Beneath the fill units at depth of 0.6 to 6.8 m (elevations 230.4 to 236.9 m) in boreholes 101, 102, 103, 104, 203, 206 and 302 to 306 and below the silty clay deposit at 2.3 to 3.0 m depths (elevations 232.5 to 234.5 m) in boreholes 201, 203 and 301, a 2.5 and 7.5 m thick silt till / silt and sand till was encountered. The silt till / silt and sand till extended to the borehole termination depths of 3.7 to 9.8 m (elevations 226.1 to 231.0 m). The deposits contain layers of various soil types including clay/silty clay/clayey silt, sandy silt, sand with gravel and silty sand and also contained scattered cobbles and boulders.

The silt/silt and sand till was typically loose to dense within the upper zones becoming very dense with depth. N values varied from 10 to 30 blows for 50 mm penetration. Locally, a low N value of 4 was recorded in borehole 303 within the upper zone of the deposit.

The water content of the silt/silt and sand till ranged between 8 and 23%, typically in range of 11 to 21. A single high moisture content of 34% was recorded in borehole 201 at depth of 6.2 m, elevation 231.3 m. The grain size distribution chart of a representative sample of the silt/silt and sand till is shown on Figure GS-4. The silt sample was non-plastic according to an Atterberg limit determination and visual examination.



4.7 Sand/Silty Sand Till

A deposit of compact to very dense sand/silty sand till was encountered in boreholes 103, 304 and 306 below the silt/silt and sand till at depths of 3.8 and 9.6 m (elevations 227.7 and 229.6 m) and extending to the borehole termination depths of 7.8 to 10.2 m at elevations 224.8 and 227.1 m. The deposit contains trace clay trace to with silt with gravel, and cobbles and boulders. The penetrated thickness of the deposit was about 0.6 and 4.1 m. The N values in the deposits ranged from 25 to 50 blows for 50 mm penetration.

The water content of the sand/silty sand till ranged between 11 and 16%, indicating wet conditions. The grain size distribution charts of representative samples of the sand/silty sand are shown on Figure GS-5. The sand/silty sand samples were non-plastic according to an Atterberg limits determination and visual examination.

4.8 Sand and Gravel Till

A deposit of dense to very dense sand and gravel till was encountered in borehole 204 below the fill unit at a depth of 2.1 m (elevation 230.4 m). The sand and gravel deposit contains trace clay with silt trace gravel and cobbles and boulders. The thickness of the deposit was 2.6 m extending to the 4.7 m termination depth of the borehole elevation 227.8 m. The N values in the deposit ranged from 41 to 30 blows for 50 mm penetration.

The grain size distribution chart of representative samples of the sand and gravel is shown on Figure GS-6.



4.9 Cobbles and Boulders

In borehole 205, a 0.4 m thick layer of cobbles and boulders was contacted below topsoil at 0.2 m depth, elevation 233.2 m, and extended to the borehole termination depth of 0.6 m, elevation 232.8 m, where augering was terminated. These obstructions could be part of the fill for the existing ONR and Highway 11 common embankments. In view of the limited access and winter conditions at the time of the investigation, the origin of this deposit could not be verified. Cobbles and boulders were also encountered in the lower zone of the till in boreholes 303 and 304.

5. GROUNDWATER

Water level was observed during drilling in boreholes 102, 201, 202, 204, 301 through 306 at depths of 0.6 to 4.6 m (elevations 231.9 and 235.1 m). Upon completion of drilling groundwater was measured in boreholes 201, 304 and 306 at depths of 2.1 to 7.6 (elevations 228.0 to 230.6 m). The groundwater table was not determined upon completion of drilling in the remaining boreholes.

The water level in the Mattawishkwia River was at elevation 231.5 m on November 14, 2008.

The groundwater levels are subjected to fluctuations due to seasonal and rainfall patterns.

6. MISCELLANEOUS

The field work was carried out under the supervision of Mr. C.M. Nascimento, P.Eng., Senior Project Engineer. The drilling equipment was supplied by Abraflex Drilling Ltd. Laboratory testing was carried out in the PML Toronto laboratories.

PART B
PRELIMINARY FOUNDATION DESIGN REPORT
for
Replacement of Mattawishkwia River Bridge
Highway 11, Site No. 39W-033
GWP 154-98-00
Town of Hearst, District of New Liskeard

7. ENGINEERING RECOMMENDATIONS

7.1 General

Part B of this report provides the preliminary foundation engineering recommendations regarding design and comments for replacement of the Mattawishkwia River Bridge on the Highway 11 in the Town of Hearst, Ontario. Comments concerning the design of foundations for a new temporary bridge (detour structure) to carry traffic over the river during construction of the replacement bridge are also provided for possible alignments located north and south of the existing bridge. The recommendations are preliminary and based on the results of the preliminary subsurface investigation that was outlined in the Part A of this report.

The road grade on Highway 11 at the existing about 72 m long and 10 m wide bridge location is near elevation 237.3 m as surveyed by Stantec. The water level in the river was at elevation 231.5 m at the time of the investigation. The existing approach fill embankments are about 5.8 m high above the water level in the river.

Further to the assessments carried out by Stantec and MTO (plans dated April 22, 2009) the following construction alternatives were considered for the bridge replacement.

Alternative 1a: New bridge on existing alignment with single lane detour 16.0 m north of the existing bridge.

Alternative 1b: New bridge on existing alignment, single lane detour 16.0 m south of the existing bridge.

Alternative 2a: New bridge on existing alignment with two-lane detour 16.0 m north of the existing bridge.

Alternative 2b: New bridge on existing alignment with two-lane detour 16.0 m south of the existing bridge.



Alternative 3a: Staged construction with single lane traffic during construction, new bridge on new alignment located 1.4 m north of the existing bridge.

Alternative 3b: Staged construction with single lane traffic during construction, new bridge on new alignment located 1.4 m south of the existing bridge.

Alternative 4: Replacement bridge on new alignment located 16.0 m north of the existing bridge (no detour).

Alternatives 3a or 3b require constructing the replacement bridge on new alignment 1.4 m north or south of the existing alignment. Consequently, their stage 1 involves the removal of a longitudinal portion of the existing bridge and construction of that respective portion of the new bridge while the bridge immediately adjacent to the remaining portion of the existing structure remains in place for temporary vehicular traffic. The stage 2 includes the demolition of the remaining portion of the old bridge and completing the balance of the new bridge.

From the Foundations perspective, the seven listed alternatives result in essentially three possible bridge locations. These are for the new and/or detour bridges on the existing bridge alignment (existing location), to the south of the existing bridge (south location) or to the north of the existing bridge (north location).

Use of conventional procedures to design and construct the replacement or detour bridges on deep or shallow type foundations is considered to be feasible. The use of shallow foundations is considered to be preferred for the temporary detour structure which likely will consist of a modular bridge.

For the replacement bridge, it is anticipated that the piles will find refusal in the very dense cohesionless till soils at both the west and east sides of the river. The geotechnical resistance of the deep foundations should be designed for bearing on the very dense layer at both abutments for preliminary design purposes. The piles should be provided with driving shoes due to potentially heavy driving through the glacial till which contains cobbles and boulders.

The staged construction alternative will have to consider the constraints from the existing sheetpiling and deadman anchors at each abutment. Construction of temporary or permanent approach embankments is considered to be feasible over the typically cohesionless soils at the



site. The existing ONR bridge and embankments are only about 20 m south of existing embankments and will require careful considerations and may render impractical the construction of permanent approach embankments at this location.

If alternatives 3a or 3b are selected, precautions should be taken where construction of the replacement bridge requires excavation and pile driving operations near the existing piers and sheetpiles, or when demolishing the existing bridge. Settlement and displacement of existing piers and sheetpiles and/or embankment could occur due to excessive vibration or ground loss. Therefore, settlement and displacement monitoring system should be provided during construction duration.

The water level in the river was at elevation 231.5 m at the time of the field investigation. The groundwater levels measured in the boreholes ranged from elevations 228.0 to 230.6 m however it is considered that the water level in the river will govern the water level during construction.

The recommendations in this report are preliminary and based on PML's interpretation of the factual information obtained from a limited number of boreholes. Detailed foundation investigations will be required at the selected bridge and detour structure locations during the Detail Design phase of the project. The foregoing "red-flag" issues and the interpretation and recommendations in this report are only provided for planning purposes and feasibility studies.

A list of the standard specifications referenced in the report is enclosed in Table 1.

7.2 Foundations

7.2.1 General

The detour structure will likely be a modular steel truss bridge type. The founding of the detour structure on deep foundation such as driven steel H-piles driven to practical refusal on the very dense cohesionless soils is considered to be feasible. Spread footings placed on the native stiff soils or on engineered fill pads should also be adequate for the temporary bridge.

Based on the preliminary data, founding the proposed replacement bridge on piles driven to practical refusal on the very dense cohesionless till soils is considered to be feasible. Pile driving for the replacement bridge near the existing sheet piles and piers (alternatives 3a and 3b) may



cause displacement and settlement to the existing sheetpiles and piers. Spread footings placed on the native stiff silty clay (west side) and cohesionless till soils (east side) or on structural fill may be used for semi-integral or conventional abutment design.

Drilled caissons bearing on the native soils to support the detour or permanent structures are not considered to be practical due to the presence of cobbles and boulders in the native soils, as well as groundwater presence above the expected founding levels for caissons.

A discussion of the advantages, disadvantages, costs and risks/consequences of the possible foundation options is presented in Section 7.4 of this report.

Footings and pile caps should be provided with at least 2.6 m of earth cover or equivalent thermal insulation for foundation against frost protection. A 25 mm thick layer of polystyrene insulation is thermally equivalent to 600 mm of soil cover.

Erosion protection measures, such as rip rap or placing the footings below the anticipated scour depth should be considered.

The seismic site coefficient for the stratigraphic conditions at this site is 1.0 soil profile Type I, Canadian Highway Bridge Design Code (CHBDC) 2006 Edition, clause 4.4.6].

7.2.2 Deep Foundations

7.2.2.1 General

As indicated previously, conventional, integral or semi-integral abutment designs using steel H-piles driven to refusal into the glacial till deposits are considered feasible for replacement or detour bridges at the site. The piles may reach adequate refusal in the layers of cobbles and boulders which are part of the local matrix of the glacial till soils.

The preliminary pile foundation design recommendations for conventional and semi-integral abutments are provided in the following section followed by additional recommendations for integral abutment foundations.



7.2.2.2 Conventional and Semi-Integral Abutments

Piles for the east and west abutments at the bridges for the replacement and detour alternatives should be driven to refusal into the very dense glacial till. The estimated preliminary founding reference levels for driven piles for abutment foundations at the three possible bridge locations are provided in the following table:

ALTER-NATIVE NO.	BRIDGE LOCATION	FOUNDING ELEMENT	REFERENCE BOREHOLE NO.	FOUNDING MATERIAL	FOUNDING DEPTH (m)	STRATUM FOUNDING ELEVATION (m)	ESTIMATED PILE TIP ELEVATION (m)
1a, 1b, 2a, 2b, 3a, 3b (New Bridge)	Existing alignment	West abutment	1, 2, 5, 101 and 102	Silt till	6.1	228.4 to 231.2	226.0
		East abutment	3, 4, 103 and 104	Sandy silt till, silt and sand till	6.8 and 7.5	228.6 to 231.2	226.5 and 228.5
1b, 2b (Detour Bridge)	South of existing alignment	West abutment	202 and 203	Silt till	3.7 and 4.3	231.1	229.0
		East abutment	204	Sand and gravel till	3.7	228.8	226.5
1a, 2a (Detour Bridge) 4 (New Bridge)	North of existing alignment	West abutment	301 and 303	Silt till and silt and sand till	6.0	229.3 and 231.0	227.0 and 229.0
		East Abutment	304	Sand till silt and sand till	3.8 and 6.0	228.1 and 228.9	226.0 and 229.0

The reference depths and elevations are taken from the existing ground surface at the borehole locations to the top of the founding stratum. About 1.5 to 2.0 m depth below these levels should be allowed for pile embedment at refusal.

The piles will have to be driven through fill units and native soils containing typically cohesionless soils and locally a layer of firm to very stiff silty clay (west side) at the abutment locations. For alignments 2 and 3, the existing grade at both abutments will be raised about 4 to 5 m unless the detour bridge is constructed at a lower level than the existing bridge. It is considered, however that the development of negative skin friction on the piles will be minimal due to the relatively thin and very stiff cohesive soil strata. Consequently, negative skin friction will not affect the axial resistance at ultimate limit states (ULS) of the abutment piles. No negative skin friction needs to be considered for bridges constructed on existing alignment since the embankment height will not be raised.



Based on very dense glacial till soils at the pile tips at the both abutments, the preliminary factored geotechnical axial resistance at ultimate limit states (ULS) and geotechnical axial resistance at serviceability limit states (SLS) for the pile sections listed below are recommended.

<u>Pile Section</u>	<u>ULS, kN</u>	<u>SLS, kN</u>
HP 310 x 110	1600	1150
HP 360 x 108	1600	1150

The resistance at SLS normally allows for 25 mm of compression of the pile and founding medium.

The piles will set in a very dense glacial till at the abutments and should be equipped with driving shoes according to OPSD-3000.201 or with Titus H-Bearing Pile Standard Model according to SP 903S01. The driving shoes should be used to minimize the potential for damage when driving through the very dense glacial till containing cobbles and boulders.

Pile caps should be provided with at least 2.6 m of earth cover or equivalent thermal insulation as protection against frost action. A 25 mm thick layer of polystyrene insulation is thermally equivalent to 600 mm of soil cover.

7.2.2.3 Integral Abutment Considerations

For the integral abutment design, the H-piles should be driven to the very dense glacial till anticipated at the depths/elevations and be designed using the axial resistance indicated in the previous section 7.2.2.2 of this report. The minimum 5.0 m long pile length below the abutment stem which should be incorporated in the design will not be a concern at this site.

To accommodate movement of the integral abutment system, two concentric CSPs that extend at least 3 m below the bottom of the abutment should be placed around the pile to create an annular space. The inner CSP should be filled with sand meeting the gradation requirements of Granular B Type I. Alternatively, a single CSP filled with loose uniform sand meeting the requirements shown in the attached Table 2 may be used. Refer to MTO Report SO-96-01 for further details.



7.2.2.4 Bridge Piers

Subsurface data is not available for the pier foundation and should be obtained for detail design. It is considered that the new pier will be adequately founded on spread footings placed on the native soils under the river bed, under similar conditions as the existing piers. The footing depth should allow for the depth of potential scour in the river bed.

7.2.2.5 Lateral Resistances

The soil adjacent to the upper section of the piles is expected to comprise the compacted approach fill and native cohesionless compact to very dense till units. At the west abutments 1.5 to 1.7 m thick cohesive firm to very stiff native cohesive soils is locally present below the embankment fill.

Resistance to lateral loads may be provided in part by mobilization of passive resistance along the pile. For integral abutment piles, only the length below the annular space referred to in Section 7.2.2.3 previously should be considered. The assessed lateral passive resistance for the HP pile sections noted previously is as follows.

	SILTY CLAY				NATIVE TILL/GRANULAR 'A' OR 'B' TYPE II			
	FIRM TO STIFF		VERY STIFF		COMPACT TO DENSE		VERY DENSE	
	HP310	HP360	HP310	HP360	HP310	HP360	HP310	HP360
Factored Lateral Resistance at ULS, kN	140	140	200	240	110	150	120	170
Lateral Resistance at SLS, kN	50	60	110	140	40	50	50	70

The assessed values of lateral resistance assume that the piles are driven through the native undisturbed soils or through compacted granular materials placed as recommended. If greater resistance is required, batter piles should be installed.



To evaluate the point of contraflexure, the coefficient of horizontal subgrade reaction, k_s (MN/m³) should be computed using the following equation:

Cohesionless Soils (Terzaghi, 1955)

$$k_s = n_h z/b$$

where n_h = coefficient related to soil density
 = 10.0 MN/m³ for granular backfill and native cohesionless till
 z = depth, m
 b = pile width, m

The cohesionless soil parameter n_h is applicable to all granular fill materials to be provided along the piles.

The coefficient of horizontal subgrade reaction, k_s , for the native silty clay soils should be taken as 25,000 kN/m³ for preliminary design purposes.

7.2.3 Shallow Foundations

7.2.3.1 Spread Footings on Native Soil

As indicated previously, supporting the abutments of the replacement bridge and detour structure on conventional spread footings founded on native soil is considered to be feasible.

A minimum of 2.6 m of earth cover for frost protection will be required for the spread footing foundations. Assuming that the pavement will be constructed at the bridge deck elevation 237.3 m, the highest founding level will be at about elevation 234.7 m for foundation frost protection purposes. The reference founding levels for each of the three possible bridge locations are provided in the Table below:

ALIGNMENT NO.	BRIDGE LOCATION	FOUNDING ELEMENT	REFERENCE BOREHOLE NO.	FOUNDING MATERIAL	SPREAD FOOTINGS	
					FOUNDING DEPTH (m)	FOUNDING ELEVATION (m)
1A, 1B, 2A, 2B, 3A, 3B (New Bridge)	Existing alignment	West abutment	1, 2, 5, 101 and 102	Silt till	0.9 to 4.7	230.6 to 234.6
		East abutment	3, 4, 103 and 104	Silt till, silt and sand till	1.7 to 6.8	230.5 to 232.5



ALIGNMENT NO.	BRIDGE LOCATION	FOUNDING ELEMENT	REFERENCE BOREHOLE NO.	FOUNDING MATERIAL	SPREAD FOOTINGS	
					FOUNDING DEPTH (m)	FOUNDING ELEVATION (m)
1b, 2b (Detour Bridge)	South of existing alignment	West abutment	202 and 203	Silt till, silty clay	0.6 and 0.7	234.2 and 234.7 *
		East abutment	204	Sand and gravel till to silt till	2.1	230.4
1a, 2a (Detour Bridge) 4 (New Bridge)	North of existing alignment	West abutment	301 and 303	Silt till, silty clay	2.3 and 1.6	233.7 and 234.7 *
		East Abutment	304	Silt till	0.6	232.1

Note: (*) Highest level for foundation frost protection.

Based on the borehole data, the founding subgrade will typically include compact to dense silt till and locally firm to stiff silty clay in alternatives 2 and 3 (west abutment). The recommended preliminary geotechnical bearing resistances for spread footings constructed on the native soils is as follows:

	SILTY CLAY		GLACIAL TILL	
	FIRM	VERY STIFF	COMPACT	DENSE
Factored Geotechnical Resistance at ULS, kPa	150	500	500	600
Geotechnical Resistance at SLS, kPa	100	300	300	400

The firm silty clay at the west abutment in Alignment 3 maybe excavated a further 0.7 m below the foundation frost protection depth to about elevation 234.0 m where compact glacial till was encountered to utilize a higher geotechnical bearing resistance.

The resistance at SLS normally allows for 25 mm compression of the founding medium. Differential settlement is expected to be less than 75% of this value. A footing embedment depth of 2.0 m and groundwater at the river level (elevation 231.5 m) founding depth was assumed for computation of the ULS resistance.

The bearing resistance for inclined loads should be reduced in accordance with the requirements of clause 6.7.4 of the CHBDC.

Construction of the spread footings on native soil should be performed and monitored in accordance with OPSS 902 and SP 902S01 to verify the competency of the founding surface.



The east abutment spread footings constructed on native soil for bridges on the existing alignment or south of the existing alignment (alternatives 1a, 1b, 2a, 2b new bridges and 1b, 2b detour bridges) will be at or below the water level in the river. The construction of these footings below about elevation 232.0 m will likely require cofferdam and dewatering systems. This constraint should be verified during detail design.

As previously indicated, all footings subject to frost action should be provided with 2.6 m of earth cover or equivalent thermal insulation. A 25 mm thick layer of polystyrene insulation is thermally equivalent to 600 mm of soil cover.

7.2.3.2 Spread Footings On Structural Fill

Construction of the abutment footings of the replacement bridge and/or detour structure on structural fill placed in the approach embankment could also be employed to support the foundation loads. All existing fill should be removed from the location of the structural fill pad. The structural fill should comprise Granular A material placed in maximum 200 mm thick lifts and compacted to 100% of the ASTM D698 (standard Proctor) maximum dry density.

A general sketch of the structural fill geometry is enclosed in Figure 1. Footings should not be constructed on rockfill. However, rockfill may be placed adjacent to the Granular A core. The recommended geotechnical bearing resistances for 2.5 m wide footings constructed on structural fill is as follows:

Factored Geotechnical Resistance at ULS, kPa	900
Geotechnical Resistance at SLS, kPa	350

A minimum 2.5 m thickness of the structural fill pad was used for the computation of the geotechnical resistances. The resistance at SLS normally allows for 25 mm compression of the founding medium. Differential settlement is expected to be less than 75% of this value. A footing embedment depth of 2.6 m and a groundwater level at elevation 231.5 m was assumed for computation of the ULS resistance.

The construction of the structural fill pads for the east abutments of the bridges on the existing alignment or south of the existing alignment (alternatives 1a, 1b, 2a, 2b new bridges and 1b, 2b detour bridges) will require excavations below the water level in the river. Consequently, the



lower zones of the structural fill below about elevation 232.0 m will likely require a cofferdam and dewatering. This constraint should be verified during detail design.

The bearing resistance for inclined loads should be reduced in accordance with the requirements of clause 6.7.4 of the CHBDC.

The horizontal force imposed on the foundations will be resisted in part by the friction force developed between the underside of the footing and the structural fill. An unfactored friction factor of 0.70 is recommended for footings placed on granular fill.

7.3 Lateral Earth Pressures

The abutment walls should be designed to resist the unbalanced lateral earth pressure imposed by the backfill adjacent to the wall. For preliminary design, the lateral earth pressure, p (kPa) may be computed using the equivalent fluid pressure diagrams presented in Section 6.9 of the CHBDC or employing the following equation.

$$p = K(\gamma h + q) + C_p + C_s$$

where K = coefficient of lateral earth pressure (dimensionless)
 γ = unit weight of free-draining granular material, kN/m^3
 h = depth below final grade, m
 q = surcharge load, kPa, if present
 C_p = compaction pressure, kPa (refer to clause 6.9.3 of CHBDC)
 C_s = earth pressure induced by seismic events, kPa (refer to clause 4.6.4 of CHBDC)
 where \emptyset = angle of internal friction of retained soil (35° for Granular A or Granular B Type II or Type III)
 δ = angle of friction between the soil and wall (23.5° for Granular A or Granular B Type II or Type III)

Free-draining granular material should be used as backfill behind the wall. The following parameters are recommended for preliminary design:

PARAMETERS	GRANULAR A OR GRANULAR B TYPE II OR TYPE III
Internal Friction Angle, \emptyset (degrees)	35
Unit weight, γ (kN/m^3)	22.8
Coefficient of Active Earth Pressure, K_a	0.27
Coefficient of Earth Pressure At Rest, K_o	0.43
Coefficient of Passive Earth Pressure, K_p	3.69



The assigned geotechnical parameter values are the same for all granular materials in view of their similar physical characteristics.

The magnitude of the passive resistance is dependent on the actual lateral movement of the structure toward the retained soil. We refer to Figure C6.16 of the CHBDC for this computation. The subsoil/backfill should be considered as medium dense sand for the project.

A subdrain system (SP 405F03) should be installed to minimize the build-up of hydrostatic pressure behind the wall. The subdrain pipes should be surrounded by a properly designed granular filter or geotextile to prevent migration of fines into the system. The drainage pipes should be installed on a positive grade and lead to frost-free outlets.

7.4 Comparison of Foundation Alternatives

In view of the site conditions described previously and foregoing considerations, it is considered that the practical or feasible foundation alternatives comprise spread footings on native soil or structural fill and driven piles for the abutments at this site.

A summary of the discussion is provided on the following table:

FOUNDATION ELEMENT	ALTERNATIVE FOUNDATION	NOTES
West and East Abutments	Spread footings on native soils	Feasible where spread footings placed on the native stiff to very stiff soils or compact to dense cohesionless soils
	Spread footing on structural fill	Feasible and practical alternative
	Caisson on native soils	Not feasible due to the presence of cobbles and boulders in the native soils as well as groundwater presence above the expected founding levels
	Driven piles to practical refusal on the very dense cohesionless till soils	Feasible and practical alternative



A comparison of the relative advantages and disadvantages related to each of the foundation alternatives is presented below.

ABUTMENT FOUNDATIONS			
Spread Footings on Native Soils or Footings on Structure Fill			
Advantages	Disadvantages	Relative Costs	Risks/Consequences
<ul style="list-style-type: none"> • Ease of installation • Lower cost than deep foundations • Reduced height of abutment • May be used with semi-integral abutments 	<ul style="list-style-type: none"> • Construction of structural fill pad requires wider area • Requires construction of a fill pad • Requires placement of mass concrete to provide subgrade above water table • Requires removal of all boulders from foundation footprint (footings on native soil) • Potentially requiring tremie concrete for under water construction 	<ul style="list-style-type: none"> • Typically lower installation costs than for deep foundations 	<ul style="list-style-type: none"> • Potential risk of flooding of excavations for footings causing delays and extra costs • Existing sheetpiling and anchoring system may cause excavation difficulties for new abutments or existing alignment resulting in delays and extra costs
Driven Piles			
Advantages	Disadvantages	Relative Costs	Risks/Consequences
<ul style="list-style-type: none"> • High bearing resistance • Allows integral abutment design and construction • Lower long-term maintenance costs of deck expansion joints with integral abutment design • Negligible settlements of foundation 	<ul style="list-style-type: none"> • Requires granular fill pads to facilitate the pile driving • Potential boulders may cause difficulties • Heavy equipment for pile driving is required 	<ul style="list-style-type: none"> • Higher installation cost than spread footings 	<ul style="list-style-type: none"> • Pile damage due to presence of cobbles and boulders may require the driving of additional/replacement piles and extra costs • Pile driving for new abutments on existing alignment may interfere with existing sheetpile support system and require field adjustments or additional structural work resulting in added costs
Caisson on Bedrock			
Advantages	Disadvantages	Relative Costs	Risks/Consequences
<ul style="list-style-type: none"> • Not feasible 	<ul style="list-style-type: none"> • Not feasible 	<ul style="list-style-type: none"> • Not feasible 	<ul style="list-style-type: none"> • Not feasible

Conventional, semi-integral and integral abutments are considered feasible at this site. The type of foundation employed to support the foundation loads of the proposed structure and the system



of bridge design will be dictated by structural considerations, economic considerations and construction constraints. From a foundation engineering perspective, use of piles driven to practical refusal for integral abutment is the preferred type of foundation.

7.5 Approach Embankments

Based on the acquired data, the new approach embankments in alternatives 1a, 1b, 2a, 2b or 4 or the possible embankment widening in alternatives 3a and 3b will be placed on the compact to very dense cohesionless till or, locally at the west abutment locations, on the firm to very stiff cohesive soils underlain by compact to very dense cohesionless till.

The approach embankments should be designed and constructed in accordance with OPSD-200.010, 201.010, 202.010, 3101.150 and SP 206S03. Embankment widening should be constructed following OPSD-203.030. The side slopes of the approach embankments will be stable where they are inclined no steeper than 2H:1V for earth fill and 1.25H:1V for rockfill, based on the encountered competent founding soils.

It is noted that where the embankment fill height exceeds 8 or 10 m for earth and rockfill, respectively a 2 m wide mid-height berm will be required. The earth fill slopes, if employed, should be protected against surface erosion by sodding (OPSS 571) and suitable vegetation.

No additional settlement of the existing embankment is expected for the alternatives 3a or 3b construction assuming that no new fill is placed to raise the grade of the existing roadway or widening of the embankment is required.

The settlements for detour and permanent new embankments utilized in alternatives 1a, 1b, 2a, 2b and/or 4 are estimated to be relatively small and will occur rapidly during construction. It is recommended that both approach embankment fills be placed prior to driving the abutments piles. Further subsurface investigation and laboratory tests should be carried out during detail design for this analysis.

The backfill to the structure should be made of granular materials. The magnitude of the "consolidation" of these fills depends on the height of the embankment, the workmanship employed by the contractor and, if placed in 200 mm thick lifts compacted to 100% of standard Proctor maximum dry density in accordance with the requirements of SP 206S03 and OPSS 501



(Method A), should be in the order of 10 to 12 mm for 4 to 5 m high embankments. These estimated total settlements of the approach fill surface near the abutments should be essentially complete within 3 to 6 months after placement of the fill.

Rockfill could be used for construction of the embankments along the detour and permanent embankments.

It is estimated, based on the limited laboratory test results that the new fill for the potential widening of the existing embankment will cause negligible consolidation settlement of the existing embankment. No new settlement of the existing embankment is expected where the detour embankments are constructed about 10 m away.

The construction of the detour or replacement bridges for alternatives 1a, 1b, 2a, 2b or 4 would require construction of new embankments or widening of the existing embankment into the water or construction of a longer bridge than in alternatives 3a or 3b.

7.6 Construction Considerations

7.6.1 Excavation

All excavation at the structure foundation sites should be carried out in accordance with the Occupational Health and Safety Act (OHSA), local and MTO regulations.

Excavation for construction of foundations of the detour structure and the replacement bridge is expected to extend through the fill and into the underlying silt till and locally silty clay soils. The depth of excavation will be established at the detailed design stage. The fill, cohesive firm to stiff silty clay and compact to dense cohesionless till encountered in the boreholes are considered Type 3 soils and very dense till is considered a Type 2 soil according to OHSA (Ontario Regulation 213/91) criteria.

The stabilized groundwater level is expected to be consistent with the water level in Mattawishkwia River, which was at elevation 231.5 m at the time of the investigation. Considering that the silty and sandy soils on site are relatively pervious, conventional sump pumping techniques are unlikely to be adequately handle groundwater seepage if the excavation extends below the water level in the river. It is anticipated that a cofferdam using the steel sheeting will be



required for these excavations. Groundwater conditions should be further assessed during the detail design stage.

7.7 Overview of Alternatives

An overview of the advantages, disadvantages, costs and risks/consequences of the various alternative foundation schemes considered in this report are presented in the attached Table 3.

Considering the advantages, disadvantages, costs and risks/consequences of each alternative provided in Table 3, the staged construction of the existing bridge on new alignment 1.4 m to the north (alternative 3a) is considered to be the most favourable alternative with many advantages, and less disadvantages and lowest cost (similar to alternative 3b). The cost is anticipated to be lower than other alternatives due to shorter length of the bridge and reuse of the existing embankment.

The issue of construction near the existing foundations should be addressed by providing a monitoring survey during construction. The monitoring program should specify the frequency of survey readings to record movements of the existing structure. These readings should be carried out at the minimum interval of three times daily and the frequency should be increased when vibrations such as pile driving, heavy excavation or removal of support systems are carried out. Alert levels should be specified by the structural designer who should also review and approve the monitoring survey scheme.

8. ADDITIONAL STUDIES

The recommendations in this report are preliminary and are based on PML's interpretation of the factual information obtained from boreholes and a visual site assessment.

Foundation investigations will be required at the specific locations of the replacement and detour structures during the detail design phase of the project. The detail design foundation investigations should include drilling boreholes at the final abutment and pier locations. Where the construction of the replacement structure includes staged construction involving the existing bridge, slope stability analyses should be considered for the removal of the existing sheet piles and deadman anchor systems. Existing data should be incorporated in the detail design.



9. CLOSURE

This Preliminary Foundation Investigation and Design Report was prepared by Mr. Idib (Adeeb) Sadoun, MSc, P.Eng., Project Engineer and by Mr. C.M.P. Nascimento, P.Eng., Senior Project Engineer. Mr. B.R. Gray, MEng, P.Eng., MTO Designated Principal Contact, carried out an independent review of the report.

Yours very truly,

Peto MacCallum Ltd.



Idib (Adeeb) Sadoun, MSc, P.Eng.
Project Engineer



C. M. P. Nascimento, P.Eng.
Senior Project Engineer



Brian R. Gray, MEng, P.Eng.
MTO Designated Principal Contact

CN/BRG:mi/lmr



TABLE 1
STANDARD SPECIFICATIONS REFERENCED IN REPORT

DOCUMENT	TITLE
OPSS 501	Construction Specification for Compacting
OPSS 571	Construction Specification for Sodding
OPSS 902	Excavation and Backfilling of Structures
SP 206S03	Construction Specification for Grading
SP 405F03	Construction Specification for Pipe Subdrains
SP 902S01	Excavation and Backfilling of Structures
SP 903S01	Construction Specification for Piling
OPSD-200.010	Earth/Shale Grading – Undivided Rural
OPSD-201.010	Rock Grading-Undivided Rural
OPSD-202.010	Slope Flattening Using Excess Material on Earth or Rock Embankment
OPSD-203.030	Embankments Over Swamp - Existing Slopes Maintained
OPSD-3000.201	Oslo Points for Foundation, Piles, Steel HP310
OPSD-3101.150	Minimum Granular Backfill Requirements - Walls Abutment



TABLE 2
GRADATION SPECIFICATIONS FOR SAND FILL IN
PRE-AUGERED HOLES AT INTEGRAL ABUTMENTS

MTO Sieve Designation	Percentage Passing by Mass
2 mm (#10)	100
600 µm (#30)	80 – 100
425 µm (#40)	40 – 80
250 µm (#60)	5 – 25
150 µm (#100)	0 – 6

Note: From MTO Report S0-96-01, Revision 1 – July, 1996.




TABLE 3
OVERVIEW OF ALTERNATIVES

Alternative No.	Advantages	Disadvantages	Relative Costs	Risks/Consequences	Rank
1a Replacement on the existing alignment with single-lane detour location on the north side	<ul style="list-style-type: none"> The existing embankment is re-used for the replacement bridge. No long-term lane closure is required No settlements of the approach embankments Removal of existing sheet pile behind each abutment is facilitated No interference with ONR embankment or bridge 	<ul style="list-style-type: none"> Detour structure and approach embankments are required Detour structure on this alignment is the longest and may require piers in the river Allce Road and Riverside Drive detouring or temporary closure is required 	<ul style="list-style-type: none"> Higher costs than the staged construction alternatives due to detour construction and removal and Allce Road and Riverside Drive detouring Estimated cost (by Stantec): <ul style="list-style-type: none"> - 1a: \$7,823,000 - 2a: \$7,942,000 	<ul style="list-style-type: none"> Piers in the water for long detour bridge may be affected by ice unless constructed to resist these forces. The consequence would be failure of the detour bridge 	4
2a Same as 1a with two-lane detour					5
1b Replacement on the existing alignment with single-lane detour location on the south side	<ul style="list-style-type: none"> The existing embankment is re-used for the replacement bridge No long-term lane closure is required No settlements of the approach embankments Removal of existing sheet pile behind each abutment is facilitated 	<ul style="list-style-type: none"> Detour structure and approach embankments are required Construction of detour may interfere with ONR embankment Installation and removal of new sheetpiles are required at south toe of the slope for spread footings for detour abutment construction Settlement and displacement monitoring systems are required during and after construction of the detour structure to assess the stability of ONR foundations and embankment 	<ul style="list-style-type: none"> Higher costs than the staged construction alternatives due to detour construction and removal and monitoring system Estimated cost (by Stantec): <ul style="list-style-type: none"> - 1b: \$7,467,000 - 2b: \$7,916,000 	<ul style="list-style-type: none"> Driving piles at the abutment location for the detour structure and filling over existing railway embankment may affect the existing railroad tracks. The consequence will be increased maintenance of the railway tracks 	6
2b Same as 1b with two-lane detour					7




TABLE 3
OVERVIEW OF ALTERNATIVES


Alternative No.	Advantages	Disadvantages	Relative Costs	Risks/Consequences	Rank
3a Staged construction of the existing bridge (no detour) 1.4 m north	<ul style="list-style-type: none"> No detour is required Removal of existing piers and existing sheetpiles may not be required Replacement structure is shorter than alternatives 1a, 1b, 2a, 2b and 4 No temporary detour or closure of Alice Road and Riverside Drive is required 	<ul style="list-style-type: none"> Long-term closure is required for one lane Settlement and displacement monitoring system of the existing bridge remaining during construction of stage 1 is required Installation and removal of new temporary sheetpiles is required 	<ul style="list-style-type: none"> Cost savings for not removing the existing pier footings and reusing the existing embankment will be offset by increased costs due to installation and removal of new sheetpiles, and a monitoring system requirement Estimated cost (by Stantec): <ul style="list-style-type: none"> - 3a: \$6,444,000 - 3b: \$6,428,000 	<ul style="list-style-type: none"> Movement of the existing piers and of the existing embankment during removal of existing sheetpiles and deadman anchors for stage 1. Consequences would be failure of the part of the bridge remaining during stage 1 	1
3b Same as 3a 1.4 m south					2
4 Replacement on new alignment north of the existing bridge	<ul style="list-style-type: none"> No detour is required No long-term lane closure is required No interference with ONR embankment or bridge 	<ul style="list-style-type: none"> New approach embankment is required Replacement structure on this alignment is the longest Alice Road and Riverside Drive detouring or temporary closure is required 	<ul style="list-style-type: none"> Higher costs than the staged construction alternatives due to longer bridge requirement, installation of new sheet piles and a new embankment construction Estimated cost (by Stantec): \$7,482,000 	<ul style="list-style-type: none"> No perceived risks 	3



SILT & CLAY				FINE		MEDIUM		COARSE		GRAVEL			COBBLES	UNIFIED		
				SAND												
CLAY	FINE		MEDIUM		COARSE		FINE		MEDIUM		COARSE		GRAVEL		COBBLES	M.I.T.
	SILT															
CLAY		SILT			V. FINE		FINE		MED.		COARSE		GRAVEL			U.S. BUREAU
					SAND											



SILT & CLAY				FINE SAND			MEDIUM SAND		COARSE SAND	GRAVEL		COBBLES	UNIFIED
CLAY	SILT			FINE SAND			MEDIUM SAND		COARSE SAND	GRAVEL		COBBLES	M.I.T.
	SILT			V. FINE	FINE	MED.	COARSE SAND		GRAVEL		COBBLES		U.S. BUREAU



LEGEND		
BH	SAMPLE	SYMBOL
201	3	—


SILT & CLAY				FINE		MEDIUM		COARSE	GRAVEL		COB BLES	UNIFIED
						SAND						
CLAY	FINE		MEDIUM	COARSE	FINE		MEDIUM	COARSE	GRAVEL		COBBLES	M.I.T.
		SILT			V. FINE	FINE	MED.	COARSE	GRAVEL			U.S. BUREAU
CLAY				SAND								


GRAIN SIZE DISTRIBUTION SILTY CLAY, trace sand, trace gravel

FIG No. GS-3


HWY: 11

G.W.P. No. 154-98-00






SILT & CLAY					FINE		MEDIUM		COARSE		GRAVEL				COBBLES	UNIFIED		
CLAY	FINE		MEDIUM		COARSE		FINE		MEDIUM		COARSE		GRAVEL				COBBLES	M.I.T.
	SILT					SAND												
CLAY		SILT			V. FINE	FINE	MED.	COARSE		GRAVEL							U.S. BUREAU	
					SAND													



SILT & CLAY				FINE		MEDIUM		COARSE	GRAVEL		COBBLES	UNIFIED		
				SAND										
CLAY	FINE		MEDIUM		COARSE		FINE		MEDIUM		COARSE	GRAVEL	COBBLES	M.I.T.
	SILT													
CLAY		SILT			V. FINE	FINE	MED.	COARSE	GRAVEL					U.S. BUREAU




Ministry of
Transportation
Ontario

PLASTICITY CHART
SILTY CLAY, trace sand, trace gravel
(FILL)

FIG No. PC-1

HWY: 11

G.W.P. No. 154-98-00



Ministry of
Transportation
Ontario


PLASTICITY CHART

SILTY CLAY, trace sand, trace gravel

FIG No. PC-2


HWY: 11

G.W.P. No. 154-98-00



CROSS SECTION A-A

NOT TO SCALE



LONGITUDINAL SECTION

NOT TO SCALE

NOTES

1. CONCEPT SHOWN DOES NOT INCLUDE A MIDHEIGHT BERM.
2. LIMITS OF GRANULAR 'A' CORE TO BE DEFINED BY A SITE SPECIFIC SURVEY.
3. REMOVE ORGANIC, DELETERIOUS OR OTHERWISE UNSUITABLE MATERIAL UNDER AREA OF COMPACTED GRANULAR 'A' AND EARTH OR ROCK FILL AS NOTED IN TEXT OF REPORT.
4. PLACE GRANULAR 'A' AND EARTH OR ROCK FILL ON APPROVED SUBGRADE TO BOTTOM OF FOOTING LEVEL, COMPACTED ACCORDING TO CURRENT M.T.O. STANDARDS.
5. CONSTRUCT CONCRETE FOOTING.
6. PLACE REMAINDER OF GRANULAR 'A' AND EARTH OR ROCK FILL INCLUDING MIDHEIGHT BENCHES, AS REQUIRED.
7. REFER TO TEXT OF REPORT FOR FROST DEPTH.

FIGURE 1: ABUTMENT ON COMPACTED FILL SHOWING GRANULAR 'A' CORE

EXPLANATION OF TERMS USED IN REPORT

N VALUE: THE STANDARD PENETRATION TEST (SPT) N VALUE IS THE NUMBER OF BLOWS REQUIRED TO CAUSE A STANDARD 51mm O.D. SPLIT BARREL SAMPLER TO PENETRATE 0.3m INTO UNDISTURBED GROUND IN A BOREHOLE WHEN DRIVEN BY A HAMMER WITH A MASS OF 63.5kg, FALLING FREELY A DISTANCE OF 0.76m. FOR PENETRATIONS OF LESS THAN 0.3m N VALUES ARE INDICATED AS THE NUMBER OF BLOWS FOR THE PENETRATION ACHIEVED. AVERAGE N VALUE IS DENOTED THUS \bar{N} .

DYNAMIC CONE PENETRATION TEST: CONTINUOUS PENETRATION OF A CONICAL STEEL POINT (51mm O.D. 60° CONE ANGLE) DRIVEN BY 475 J IMPACT ENERGY ON 'A' SIZE DRILL RODS. THE RESISTANCE TO CONE PENETRATION IS MEASURED AS THE NUMBER OF BLOWS FOR EACH 0.3m ADVANCE OF THE CONICAL POINT INTO THE UNDISTURBED GROUND.

SOILS ARE DESCRIBED BY THEIR COMPOSITION AND CONSISTENCY OR DENSENESS.

CONSISTENCY: COHESIVE SOILS ARE DESCRIBED ON THE BASIS OF THEIR UNDRAINED SHEAR STRENGTH (c_u) AS FOLLOWS:

c_u (kPa)	0 - 12	12 - 25	25 - 50	50 - 100	100 - 200	> 200
	VERY SOFT	SOFT	FIRM	STIFF	VERY STIFF	HARD

DENSENESS: COHESIONLESS SOILS ARE DESCRIBED ON THE BASIS OF DENSENESS AS INDICATED BY SPT N VALUES AS FOLLOWS:

N (BLOWS/0.3m)	0 - 5	5 - 10	10 - 30	30 - 50	> 50
	VERY LOOSE	LOOSE	COMPACT	DENSE	VERY DENSE

ROCKS ARE DESCRIBED BY THEIR COMPOSITION AND STRUCTURAL FEATURES AND / OR STRENGTH.

RECOVERY: SUM OF ALL RECOVERED ROCK CORE PIECES FROM A CORING RUN EXPRESSED AS A PERCENT OF THE TOTAL LENGTH OF THE CORING RUN.

MODIFIED RECOVERY: SUM OF THOSE INTACT CORE PIECES, 100mm+ IN LENGTH EXPRESSED AS A PERCENT OF THE LENGTH OF THE CORING RUN. THE ROCK QUALITY DESIGNATION (R Q D), FOR MODIFIED RECOVERY, IS:

R Q D (%)	0 - 25	25 - 50	50 - 75	75 - 90	90 - 100
	VERY POOR	POOR	FAIR	GOOD	EXCELLENT

JOINTING AND BEDDING:

SPACING	50mm	50 - 300mm	0.3m - 1m	1m - 3m	> 3m
JOINTING	VERY CLOSE	CLOSE	MOD. CLOSE	WIDE	VERY WIDE
BEDDING	VERY THIN	THIN	MEDIUM	THICK	VERY THICK

ABBREVIATIONS AND SYMBOLS

FIELD SAMPLING

S S	SPLIT SPOON	T P	THINWALL PISTON
W S	WASH SAMPLE	O S	OSTERBERG SAMPLE
S T	SLOTTED TUBE SAMPLE	R C	ROCK CORE
B S	BLOCK SAMPLE	P H	T W ADVANCED HYDRAULICALLY
C S	CHUNK SAMPLE	P M	T W ADVANCED MANUALLY
T W	THINWALL OPEN	F S	FOIL SAMPLE
F V	FIELD VANE		

STRESS AND STRAIN

u_w	kPa	PORE WATER PRESSURE
u	1	PORE PRESSURE RATIO
σ	kPa	TOTAL NORMAL STRESS
σ'	kPa	EFFECTIVE NORMAL STRESS
τ	kPa	SHEAR STRESS
$\sigma_1, \sigma_2, \sigma_3$	kPa	PRINCIPAL STRESSES
ϵ	%	LINEAR STRAIN
$\epsilon_1, \epsilon_2, \epsilon_3$	%	PRINCIPAL STRAINS
E	kPa	MODULUS OF LINEAR DEFORMATION
G	kPa	MODULUS OF SHEAR DEFORMATION
μ	1	COEFFICIENT OF FRICTION

MECHANICAL PROPERTIES OF SOIL

m_v	kPa^{-1}	COEFFICIENT OF VOLUME CHANGE
C_c	1	COMPRESSION INDEX
C_s	1	SWELLING INDEX
C_α	1	RATE OF SECONDARY CONSOLIDATION
c_v	m^2/s	COEFFICIENT OF CONSOLIDATION
H	m	DRAINAGE PATH
T_v	1	TIME FACTOR
U	%	DEGREE OF CONSOLIDATION
σ'_{vo}	kPa	EFFECTIVE OVERBURDEN PRESSURE
σ'_p	kPa	PRECONSOLIDATION PRESSURE
τ_f	kPa	SHEAR STRENGTH
c'	kPa	EFFECTIVE COHESION INTERCEPT
ϕ'	-°	EFFECTIVE ANGLE OF INTERNAL FRICTION
c_u	kPa	APPARENT COHESION INTERCEPT
ϕ_u	-°	APPARENT ANGLE OF INTERNAL FRICTION
τ_R	kPa	RESIDUAL SHEAR STRENGTH
τ_r	kPa	REMOULDED SHEAR STRENGTH
S_t	1	SENSITIVITY = $\frac{c_u}{\tau_r}$

PHYSICAL PROPERTIES OF SOIL

ρ_s	kg/m^3	DENSITY OF SOLID PARTICLES	n	1, %	POROSITY	e_{max}	1, %	VOID RATIO IN LOOSEST STATE
γ_s	kN/m^3	UNIT WEIGHT OF SOLID PARTICLES	w	1, %	WATER CONTENT	e_{min}	1, %	VOID RATIO IN DENSEST STATE
ρ_w	kg/m^3	DENSITY OF WATER	S_r	%	DEGREE OF SATURATION	I_D	1	DENSITY INDEX = $\frac{e_{max} - e}{e_{max} - e_{min}}$
γ_w	kN/m^3	UNIT WEIGHT OF WATER	w_L	%	LIQUID LIMIT	D	mm	GRAIN DIAMETER
ρ	kg/m^3	DENSITY OF SOIL	w_p	%	PLASTIC LIMIT	D_n	mm	n PERCENT - DIAMETER
γ	kN/m^3	UNIT WEIGHT OF SOIL	w_s	%	SHRINKAGE LIMIT	C_u	1	UNIFORMITY COEFFICIENT
ρ_d	kg/m^3	DENSITY OF DRY SOIL	I_p	%	PLASTICITY INDEX = $w_L - w_p$	h	m	HYDRAULIC HEAD OR POTENTIAL
γ_d	kN/m^3	UNIT WEIGHT OF DRY SOIL	I_L	1	LIQUIDITY INDEX = $\frac{w - w_p}{I_p}$	q	m^3/s	RATE OF DISCHARGE
ρ_{sat}	kg/m^3	DENSITY OF SATURATED SOIL	I_C	1	CONSISTENCY INDEX = $\frac{w_L - w}{I_p}$	v	m/s	DISCHARGE VELOCITY
γ_{sat}	kN/m^3	UNIT WEIGHT OF SATURATED SOIL	DTPL		DRIER THAN PLASTIC LIMIT	i	1	HYDRAULIC GRADIENT
ρ'	kg/m^3	DENSITY OF SUBMERGED SOIL	APL		ABOUT PLASTIC LIMIT	k	m/s	HYDRAULIC CONDUCTIVITY
γ'	kN/m^3	UNIT WEIGHT OF SUBMERGED SOIL	WTPL		WETTER THAN PLASTIC LIMIT	j	kN/m^3	SEEPAGE FORCE
e	1, %	VOID RATIO						

RECORD OF BOREHOLE No 101

1 of 1

METRIC

G.W.P. 154-98-00 LOCATION Coordinates: 5 505 350.6 N; 331 190.6 E ORIGINATED BY F.P.
DIST 53 HWY 11 BOREHOLE TYPE Continuous Flight Hollow Stem Augers COMPILED BY A.S.
DATUM Geodetic DATE November 17, 2008 CHECKED BY C.N.

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS *	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT					PLASTIC LIMIT NATURAL MOISTURE CONTENT LIQUID LIMIT			UNIT WEIGHT γ kN/m ³	REMARKS & GRAIN SIZE DISTRIBUTION (%)
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	"N" VALUES			SHEAR STRENGTH kPa					WATER CONTENT (%)				
								○ UNCONFINED + FIELD VANE ● QUICK TRIAXIAL x LAB VANE									
237.3	Ground Surface						20	40	60	80	100						
0.0	100mm asphaltic concrete over sand, some gravel, some silt (PAVEMENT FILL)		1	CS	-												10 77 (13)
235.8																	
1.5	Silty clay, trace sand organic inclusions Stiff Moist (FILL)		2	SS	11												
234.6			3	SS	14												
2.7	Silt, some sand trace clay, trace gravel Compact to Brown Moist very dense (TILL)		4	SS	16												
			5	SS	57												3 18 72 7
			6	SS	57												
			7	SS	46												
231.0			8	SS	50/8cm												
6.3	End of borehole																
	Sample 8: Sampler bouncing																
	* Borehole dry upon completion of drilling																

RECORD OF BOREHOLE No 102

1 of 1

METRIC

G.W.P. 154-98-00 LOCATION Coordinates: 5 505 345.2 N; 331 210.5 E ORIGINATED BY F.P.
DIST 53 HWY 11 BOREHOLE TYPE Continuous Flight Hollow Stem Augers COMPILED BY A.S.
DATUM Geodetic DATE November 13, 2008 CHECKED BY C.N.

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT					PLASTIC LIMIT w _p	NATURAL MOISTURE CONTENT w	LIQUID LIMIT w _L	UNIT WEIGHT γ kN/m ³	REMARKS & GRAIN SIZE DISTRIBUTION (%)			
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	"N" VALUES			SHEAR STRENGTH kPa										WATER CONTENT (%)		
								○ UNCONFINED	● QUICK TRIAXIAL	+ FIELD VANE	× LAB VANE	20						40	60	80
237.3	Ground Surface																GR SA SI CL			
0.0	100mm asphaltic concrete over sand, some gravel, some silt						237										20 70 (10)			
	(PAVEMENT FILL)		1	CS	-		236													
235.8	Sand, trace gravel		2	SS	35		235													
1.5	Dense Brown Moist (FILL)						234													
	Silt trace clay, trace sand		3	SS	8		233													
	Loose Grey Moist						232													
233.6	Silt some clay, trace sand		4	SS	32		231													
3.7	Compact Brown Moist to dense		5	SS	21		230													
	(TILL)		6	SS	31		229													
	trace gravel		7	SS	50/10cm															
	Very dense Grey																			
228.1	End of borehole		9	SS	50/8cm															
9.2	Samples 7, 8, 9: Sampler bouncing																			
	* 2008 11 13																			
	▽ Water level observed during drilling																			

RECORD OF BOREHOLE No 103

1 of 1

METRIC

G.W.P. 154-98-00 LOCATION Coordinates: 5 505 325.0 N; 331 307.7 E ORIGINATED BY F.P.
DIST 53 HWY 11 BOREHOLE TYPE Continuous Flight Hollow Stem Augers COMPILED BY A.S.
DATUM Geodetic DATE November 12 & 13, 2008 CHECKED BY C.N.

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS *	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT				PLASTIC LIMIT NATURAL MOISTURE CONTENT LIQUID LIMIT			UNIT WEIGHT γ kN/m³	REMARKS & GRAIN SIZE DISTRIBUTION (%)	
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	"N" VALUES			SHEAR STRENGTH kPa					w _p	w			w _L
237.3	Ground Surface						20	40	60	80	100						
0.0	100mm asphaltic concrete over sand, some gravel, some silt		1	CS	-												
	(PAVEMENT FILL)																
235.8																	
1.5	Sand, trace gravel		2	SS	14												
	Compact Brown Moist to loose (FILL)																
	Silty clay		3	SS	8												
	trace sand, trace gravel organic inclusions																
	Stiff Dark brown		4	SS	7												
			5	SS	6												
			6	SS	7												
	Organic silt		7	SS	12												
230.5																	
6.8	Sandy silt, trace gravel cobbles		8	SS	50/5cm												
	Very dense Grey Moist (TILL)																
			9	SS	50/3cm												
			10	SS	50/8cm												
227.7																	
9.6	Sand with silt with gravel, trace clay																
227.1	Very dense Grey Moist (TILL)		11	SS	95/25cm												
10.2	End of borehole																
	Samples 8, 9, 10, 11: Sampler bouncing																
	* Borehole dry																

RECORD OF BOREHOLE No 104

1 of 1

METRIC

G.W.P. 154-98-00 LOCATION Coordinates: 5 505 322.2 N; 331 321.1 E ORIGINATED BY F.P.
DIST 53 HWY 11 BOREHOLE TYPE Continuous Flight Hollow Stem Augers COMPILED BY A.S.
DATUM Geodetic DATE November 12, 2008 CHECKED BY C.N.

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS *	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT					PLASTIC LIMIT w _p	NATURAL MOISTURE CONTENT w	LIQUID LIMIT w _L	UNIT WEIGHT γ kN/m ³	REMARKS & GRAIN SIZE DISTRIBUTION (%) GR SA SI CL
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	"N" VALUES			SHEAR STRENGTH kPa									
								○ UNCONFINED + FIELD VANE									
								● QUICK TRIAXIAL × LAB VANE									
					WATER CONTENT (%)												
					20	40	60	80	100	20	40	60					
237.2	Ground Surface																
0.0	100mm asphaltic concrete over sand, some silt, trace gravel cobble (PAVEMENT FILL)		1	CS	-											6 84 (10)	
235.7																	
1.5	Silty clay, trace sand organic inclusions		2	SS	8												
	Firm Brown Moist (FILL)																
	Clayey silt, trace sand		3	SS	5												
	Grey																
			4	SS	8												
	Organic silt		5	SS	7												
	Dark brown																
			6	SS	5												
231.1	Silt and sand trace clay, trace gravel		7	SS	20											5 42 44 9	
6.1	Compact Grey Moist (TILL)																
	cobbles		8	SS	75												
	Very dense																
228.3			9	SS	30/1cm												
8.9	End of borehole																
	Sample 9: Sampler bouncing																

RECORD OF BOREHOLE No 201

1 of 1

METRIC

G.W.P. 154-98-00 LOCATION Coordinates: 5 505 366.6 N; 331 097.4 E ORIGINATED BY F.P.
DIST 53 HWY 11 BOREHOLE TYPE Continuous Flight Hollow Stem Augers COMPILED BY A.S.
DATUM Geodetic DATE November 16, 2008 CHECKED BY C.N.

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT						PLASTIC LIMIT w _p	NATURAL MOISTURE CONTENT w	LIQUID LIMIT w _L	UNIT WEIGHT γ kN/m ³	REMARKS & GRAIN SIZE DISTRIBUTION (%) GR SA SI CL			
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	"N" VALUES			SHEAR STRENGTH kPa											WATER CONTENT (%)		
								○ UNCONFINED + FIELD VANE			● QUICK TRIAXIAL × LAB VANE										
237.5 0.0	Ground Surface							20	40	60	80	100									
237.3 0.2	Topsoil																				
236.9 0.6	Silty clay organic inclusions		1	SS	3		237							○							
	Soft Brown Moist (FILL)		2	SS	7									○							
	Silty clay, trace sand																				
	Firm to Brown Moist stiff grey		3	SS	11						■			○	○		2 2 30 66				
	trace gravel																				
	layers of sandy silt		4	SS	8		235														
234.5 3.0	Silt trace sand, trace gravel silty clay/ clayey silt layers		5	SS	11		234							○							
	Compact Grey Moist to loose (TILL) to wet		6	SS	9									○							
			7	SS	7		233							○							
			8	SS	12		232							○							
			9	SS	6		231								○						
	sandy										■										
			10	SS	26		230							○							
228.7 8.8	End of borehole						229														
<div>* 2008 11 16</div> <div> Water level observed during drilling</div> <div> Water level measured after drilling</div> <div> Penetrometer test</div>																					

RECORD OF BOREHOLE No 202

1 of 1

METRIC

G.W.P. 154-98-00 LOCATION Coordinates: 5 505 341.6 N; 331 180.1 E ORIGINATED BY F.P.
DIST 53 HWY 11 BOREHOLE TYPE Continuous Flight Hollow Stem Augers COMPILED BY A.S.
DATUM Geodetic DATE November 16, 2008 CHECKED BY C.N.

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT					PLASTIC LIMIT w _p	NATURAL MOISTURE CONTENT w	LIQUID LIMIT w _L	UNIT WEIGHT γ kN/m ³	REMARKS & GRAIN SIZE DISTRIBUTION (%) GR SA SI CL
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	"N" VALUES			SHEAR STRENGTH kPa									
								○ UNCONFINED	+	FIELD VANE							
235.4	Ground Surface						20	40	60	80	100						
0.0 235.1	Topsoil		1	SS	1		235										
0.3 234.8	Sandy silt trace clay, trace gravel																
0.6	Very loose Moist (FILL)		2	SS	10												
	Silt, trace sand trace clay, trace gravel silty clay layers		3	SS	11												
	Compact Brown Moist to dense (TILL)		4	SS	37												
	Grey Moist to wet		5	SS	19												
			6	SS	30												
	Very dense		7	SS	65												
229.7 5.7	End of borehole		8	SS	81/25cm		230										
	Sample 8: Sampler bouncing																
	 <																

RECORD OF BOREHOLE No 203

1 of 1

METRIC

G.W.P. 154-98-00 LOCATION Coordinates: 5 505 335.0 N; 331 201.9 E ORIGINATED BY F.P.
DIST 53 HWY 11 BOREHOLE TYPE C.F.H.S.A. + Wash Bore COMPILED BY A.S.
DATUM Geodetic DATE November 16 & 17, 2008 CHECKED BY C.N.

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS *	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT					PLASTIC LIMIT w _p	NATURAL MOISTURE CONTENT w	LIQUID LIMIT w _L	UNIT WEIGHT γ kN/m ³	REMARKS & GRAIN SIZE DISTRIBUTION (%) GR SA SI CL
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	"N" VALUES			SHEAR STRENGTH kPa									
								○ UNCONFINED		+ FIELD VANE		● QUICK TRIAXIAL					
234.8 0.0	Ground Surface						20	40	60	80	100						
234.6 0.2	Topsoil		1	SS	3												
234.2 0.6	Silty clay organics inclusions																
	Soft (FILL)		2	SS	7												
	Silty clay, trace sand																
	Very stiff Brown Moist		3	SS	5												
232.5 2.3	Silt, trace sand trace gravel, trace clay		4	SS	21												
	Compact Brown Moist																
	(TILL)		5	SS	31												
	with gravel, some sand some clay																
	Dense to Grey Moist very dense to wet		6	SS	109												
	trace clay boulders		7	SS	50/13cm												
			8	CS	-												
			9	SS	50/13cm												
227.9 6.9	End of borehole		10	SS	30/3cm												
	Samples 7, 9, 10: Sampler bouncing																
	* Borehole dry upon completion of drilling																
	■ Penetrometer test																
	C.F.H.S.A. - Denotes: Continuous Flight Hollow Stem Augers																

RECORD OF BOREHOLE No 204

1 of 1

METRIC

G.W.P. 154-98-00 LOCATION Coordinates: 5 505 308.0 N; 331 290.7 E ORIGINATED BY F.P.
 DIST 53 HWY 11 BOREHOLE TYPE Continuous Flight Hollow Stem Augers COMPILED BY A.S.
 DATUM Geodetic DATE November 19, 2008 CHECKED BY C.N.




SOIL PROFILE			SAMPLES			GROUND WATER	CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT					PLASTIC LIMIT w _p	NATURAL MOISTURE CONTENT w	LIQUID LIMIT w _L	UNIT WEIGHT γ kN/m ³	REMARKS & GRAIN SIZE DISTRIBUTION (%) GR SA SI CL
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	"N" VALUES				SHEAR STRENGTH kPa									
									○ UNCONFINED	● QUICK TRIAXIAL	+	×	FIELD VANE					
232.5 0.0	Ground Surface							20	40	60	80	100						
232.3	Topsoil																	
0.2	Silty sand		1	SS	1	∇*	232											
	Loose to Brown compact (FILL)																	
		2	SS	4														
230.4			3	SS	13		231											
2.1	Sand and gravel, with silt trace clay, trace gravel cobbles and boulders		4	SS	30/5cm		230										36 36 22 6	
	Dense to Grey Moist very dense (TILL)																	
		5	SS	41														
							229											
		6	SS	50/10cm														
																	30 46 20 4	
227.8 4.7	End of borehole		7	SS	30/10cm		228											
	Samples 4, 6, 7: Sampler bouncing																	
	* 2008 11 19																	
	∇ Water level observed during drilling																	

RECORD OF BOREHOLE No 205

1 of 1

METRIC

G.W.P. 154-98-00 LOCATION Coordinates: 5 505 307.7 N; 331 299.9 E ORIGINATED BY F.P.
 DIST 53 HWY 11 BOREHOLE TYPE Continuous Flight Hollow Stem Augers COMPILED BY A.S.
 DATUM Geodetic DATE November 19, 2008 CHECKED BY C.N.

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS *	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT					PLASTIC LIMIT w _p	NATURAL MOISTURE CONTENT w	LIQUID LIMIT w _L	UNIT WEIGHT γ kN/m ³	REMARKS & GRAIN SIZE DISTRIBUTION (%) GR SA SI CL
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	"N" VALUES			SHEAR STRENGTH kPa									
○ UNCONFINED + FIELD VANE ● QUICK TRIAXIAL × LAB VANE																	
233.4 0.0	Ground Surface							20	40	60	80	100					
233.2 0.2	Topsoil																
232.8 0.6	Cobbles and boulders		1	SS	6		233										
	End of borehole																
	Refusal on probable cobbles and boulders (possible rockfill)																
	* Borehole dry																

RECORD OF BOREHOLE No 206

1 of 1

METRIC

G.W.P. 154-98-00 LOCATION Coordinates: 5 505 305.7 N; 331 348.3 E ORIGINATED BY F.P.
DIST 53 HWY 11 BOREHOLE TYPE Continuous Flight Hollow Stem Augers COMPILED BY A.S.
DATUM Geodetic DATE November 17, 2008 CHECKED BY C.N.

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS *	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT					PLASTIC LIMIT w _p	NATURAL MOISTURE CONTENT w	LIQUID LIMIT w _L	UNIT WEIGHT γ kN/m ³	REMARKS & GRAIN SIZE DISTRIBUTION (%) GR SA SI CL			
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	"N" VALUES			SHEAR STRENGTH kPa										WATER CONTENT (%)		
								○ UNCONFINED + FIELD VANE												
								● QUICK TRIAXIAL × LAB VANE												
237.2 0.0	Ground Surface 100mm asphaltic concrete over sand, trace gravel (PAVEMENT FILL)		1	CS	-	237								○						
235.7 1.5	Silty clay, trace sand organic inclusions Firm Moist (FILL)		2	SS	8	236														
						235														
						234								○						
			3	SS	6	233														
			4	SS	6	232														
	trace gravel					231								○						
	Dark grey		5	SS	4	230														
231.9 5.3	Silt trace sand, trace gravel cobbles and boulders Compact to Grey Moist Very dense (TILL)		6	SS	30/3cm	229														
			7	SS	23									○						
	sandy		8	SS	50/8cm															
228.7 8.5	End of borehole		9	SS	50/8cm															
	Samples 6, 8, 9: Sampler bouncing																			
	* Borehole dry upon completion of drilling																			

1 of 1

METRIC

Foundation Design









[illegible]

RECORD OF BOREHOLE No 302

1 of 1

METRIC

G.W.P. 154-98-00 LOCATION Coordinates: 5 505 373.3 N; 331 227.9 E ORIGINATED BY F.P.
DIST 53 HWY 11 BOREHOLE TYPE Continuous Flight Hollow Stem Augers COMPILED BY A.S.
DATUM Geodetic DATE November 14, 2008 CHECKED BY C.N.

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT					PLASTIC LIMIT w _p	NATURAL MOISTURE CONTENT w	LIQUID LIMIT w _L	UNIT WEIGHT γ kN/m ³	REMARKS & GRAIN SIZE DISTRIBUTION (%) GR SA SI CL	
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	"N" VALUES			SHEAR STRENGTH kPa										
								○ UNCONFINED	+	FIELD VANE								
235.7 0.0	Ground Surface Silty clay, trace sand organics inclusions		1	SS	7													
235.1 0.6	Firm Brown Moist (FILL)		2	SS	10													
	Silt trace clay, trace sand		3	SS	12													
	Compact Brown Moist to wet (TILL)		4	SS	29													
	Grey		5	SS	30													
	sandy trace gravel		6	SS	50/13cm													
	Very dense		7	SS	50/5cm													
231.0 4.7	End of borehole																	
	Samples 6, 7: Sampler bouncing																	

RECORD OF BOREHOLE No 303

1 of 1

METRIC

G.W.P. 154-98-00 LOCATION Coordinates: 5 505 373.9 N; 331 254.3 E ORIGINATED BY F.P.
DIST 53 HWY 11 BOREHOLE TYPE C.F.H.S.A. + NW Casing COMPILED BY A.S.
DATUM Geodetic DATE November 14, 2008 CHECKED BY C.N.

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT					PLASTIC LIMIT w _p	NATURAL MOISTURE CONTENT w	LIQUID LIMIT w _L	UNIT WEIGHT γ kN/m ³	REMARKS & GRAIN SIZE DISTRIBUTION (%) GR SA SI CL		
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	"N" VALUES			SHEAR STRENGTH kPa											
								○ UNCONFINED		+ FIELD VANE									
235.3	Ground Surface						20	40	60	80	100								
0.0	Topsoil		1	SS	4	▽*	235							○			0 4 35 61		
234.7	Silty clay, trace sand organics inclusions		2	SS	6		234												
233.7	Firm (FILL) Moist						233								○				
1.6	Silt trace clay, trace sand sandy silt layers		3	SS	4		232								○				
	Loose to dense Brown Moist to wet sandy		4	SS	35		231								○				
	Compact to very dense		5	SS	25		230								○				
	(TILL)		6	SS	52		229								○				
230.8	Silt and sand trace clay, trace gravel		7	SS	51		228								○				4 46 41 9
4.5	Very dense Grey Moist		8	SS	57		227								○				
	(TILL)		9	SS	50/13cm										○				
	Cobbles and boulders																		**
			10	RC NQ	**												**		
			11	RC NQ	**												**		
226.1	End of borehole																		
9.2	Sample 9: Sampler bouncing																		
	* 2008 11 14																		
	▽ Water level observed during drilling																		
	** Rock core sample not recovered																		

RECORD OF BOREHOLE No 304

1 of 1

METRIC

G.W.P. 154-98-00 LOCATION Coordinates: 5 505 333.8 N; 331 337.0 E ORIGINATED BY F.P.
DIST 53 HWY 11 BOREHOLE TYPE Continuous Flight Hollow Stem Augers COMPILED BY A.S.
DATUM Geodetic DATE November 18, 2008 CHECKED BY C.N.

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT					PLASTIC LIMIT w _p	NATURAL MOISTURE CONTENT w	LIQUID LIMIT w _L	UNIT WEIGHT γ kN/m ³	REMARKS & GRAIN SIZE DISTRIBUTION (%)
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	"N" VALUES			SHEAR STRENGTH kPa									
								○ UNCONFINED		+ FIELD VANE		● QUICK TRIAXIAL					
232.7 0.0	Ground Surface						20	40	60	80	100						GR SA SI CL
232.5 0.2	Topsoil		1	CS	-									○			2 22 64 12
232.1 0.6	Silty clay, trace gravel organic inclusions													○			
	Brown (FILL)		2	SS	14									○			
	Silt, trace gravel cobbles																
	Compact Grey Moist to wet		3	SS	11									○			
	(TILL)													○			
			4	SS	19												
			5	SS	17												
228.9 3.8	Sand, with gravel some silt, trace clay cobbles and boulders		6	SS	50/10cm									○		28 49 18 5	
	Very dense Grey Moist																
	(TILL)		7	SS	25/2cm												
			8	SS	50/8cm												
	cobbles and boulders		9	RC NQ	**											**	
			10	RC NQ	**											**	
224.8 7.9	End of borehole																
	Samples 6, 7, 8: Sampler bouncing																
	* 2008 11 13																
	Water level observed during drilling																
	Water level measured after drilling																
	** Rock core sample not recovered																

METRIC

20
15 — 5 (%) STRAIN AT FAILURE
10

RECORD OF BOREHOLE No 306

1 of 1

METRIC

G.W.P. 154-98-00 LOCATION Coordinates: 5 505 318.5 N; 331 386.9 E ORIGINATED BY F.P.
 DIST 53 HWY 11 BOREHOLE TYPE Continuous Flight Hollow Stem Augers COMPILED BY A.S.
 DATUM Geodetic DATE November 11, 2008 CHECKED BY C.N.

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT					PLASTIC LIMIT w _p	NATURAL MOISTURE CONTENT w	LIQUID LIMIT w _L	UNIT WEIGHT γ kN/m ³	REMARKS & GRAIN SIZE DISTRIBUTION (%) GR SA SI CL			
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	"N" VALUES			SHEAR STRENGTH kPa										WATER CONTENT (%)		
								○ UNCONFINED		+ FIELD VANE								○		
							20	40	60	80	100									
							● QUICK TRIAXIAL													
							×													
234.1	Ground Surface																			
0.0	Topsoil																			
233.9	Sand and gravel		1	SS	7								○							
0.2	silty clay lenses																			
	Loose to Dark Wet																			
	very loose brown		2	SS	5								○							
	(FILL)																			
	Sandy silt																			
	clayey silt layers		3	SS	3								○							
232.0																				
2.1	Silt, with sand																			
	trace clay, trace gravel																			
	Compact Brown Wet		4	SS	17								○							
	(TILL)																			
			5	SS	20								○							
			6	SS	17								○							
229.6																				
4.5	Silty sand																			
	trace gravel, trace clay																			
	Compact Grey Moist		7	SS	25								○							
	(TILL)																			
			8	SS	27								○							
228.1																				
6.0	Sand																			
	with silt, trace clay																			
	Very dense Grey Moist		9	SS	50/8cm															
	(TILL)																			
226.3																				
7.8	End of borehole		10	SS	50/5cm															
			</																	


DIMENSIONS ARE IN METRES
AND/OR MILLIMETRES UNLESS
OTHERWISE SHOWN. STATIONS
IN KILOMETRES + METRES

GWP No 154-98-00

HIGHWAY 1



SHEET



(Legend Continued)

BH No	ELEVATION	COORDINATES	
		NORTHINGS	EASTINGS
1	231.5	5 505 347.8	331 236.4
2	237.3	5 505 340.7	331 226.6
3	237.3	5 505 324.3	331 286.6
4	237.3	5 505 326.6	331 293.5
5	237.3	5 505 349.5	331 229.3

(Legend Continues)

The boundaries between soil strata have been established only at Borehole locations. Between Boreholes the boundaries are assumed from geological evidence.





HYD No	11	CHECKED ON	DATE JUNE 16, 2009	DIST	53
SRW	AS	CHECKED ON	APPROVED BRG	SITE	39W-033
DRUM	NA			DWS	1

REF No. Stantec drawing: 154--98-00-B_PLAN.dwg


received on February 02, 2009

1. NOTES: CO-ORDINATES OF PREVIOUS BOREHOLES (No. 1 TO 5), DRILLED IN 1977, ARE APPROXIMATE.
2. REFER TO DRAWINGS 2 AND 3 FOR SECTIONS A-A TO E-E.
3. THIS DRAWING IS FOR SUBSURFACE INFORMATION ONLY. SURFACE DETAILS AND FEATURES ARE FOR CONCEPTUAL ILLUSTRATION.


CONT No	
GWP No 154-98-00	
MATAMSHKWA RIVER BRIDGE	
SOIL STRATA II	
	SHEET




PROFILE C-C



SECTION D-D



SECTION E-E



PROFILE C-C (CONT'D)

NOTES:

- REFER TO DRAWING 1 FOR BOREHOLE LOCATIONS PLAN AND DRAWING 2 FOR SECTIONS A-A AND B-B.
- THIS DRAWING IS FOR SUBSURFACE INFORMATION ONLY. SURFACE DETAILS AND FEATURES ARE FOR CONCEPTUAL ILLUSTRATION.

PROFILE AND SECTIONS



REF No. Stantec drawing: 154-98-00-B_PLAN.dwg
received on February 02, 2009

REVISIONS				
DATE	BY	DESCRIPTION		
Geoties No. 426-29				
AWT No. 11	AS	CHECKED CN	DATE JUNE 18, 2009	SITE 38W-033
SUBMITTAL NA	CHECKED CN	APPROVED BRG		DWG 3

— NOTE —
The boundaries between soil strata have been established only at Borehole locations. Between Boreholes the boundaries are assumed from geological evidence.

(Legend Continues)

SEE DRAWING 1 FOR DETAILS

LEGEND		
	Borehole	
	Dynamic Cone Penetration Test (Cone)	
	Borehole & Cone	
	Blows/0.3m (Std. Pen Test, 475 J / blow)	
	W L at time of investigation Nov. 2008	
	Head	
	ARTESIAN WATER	
	Encountered	
	PIEZOMETER	
BH No	ELEVATION	COORDINATES NORTHINGS EASTINGS



APPENDIX A

Record of Borehole Sheets and Foundation Drawing
(Foundation Investigation Report Contract No. 82-213)



RECORD OF BOREHOLE No 1

9

W P 236-77-00 LOCATION Sta. 380+90.0, Rt. 12.8' ORIGINATED BY C.T.J.
DIST 16 HWY 11 BOREHOLE TYPE Casing and Wash Boring COMPILED BY C.T.J.
DATUM Geodetic DATE July 30, 1978 CHECKED BY J.J.

SOIL PROFILE		SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT					PLASTIC LIMIT W _p	NATURAL MOISTURE CONTENT W	LIQUID LIMIT W _L	UNIT WEIGHT γ	REMARKS & GRAIN SIZE DISTRIBUTION (%)
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE			20	40	60	80	100					
759.3	Ground Level															
0.0	Clayey Silt, some		1	SS												
756.3	Sand, fine		2	SS												
3.0	Sandy Silt, Trace of		3	SS												
	Gravel and Clay		4	SS												
750.8	(Glacial till)															
	Dense to Very Dense															
8.5	End of Borehole					750										

*3, x³: Numbers refer to
Sensitivity

20
15 5 (%) STRAIN AT FAILURE
10

OFFICE REPORT ON SOIL EXPLORATION



Ministry of
Transportation and
Communications
Ontario

HIGHWAY ENGINEERING DIVISION-ENGINEERING MATERIALS OFFICE-SOIL MECHANICS SECTION

RECORD OF BOREHOLE No 2

10

W P 236-77-00 LOCATION Sta. 381+47.0, Lt. 10.5' ORIGINATED BY C.T.J.
DIST 16 HWY 11 BOREHOLE TYPE Continuous Flight Auger COMPILED BY C.T.J.
DATUM Geodetic DATE August 1, 1978 CHECKED BY J.J.

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT 20 40 60 80 100 SHEAR STRENGTH ○ UNCONFINED + FIELD VANE ● QUICK TRIAXIAL x LAB VANE	PLASTIC LIMIT W _p NATURAL MOISTURE CONTENT W LIQUID LIMIT W _L WATER CONTENT (%) 10 20 30	UNIT WEIGHT γ	REMARKS & GRAIN SIZE DISTRIBUTION (%) GR SA SI CL
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	'N' VALUES						
778.2	Pavement Surface										
0.0	Asphalt Reinforced Concrete										
1.5	Fill Material, Sand & Gravel, Traces of Silt & Clay, Occ. Boulders Loose		1	SS	100/	4" Bouncing					
			2	SS	10						
			3	SS	11						
			4	SS	11						0 17 49 34
162.7	Silty Clay, Traces of Sand and Gravel, Occ. Layers of Organics up to 4" Silt		5	SS	41						0 6 91 3
15.5	Silt, Tr. of Sand & Clay		6	SS	100/	6"					
	Sandy Silt, Trace of Gravel and Clay (Glacial Till)		7	SS	100/	6"					2 34 56 8
752.2	Dense to Very Dense										
26.0	End of Borehole										

OFFICE REPORT ON SOIL EXPLORATION

*3, x5: Numbers refer to
Sensitivity

20
15
10
5 (%) STRAIN AT FAILURE



Ministry of
Transportation and
Communications
Ontario

HIGHWAY ENGINEERING DIVISION-ENGINEERING MATERIALS OFFICE-SOIL MECHANICS SECTION

RECORD OF BOREHOLE No 3

11

W P 236-77-00 LOCATION Sta. 379+01.0, Lt. 9' ORIGINATED BY C.T.J.
DIST 16 HWY 11 BOREHOLE TYPE Continuous Flight Auger COMPILED BY C.T.J.
DATUM Geodetic DATE August 1, 1978 CHECKED BY E.J.

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT					PLASTIC LIMIT W _p	NATURAL MOISTURE CONTENT W	LIQUID LIMIT W _L	UNIT WEIGHT γ	REMARKS & GRAIN SIZE DISTRIBUTION (%)
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	'N' VALUES			20	40	60	80	100					
778.3	Pavement Surface																
778.3	Asphalt Reinforced Concrete																
778.3	Void																
778.3	Reinforced Concrete																
3.6	Fill Material, Sand & Gravel, Traces of Silt & Clay, Occasional Cobbles & Wood Inclusions. Vary Loose to Compact		1	SS	4		770										41 52 6 1
			2	SS	7												5 11 54 30
			3	SS	19												
			4	SS	22												
762.7	Silty Clay, Trace of Sand & Gravel. Very Stiff		5	SS	23												
15.6	Sandy Silt, Trace of Gravel and Clay, Occ. Cobbles, Very Dense Boulder at elev. 758 (Glacial Till)		6	SS	53		760										
	Sandy Gravel		7	SS	100/5"												51 29 17 3
748.2			8	SS	100/15"		750										5 49 42 4
30.1	End of Borehole																

*3, *5: Numbers refer to
Sensitivity

20
15
10
5
0
5
10
15
20
(%) STRAIN AT FAILURE

OFFICE REPORT ON SOIL EXPLORATION



RECORD OF BOREHOLE No 4

12

W P 236-77-00 LOCATION Sta. 378+88.0, Rt. 10.5' ORIGINATED BY C.T.J.
DIST 16 HWY 11 BOREHOLE TYPE Continuous Flight Auger COMPILED BY C.T.J.
DATUM Geodetic DATE August 1 & 2, 1978 CHECKED BY A.S.

SOIL PROFILE		SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT 20 40 60 80 100 SHEAR STRENGTH ○ UNCONFINED + FIELD VANE ● QUICK TRIAXIAL x LAB VANE	PLASTIC LIMIT W _p NATURAL MOISTURE CONTENT W LIQUID LIMIT W _L WATER CONTENT (%) 10 20 30	UNIT WEIGHT γ	REMARKS & GRAIN SIZE DISTRIBUTION (%) GR SA SI CL
ELEV. DEPTH	DESCRIPTION	STRAT. PLOT	NUMBER	TYPE						
778.3	Pavement Surface									
1.4	Asphalt Reinforced Concrete									
2.9	Fill Material, Sand & Gravel, Traces of Silt & Clay, Occ. Cobbles & Wood Inclusions, Very Loose to Compact		1	SS	4					
			2	SS	9					
			3	SS	15					
	Silty Clay, Trace of Sand & Gravel, Occ. Layers of Organics Up to 4"		4	SS	13					
757.8	Stiff		5	SS	53					
20.5	Sandy Silt, Trace of Gravel and Clay Very Dense (Glacial Till)		6	SS	100/6"					
749.3										
29.0	Refusal to Augering Probable Boulders									
	*Note: Water Level Not Established									

Cons. Sta. 378+82, 22' Rt.

120/10"

45 48 5 2

5 43 46 6

OFFICE REPORT ON SOIL EXPLORATION



RECORD OF BOREHOLE No. 5

W P 236-77-00 LOCATION Sta. 381+22.5 R.L. 10.5' ORIGINATED BY C.T.J.
DIST 16 HWY 11 BOREHOLE TYPE Continuous Flight Auger COMPILED BY C.T.J.
DATUM Geodetic DATE August 1 & 2, 1978 CHECKED BY aj

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT					PLASTIC LIMIT W _p	NATURAL MOISTURE CONTENT W	LIQUID LIMIT W _L	UNIT WEIGHT γ	REMARKS & GRAIN SIZE DISTRIBUTION (%)
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	'N' VALUES			20	40	60	80	100					
778.3	Pavement Surface																
778.3	Asphalt Reinforced																
1.2	Fill Material Concrete					*											
	Sand & Gravel		1	SS	9												
	Traces of Silt & Clay																
	Occasional Cobbles																
	Loose																
	Clayey Silt		2	SS	22												
	Silty Clay, Trace of Sand		3	SS	24												
763.3	Occ. Layer of Organics up to 1" Very Silty																
15.0	Silt, Traces of Sand & Clay, Dense to Very Dense		4	SS	66												0 6 56 38
	Sandy Silt, Trace of Gravel and Clay Occasional Cobble Very Dense (Glacial Till)		5	SS	38												0 6 91 3
			6	SS	130												
			7	SS	1007	5" Bouncing											4 35 54 7
745.3																	
33.0	Refusal to Augering Probable Boulder																
	*Note: Water Level Not Established																

