



December 23, 2013

FOUNDATION INVESTIGATION REPORT

**LITTLE EAST RIVER BRIDGE NO. 1, SITE NO. 44-174
HIGHWAY 592 - REPLACEMENT OF SIX STRUCTURES
MINISTRY OF TRANSPORTATION, ONTARIO
GWP 5265-07-00 WP 5265-07-01**

Submitted to:

Morrison Hershfield Limited
Suite 600, 235 Yorkland Blvd.
Toronto, Ontario
M2J 1T1



REPORT

GEOCREs No: 31E-330

Report Number: 11-1111-0149-1

Distribution:

- 3 Copies – Ministry of Transportation, Ontario, North Bay, Ontario (Northeastern Region)
- 1 Copy – Ministry of Transportation, Ontario, Downsview, Ontario (Foundations Section)
- 2 Copies – Morrison Hershfield Limited, Toronto, Ontario
- 2 Copies – Golder Associates Ltd., Mississauga, Ontario



Table of Contents

PART A – FOUNDATION INVESTIGATION REPORT

1.0 INTRODUCTION.....	1
2.0 SITE DESCRIPTION.....	1
3.0 INVESTIGATION PROCEDURES	1
3.1 Foundation Investigation.....	1
4.0 SITE GEOLOGY AND SUBSURFACE CONDITIONS	3
4.1 Regional Geology	3
4.2 Subsurface Conditions.....	3
4.2.1 Asphalt.....	4
4.2.2 Fill	4
4.2.3 Organic Sand.....	4
4.2.4 Silt and Sand to Sand	4
4.2.5 Clayey Silt.....	5
4.2.6 Sand and Gravel to Sandy Gravel	5
4.3 Groundwater Conditions	6
5.0 CLOSURE	7

DRAWINGS

Drawing 1	Key Map
Drawing 2	Borehole Locations and Soil Strata

APPENDICES

APPENDIX A Record of Borehole Sheets

Lists of Symbols and Abbreviations	
Record of Boreholes	B1-01 to B1-05

APPENDIX B Laboratory Test Results and Cobbles/Boulders Core Photographs

Figure B1	Pieces of Wood Photographs – Boreholes B1-03, B1-04 and B1-05
Figure B2	Grain Size Distribution – Sand to Gravelly Sand (Fill)
Figure B3	Grain Size Distribution – Organic Sand
Figure B4	Grain Size Distribution – Silt and Sand to Sand
Figure B5	Grain Size Distribution – Clayey Silt
Figure B6	Plasticity Chart – Clayey Silt
Figure B7	Cobbles and Boulders Photograph – Boreholes B1-02 and B1-05
Figure B8	Grain Size Distribution – Sand and Gravel to Sandy Gravel



PART A

FOUNDATION INVESTIGATION REPORT

LITTLE EAST RIVER BRIDGE NO. 1 – SITE NO. 44-174

HIGHWAY 592 – REPLACEMENT OF SIX STRUCTURES

MINISTRY OF TRANSPORTATION, ONTARIO

GWP 5265-07-00; WP 5265-07-01



1.0 INTRODUCTION

Golder Associates Ltd. (Golder) has been retained by Morrison Hershfield Limited (MH) on behalf of the Ministry of Transportation, Ontario (MTO) to provide detail foundation engineering services for the replacement of Little East River Bridge No. 1 (Site No. 44-174) over Highway 592 in Huntsville, Ontario. The proposed work is part of the replacement of six bridge structures along Highway 592. The Little East River Bridge No. 1 is located approximately 75 m south of Savage Settlement Road and approximately 1 km north of the Highway 11/Novar Road interchange in Novar, Ontario. The location of the existing bridge structure along Highway 592 is shown on the Key Map on Drawing 1.

The Terms of Reference (TOR) for the foundation investigation are outlined in MTO's Request for Proposal, dated September 2011. Golder's proposal (Scope of Work) for foundation engineering services associated with the Little East River Bridge No. 1 structure is contained in Section 6.8 of MH's Technical Proposal for this assignment. The work was carried out in accordance with Golder's Project Specific Supplementary Specialty Plan for foundation engineering services, dated March 21, 2012.

This report addresses the investigation carried out for the Little East River Bridge No. 1 structure and the associated approach embankments only.

The purpose of this investigation is to establish the subsurface conditions at the replacement bridge structure location, including the associated approach embankments, by borehole drilling and coring techniques, in situ testing and laboratory testing on selected soil samples. The borehole locations for this investigation were surveyed by Tulloch Geomatics Inc. (Tulloch), a professional surveying company retained by MH. The investigation area is shown in plan on Drawing 2.

2.0 SITE DESCRIPTION

The existing Highway 592 alignment is oriented generally in a south-north direction.

In general, the topography along Highway 592 consists of rolling terrain, including lakes, low-lying swamps containing areas of standing water, sparsely to densely populated tree covered areas. Land use in some areas consists of residential/recreational communities. The existing bridge is a single-span rigid frame structure with a span length of 6.1 m. The bridge structure and associated approach embankments are situated on a relatively flat, sparsely treed area surrounded by residential/recreational properties to the north and south and with Little East River flowing easterly at this location. The existing ground surface within the limits of the proposed structure and approach embankments is at about Elevation 322.5 m, referenced to Geodetic datum. The existing Highway 592 south and north approach embankments along the centreline are at Elevations 322.6 m and 322.5 m, respectively.

3.0 INVESTIGATION PROCEDURES

3.1 Foundation Investigation

The field work for the proposed bridge structure was carried out between May 14 and June 6, 2013 during which time a total of five boreholes were advanced at the location of the structure foundation footprints and approach embankments. In addition, Dynamic Cone Penetration Tests were carried out from the bottom of Borehole B1-02 and from the ground surface adjacent to Borehole B1-03 to determine the depth to refusal at



FOUNDATION REPORT - LITTLE EAST RIVER BRIDGE NO. 1 - HIGHWAY 592 GWP 5265-07-00 WP 5265-07-01

these locations. A summary of the respective boreholes advanced at each foundation element and approach embankment is presented below.

Foundation Unit	Borehole
South Approach Embankment	B1-01
South Abutment	B1-02
North Abutment	B1-03 and B1-05
North Approach Embankment	B1-04

The results of the borehole investigation and dynamic cone penetration tests are presented on the Record of Borehole sheets in Appendix A. The boreholes were advanced at the locations shown in plan on Drawing 2.

The field borehole investigation was carried out using a truck-mounted CME 55 drill rig supplied and operated by Landcore Drilling of Chelmsford, Ontario. The boreholes were advanced through the overburden using 120 mm and 203 mm outer diameter (O.D.) continuous flight hollow-stem augers and 'NW' casing. Soil samples were obtained at intervals of depth of about 0.75 m and 3.0 m, using a 50 mm outer diameter (O.D.) split-spoon sampler driven by an automatic hammer in accordance with Standard Penetration Test (SPT) procedures (ASTM D1586 – Standard Test Method for Standard Penetration Test). Cobbles and boulders were cored using an 'NQ' size rock core barrel. The boreholes and DCPTs were advanced to depths of up to about 23.5 m and 25.4 m below existing ground surface, respectively. The DCPTs were terminated on refusal to further dynamic cone penetration.

The groundwater conditions in the open boreholes were observed during and upon completion of drilling operations, and a standpipe piezometer was installed in Borehole B1-04 to permit monitoring of the water level at that location. The piezometers consist of 38 mm diameter PVC pipe, with a slotted screen surrounded with sand sealed at a select depth within the borehole. The borehole and annulus surrounding the piezometer pipe above the screen and sand pack were backfilled to the surface with bentonite pellets/grout. Piezometer installation details and water level readings are described on the Record of Borehole sheets in Appendix A. All open boreholes were backfilled with cement grout by tremie technique upon completion and the piezometer in Borehole B1-04 was also abandoned with cement grout by tremie technique on May 15, 2013 in accordance with Ontario Regulation 903, Wells (as amended).

The field work was observed by a member of our engineering and technical staff, who located the boreholes, arranged for the clearance of underground services, observed the drilling and sampling operations, logged the boreholes, and examined and cared for the soil samples. The soil samples were identified in the field, placed in appropriate containers, labelled and transported to our Mississauga geotechnical laboratory where samples underwent further visual examination and laboratory testing. All of the laboratory tests were carried out to MTO and/or ASTM Standards, as appropriate. Classification testing (water content, organic content, grain size distribution and Atterberg limits) was carried out on selected samples. The results of the laboratory testing are included in Appendix B.

The as-drilled borehole locations and ground surface elevations were surveyed by Tulloch. The locations given in the Record of Borehole sheets and shown on Drawing 2 are positioned relative to MTM NAD 83 northing and easting coordinates and the ground surface elevations are referenced to Geodetic datum. The borehole locations, ground surface elevations and drilled depths are summarized below.



FOUNDATION REPORT - LITTLE EAST RIVER BRIDGE NO. 1 - HIGHWAY 592 GWP 5265-07-00 WP 5265-07-01

Borehole	Location (MTM NAD 83)		Ground Surface Elevation	Borehole / DCPT Depth
	Northing	Easting		
B1-01	5035109.1	324438.5	322.6 m	8.2 m
B1-02	5035127.1	324448.4	322.5 m	19.8 m / 25.4 m
B1-03	5035139.4	324447.6	322.5 m	6.1 m / 18.9 m
B1-04	5035156.5	324456.9	322.5 m	9.8 m
B1-05	5035139.6	324452.1	322.5 m	23.5 m

4.0 SITE GEOLOGY AND SUBSURFACE CONDITIONS

4.1 Regional Geology

As delineated in *The Physiography of Southern Ontario*¹, this section of Highway 592 lies within the physiographic region known as the “Number 11 Strip”, with portions of Highway 592 in contact with the “Georgian Bay Fringe” region. The Number 11 Strip is a narrow belt that extends from Gravenhurst to North Bay and is characterized by deposits of sand, silt and clay, together with more recent swamp deposits between rock knobs and ridges. The bedrock in the area is typically highly deformed gneiss of the Moon River Domain of the Central Gneiss Belt, a subdivision of the Grenville Structural Province (Geology of Ontario, 1991)².

4.2 Subsurface Conditions

The detailed subsurface soil and groundwater conditions as encountered in the boreholes advanced during this investigation, together with the results of the laboratory tests carried out on selected soil samples, are provided in Appendix A and B, respectively. The results of the in situ field tests (i.e. SPT ‘N’-values) as presented on the Record of Borehole sheets and in Section 4.2 are uncorrected. The stratigraphic boundaries shown on the Record of Borehole sheets and on the profile and cross-section on Drawing 2 are inferred from non-continuous sampling, observations of drilling progress and the results of Standard Penetration Test (SPTs). These boundaries, therefore, represent transitions between soil types rather than exact planes of geological change. Further, subsurface conditions will vary between and beyond the borehole locations. It should be noted that the interpreted stratigraphy shown on Drawing 2 is a simplification of the subsurface conditions.

In general, the subsurface conditions in the area of the proposed bridge structure consist of a surficial layer of asphalt over a deposit of fill associated with the Highway 592 embankments. The fill is underlain by a near surface layer of organic sand in places, and by deposits of silt and sand to sand and/or clayey silt. These deposits are in turn underlain by a deposit of sand and gravel to sandy gravel.

A detailed description of the subsurface conditions encountered in the boreholes at the abutments and approach embankments is provided in the following sections.

¹ Chapman, L.J. and D. F. Putnam, 1984. *The Physiography of Southern Ontario*, Ontario Geological Survey, Special Volume 2, Third Edition. Accompanied by Map P. 2715, Scale 1:600,000.

² Ontario Geological Society. 1991. *Geology of Ontario*, Special Volume 4, Part 2. Eds. P.C. Thurston, H.R. Williams, R.H. Sutcliffe and G.M. Stott. Ministry of Northern Development and Mines, Ontario.



4.2.1 Asphalt

An approximately 25 mm to 90 mm thick layer of asphalt was encountered at the ground surface in all boreholes.

4.2.2 Fill

A fill deposit comprised of brown sand and gravel to gravelly sand to sand some gravel was encountered in all boreholes below the asphalt layer. The gravelly sand and sand some gravel portions of the fill contain trace to some silt, trace clay, organics. Pieces of wood were encountered within the fill deposit at the location of north abutment in Boreholes B1-03, B1-04 and B1-05, as shown on Figure B1 in Appendix B, and are inferred to be remnants of an existing corduroy roadbed. The top of the fill deposit is at between Elevations 322.5 m and 322.4 m and the thickness of the deposit ranges from 1.4 m to 3.7 m.

The SPT 'N'-values measured within the fill deposit range from 8 blows to 30 blows per 0.3 m of penetration, and 16 blows per 0.2 m of penetration, indicating a loose to compact relative density. In Boreholes B1-03 and B1-04, it is inferred that the split-spoon sampler was bouncing on wood pieces while obtaining the SPT 'N'-values for Samples 2 and 3, as such, the SPT 'N'-values are considered not representative of the fill material's relative density.

The natural water content measured on eight samples of the fill ranges from about 4 per cent to 27 per cent.

The organic content measured on two samples of fill is about 3 per cent and 7 per cent, with the greater organic content measured on a sample containing wood pieces.

The results of grain size distribution tests completed on four samples of the fill deposit are shown on Figure B2 in Appendix B.

4.2.3 Organic Sand

An approximately 0.8 m thick layer of dark brown organic sand, trace to some gravel, trace to some silt was encountered underlying the fill deposit in Borehole B1-05. The top of the deposit was encountered at Elevation 320.3 m

An SPT 'N'-value of 5 blows per 0.3 m of penetration was measured within this layer, indicating a loose relative density.

The natural water content measured on a sample of the organic sand layer is about 31 per cent.

The result of a grain size distribution test completed on a sample of the organic sand layer is shown on Figure B3 in Appendix B.

4.2.4 Silt and Sand to Sand

A deposit of non-cohesive soil comprised of brown to grey silt and sand to silty sand to sand trace to some silt was encountered underlying the fill deposit in Boreholes B1-01 and B1-02. The deposit contains trace to some clay and trace gravel as well as clayey silt seams within the upper 1.9 m portion of this deposit in Borehole B1-01. The top of the silt and sand to sand deposit is at Elevations 318.9 m and 319.5 m, and the



thickness of the deposit is 4.5 m and 2.6 m in Boreholes B1-01 and B1-02, respectively. Borehole B1-01 was terminated within this deposit at a depth of 8.2 m below ground surface (Elevation 314.4 m)

The SPT 'N'-values measured within this deposit range from 4 blows to 11 blows per 0.3 m of penetration, indicating a loose to compact relative density.

The natural water content measured on four samples of this deposit ranges from about 20 per cent and 24 per cent.

The results of grain size distribution tests completed on four samples of the deposit are shown on Figure B4 in Appendix B.

4.2.5 Clayey Silt

A deposit of grey clayey silt was encountered underlying the silt and sand deposit in Borehole B1-02, below the fill deposit in Borehole B1-03 and below the organic sand layer in Borehole B1-05. The deposit generally contains trace to some sand. The top of the clayey silt deposit was encountered between Elevations 319.5 m and 316.9 m and the thickness of deposit varies between 1.3 m and 2.6 m.

The SPT 'N'-values measured within this deposit range from about 3 blows to 7 blows per 0.3 m of penetration, suggesting a soft to firm consistency.

The natural water content measured on five samples of the deposit ranges from about 25 per cent to 36 per cent.

The results of grain size distribution tests completed on two samples of the clayey silt deposit are shown on Figure B5 in Appendix B.

Atterberg limits tests were carried out on three samples of the clayey silt deposit and measured liquid limits ranging from about 26 per cent to 31 per cent, plastic limits ranging from about 17 per cent to 21 per cent and plasticity indices ranging from about 9 per cent to 10 per cent. The results of Atterberg limits tests are shown on plasticity chart on Figure B6 in Appendix B and indicate that the material is classified as clayey silt of low plasticity.

4.2.6 Sand and Gravel to Sandy Gravel

A deposit of brown to grey sand and gravel to sandy gravel was encountered underlying the clayey silt deposit in Boreholes B1-02, B1-03 and B1-05 and below the organic sand layer in Borehole B1-04. The top of the deposit ranges from Elevations 319.5 m to 314.3 m and the thickness of the deposit ranges from 0.9 m to 19.2 m. Boreholes B1-02 to B1-05 were terminated within this deposit between Elevations 316.4 m and 299.0 m. The DCPTs advanced from the bottom of the sampled Borehole B1-02 (at a depth of 19.8 m below ground surface (Elevation 302.7 m)) and adjacent to Borehole B1-03 penetrated 5.6 m and 13.7 m into this deposit (based on the resistance to dynamic cone penetration) and is inferred to terminate within this deposit at a depth of 25.4 m and 18.9 m below ground surface (Elevations 297.1 m and 303.6 m), respectively.

The sand and gravel to sandy gravel deposit generally contains trace to some silt, trace clay and the upper 0.9 m portion of the deposit contains clayey silt seams in Borehole B1-05. Cobbles and/or boulders were encountered at varying depths throughout the deposit and were cored using an 'NQ' size rock core barrel as



FOUNDATION REPORT - LITTLE EAST RIVER BRIDGE NO. 1 - HIGHWAY 592 GWP 5265-07-00 WP 5265-07-01

summarized below. In general, the sizes range from about 107 mm to 671 mm. The photographs of the recovered cobbles and boulders are shown on Figure B7 in Appendix B.

Foundation Element/ Approach Embankment	Borehole	Top Elevation of Cored Cobbles and/or Boulders	Thickness
South Abutment	B1-02	313.0 m	0.9 m
		311.8 m	1.5 m
		309.4 m	0.3 m
		307.7 m	0.4 m
		304.1 m	1.4 m
North Abutment	B1-05	317.3 m	0.7 m
		315.5 m	0.6 m
		311.2 m	0.9 m
		309.4 m	0.3 m
		306.3 m	0.6 m
North Approach Embankment	B1-04	304.7 m	0.5 m
		317.2 m	0.8 m
		315.5 m	0.3 m

The SPT 'N'-values measured within the sand and gravel to sandy gravel deposit typically range from about 10 blows to 46 blows per 0.3 m of penetration, indicating a compact to dense relative density. SPT 'N'-values of about 34 blows to 50 blows per 0.15 m of penetration were recorded prior to split-spoon sampler refusal on cobbles and boulders within this deposit. The DCPT advanced from the bottom of Borehole B1-02 extends to effective refusal at 30 blows per 0.13 m of penetration and noticeable bouncing of the drive hammer, while the DCPT advanced adjacent to Borehole B1-03 encountered effective refusal at greater than 137 blows per 0.3 m of penetration. The Total Core Recovery of the cored cobbles/boulders samples generally ranges between about 20 per cent and 100 per cent, except in few instances where percentage of recovery was not recorded.

The natural water content measured on ten samples of the deposit ranges from about 6 per cent to 14 per cent.

The results of grain size distribution tests completed on six samples of the sand and gravel to sandy gravel deposit are shown on Figure B8 in Appendix B.

4.3 Groundwater Conditions

In general, the soil samples taken in the boreholes were moist to wet. During the drilling operations, artesian groundwater conditions were noted in Boreholes B1-02 and B1-05 when advancing the casing between depths of 5.2 m and 22.3 m below ground surface (between Elevations 317.3 m and 300.2 m) and in Borehole B1-03 upon completion of the dynamic cone penetration test at a depth of 18.9 m below ground surface (Elevation 303.6 m). The series of groundwater levels recorded in the drill casing during and upon completion of drilling/penetration were measured at depths ranging from 0.3 m to 0.8 m above ground surface (Elevations 322.8 m to 323.3 m). The groundwater levels measured in the open boreholes upon completion of drilling range from about 1.0 m to 1.6 m below ground surface (Elevations 321.5 m and 321.0 m) and 0.8 m above ground surface (Elevation 323.3 m).



FOUNDATION REPORT - LITTLE EAST RIVER BRIDGE NO. 1 - HIGHWAY 592 GWP 5265-07-00 WP 5265-07-01

A standpipe piezometer was installed in Borehole B1-04 to allow monitoring of the groundwater level at the site. The water level in the piezometer was monitored for five hours upon completion of the installation and then the piezometer was decommissioned. Details of the piezometer installation are shown on the Record of Borehole No. B1-04 in Appendix A, and the groundwater level measured in the piezometer is summarized below.

Borehole	Ground Surface Elevation	Depth to Water Level	Groundwater Elevation	Date of Measurement
B1-04	322.5 m	-0.1 m	322.6 m ¹	May 15, 2013

Notes:

1. Artesian Conditions

It should be noted that groundwater levels in the area are subject to seasonal fluctuations and precipitation events, and should be expected to be higher during wet periods of the year.

5.0 CLOSURE

Mr. Indulis Dumpis, a senior technician with Golder, directed the drilling program. This report was prepared by Mr. Al Varshoi, M.E.Sc., and reviewed by Ms. Veronica Ayetan, P.Eng., a geotechnical engineer with Golder. Mr. Jorge M. A. Costa, P.Eng., Golder's Designated MTO Contact for this project and Principal with Golder, conducted an independent quality control review of the report.



Report Signature Page

Al Varshoi, M.E.Sc,
Geotechnical Engineering Group



T. Veronica Ayetan, P. Eng.
Geotechnical Engineer




Jorge M. A. Costa, P. Eng.
Designated MTO Contact, Principal

AW/TVA/CN/JMAC/sm


n:\active\2011\11-1111-0149 mh - highway 592 - huntsville\reporting\verb no. 1\final\11-1111-0149-1 rpt 13dec23 fidr little east river bridge no.1.docx



DRAWINGS




METRIC
DIMENSIONS ARE IN METRES AND/OR
MILLIMETRES UNLESS OTHERWISE SHOWN.
STATIONS IN KILOMETRES + METRES.

CONT No. WP No. 5265-07-01		 SHEET
HIGHWAY 592 REPLACEMENT OF SIX STRUCTURES KEY MAP		



Golder Associates Ltd.
MISSISSAUGA, ONTARIO, CANADA




N.T.S




REFERENCE
Base data - MNR NRVIS, obtained 2004, CANMAP v2006.4 Produced by
Golder Associates Ltd. under licence from Ontario Ministry of Natural
Resources

NO.	DATE	BY	REVISION	
Geocres No. 31E-330				
HWY. 592		PROJECT NO. 11-1111-0149		DIST.
SUBM'D. AV		CHKD. CN	DATE: Dec. 2013	SITE:
DRAWN: JFC		CHKD.	APPD.	DWG. 1



PLAN

SCALE
2.5 0 2.5 5 m



CENTRELINE PROFILE

SCALE
2.5 0 2.5 5 m


METRIC
DIMENSIONS ARE IN METRES AND/OR
MILLIMETRES UNLESS OTHERWISE SHOWN.
STATIONS IN KILOMETRES + METRES.

CONT No.
WP No. 5265-07-01

HIGHWAY 592
LITTLE EAST RIVER BRIDGE #1
BOREHOLE LOCATIONS AND SOIL STRATA



Golder Associates Ltd.
MISSISSAUGA, ONTARIO, CANADA



KEY PLAN

SCALE
1.2 0 1.2 2.4 km

LEGEND

- Borehole - Current Investigation
- Seal
- Piezometer
- N Standard Penetration Test Value
- 16 Blows/0.3m unless otherwise stated (Std. Pen. Test, 475 j/blow)
- REC Total core recovery
- WL in piezometer, measured on May 14, 2013
- WL upon completion of drilling
- R Refusal

BOREHOLE CO-ORDINATES			
No.	ELEVATION	NORTHING	EASTING
B1-01	322.6	5035109.1	324438.5
B1-02	322.5	5035127.1	324448.4
B1-03	322.5	5035139.4	324447.6
B1-04	322.5	5035156.5	324456.9
B1-05	322.5	5035139.6	324452.1

NOTES

This drawing is for subsurface information only. The proposed structure details/works are shown for illustration purposes only and may not be consistent with the final design configuration as shown elsewhere in the Contracts Documents.

The boundaries between soil strata have been established only at borehole locations. Between boreholes the boundaries are assumed from geological evidence.

The complete Foundation Investigation and Design Report for this project and other related documents may be examined at the Materials Engineering and Research Office, Downsview. Information contained in this report and related documents is specifically excluded in accordance with Section GC 2.01 of OPS General Conditions.

REFERENCE

Base plans provided in digital format by MH, drawing file nos. X1114246_44-174_44-175_44-176align.dwg, x1114246_44177align.dwg, x1114246_44178_44166align.dwg and X1114246_44-174_44-175_44-176base.dwg, x1114246_44177base.dwg and x1114246_44178_44166base.dwg, received June 11, 2013 and General Arrangement Plan and Profile file no. 44174-01.dwg, received November 07, 2013.

NO.	DATE	BY	REVISION
Geocres No. 31E-330			
HWY. 592		PROJECT NO. 11-1111-0149	
SUBM'D. AV		DIST.	
CHKD. TVA		DATE: Dec. 2013	
DRAWN: JFC		SITE: 44-174	
CHKD.		APPD. CN/JMAC	
		DWG. 2	





APPENDIX A

Record of Borehole Sheets



LIST OF SYMBOLS

Unless otherwise stated, the symbols employed in the report are as follows:

I. GENERAL

π	3.1416
$\ln x$,	natural logarithm of x
\log_{10}	x or log x, logarithm of x to base 10
g	acceleration due to gravity
t	time
FoS	factor of safety

II. STRESS AND STRAIN

γ	shear strain
Δ	change in, e.g. in stress: $\Delta \sigma$
ε	linear strain
ε_v	volumetric strain
η	coefficient of viscosity
ν	Poisson's ratio
σ	total stress
σ'	effective stress ($\sigma' = \sigma - u$)
σ'_{vo}	initial effective overburden stress
$\sigma_1, \sigma_2, \sigma_3$	principal stress (major, intermediate, minor)
σ_{oct}	mean stress or octahedral stress $= (\sigma_1 + \sigma_2 + \sigma_3)/3$
τ	shear stress
u	porewater pressure
E	modulus of deformation
G	shear modulus of deformation
K	bulk modulus of compressibility

III. SOIL PROPERTIES

(a)	Index Properties
$\rho(\gamma)$	bulk density (bulk unit weight)*
$\rho_d(\gamma_d)$	dry density (dry unit weight)
$\rho_w(\gamma_w)$	density (unit weight) of water
$\rho_s(\gamma_s)$	density (unit weight) of solid particles
γ'	unit weight of submerged soil ($\gamma' = \gamma - \gamma_w$)
D_R	relative density (specific gravity) of solid particles ($D_R = \rho_s / \rho_w$) (formerly G_s)
e	void ratio
n	porosity
S	degree of saturation

(a) Index Properties (continued)

w	water content
w_l or LL	liquid limit
w_p or PL	plastic limit
I_p or PI	plasticity index = $(w_l - w_p)$
w_s	shrinkage limit
I_L	liquidity index = $(w - w_p) / I_p$
I_C	consistency index = $(w_l - w) / I_p$
e_{max}	void ratio in loosest state
e_{min}	void ratio in densest state
I_D	density index = $(e_{max} - e) / (e_{max} - e_{min})$ (formerly relative density)

(b) Hydraulic Properties

h	hydraulic head or potential
q	rate of flow
v	velocity of flow
i	hydraulic gradient
k	hydraulic conductivity (coefficient of permeability)
j	seepage force per unit volume

(c) Consolidation (one-dimensional)

C_c	compression index (normally consolidated range)
C_r	recompression index (over-consolidated range)
C_s	swelling index
C_α	secondary compression index
m_v	coefficient of volume change
C_v	coefficient of consolidation (vertical direction)
C_h	coefficient of consolidation (horizontal direction)
T_v	time factor (vertical direction)
U	degree of consolidation
σ'_p	pre-consolidation stress
OCR	over-consolidation ratio = σ'_p / σ'_{vo}

(d) Shear Strength

τ_p, τ_r	peak and residual shear strength
ϕ'	effective angle of internal friction
δ	angle of interface friction
μ	coefficient of friction = $\tan \delta$
c'	effective cohesion
c_u, s_u	undrained shear strength ($\phi = 0$ analysis)
p	mean total stress $(\sigma_1 + \sigma_3)/2$
p'	mean effective stress $(\sigma'_1 + \sigma'_3)/2$
q	$(\sigma_1 - \sigma_3)/2$ or $(\sigma'_1 - \sigma'_3)/2$
q_u	compressive strength $(\sigma_1 - \sigma_3)$
S_t	sensitivity

* Density symbol is ρ . Unit weight symbol is γ where $\gamma = \rho g$ (i.e. mass density multiplied by acceleration due to gravity)

Notes: 1
2

$\tau = c' + \sigma' \tan \phi'$
shear strength = (compressive strength)/2



LIST OF ABBREVIATIONS

The abbreviations commonly employed on Records of Boreholes, on figures and in the text of the report are as follows:

I. SAMPLE TYPE

AS	Auger sample
BS	Block sample
CS	Chunk sample
DS	Denison type sample
FS	Foil sample
RC	Rock core
SC	Soil core
SS	Split-spoon
ST	Slotted tube
TO	Thin-walled, open
TP	Thin-walled, piston
WS	Wash sample

II. PENETRATION RESISTANCE

Standard Penetration Resistance (SPT), N:

The number of blows by a 63.5 kg. (140 lb.) hammer dropped 760 mm (30 in.) required to drive a 50 mm (2 in.) drive open sampler for a distance of 300 mm (12 in.)

Dynamic Cone Penetration Resistance; N_d :

The number of blows by a 63.5 kg (140 lb.) hammer dropped 760 mm (30 in.) to drive uncased a 50 mm (2 in.) diameter, 60° cone attached to "A" size drill rods for a distance of 300 mm (12 in.).

PH: Sampler advanced by hydraulic pressure

PM: Sampler advanced by manual pressure

WH: Sampler advanced by static weight of hammer

WR: Sampler advanced by weight of sampler and rod

Piezo-Cone Penetration Test (CPT)

A electronic cone penetrometer with a 60° conical tip and a project end area of 10 cm² pushed through ground at a penetration rate of 2 cm/s. Measurements of tip resistance (Q_t), porewater pressure (PWP) and friction along a sleeve are recorded electronically at 25 mm penetration intervals.

III. SOIL DESCRIPTION

(a) Non-Cohesive (Cohesionless) Soils

Density Index	N
Relative Density	Blows/300 mm or Blows/ft
Very loose	0 to 4
Loose	4 to 10
Compact	10 to 30
Dense	30 to 50
Very dense	over 50

(b) Cohesive Soils Consistency

	c_u, s_u	
	kPa	psf
Very soft	0 to 12	0 to 250
Soft	12 to 25	250 to 500
Firm	25 to 50	500 to 1,000
Stiff	50 to 100	1,000 to 2,000
Very stiff	100 to 200	2,000 to 4,000
Hard	over 200	over 4,000

IV. SOIL TESTS

w	water content
w _p	plastic limit
w _l	liquid limit
C	consolidation (oedometer) test
CHEM	chemical analysis (refer to text)
CID	consolidated isotropically drained triaxial test ¹
CIU	consolidated isotropically undrained triaxial test with porewater pressure measurement ¹
D _R	relative density (specific gravity, G_s)
DS	direct shear test
M	sieve analysis for particle size
MH	combined sieve and hydrometer (H) analysis
MPC	Modified Proctor compaction test
SPC	Standard Proctor compaction test
OC	organic content test
SO ₄	concentration of water-soluble sulphates
UC	unconfined compression test
UU	unconsolidated undrained triaxial test
V	field vane (LV-laboratory vane test)
γ	unit weight

Note: 1 Tests which are anisotropically consolidated prior to shear are shown as CAD, CAU.

V. MINOR SOIL CONSTITUENTS

Per cent by Weight	Modifier	Example
0 to 5	Trace	Trace sand
5 to 12	Trace to Some (or Little)	Trace to some sand
12 to 20	Some	Some sand
20 to 30	(ey) or (y)	Sandy
over 30	And (non-cohesive (cohesionless)) or With (cohesive)	Sand and Gravel Silty Clay with sand / Clayey Silt with sand

PROJECT <u>11-1111-0149</u>		RECORD OF BOREHOLE No B1-01		SHEET 1 OF 1		METRIC	
W.P. <u>5265-07-01</u>		LOCATION <u>N 5035109.1 ; E 324438.5</u>		ORIGINATED BY <u>ID</u>			
DIST <u> </u> HWY <u>592</u>		BOREHOLE TYPE <u>120 mm O.D. Hollow Stem Augers and NW Casing</u>		COMPILED BY <u>AV</u>			
DATUM <u>Geodetic</u>		DATE <u>May 21, 2013</u>		CHECKED BY <u>TVA</u>			

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT					PLASTIC LIMIT NATURAL MOISTURE LIQUID LIMIT CONTENT			UNIT WEIGHT γ kN/m³	REMARKS & GRAIN SIZE DISTRIBUTION (%)			
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	"N" VALUES			SHEAR STRENGTH kPa ○ UNCONFINED + FIELD VANE ● QUICK TRIAXIAL × REMOULDED					WATER CONTENT (%) w _p w w _L				GR	SA	SI	CL
								20	40	60	80	100	20	40	60					
322.6	GROUND SURFACE																			
0.0	Asphalt (90 mm)		1	SS	29															
	Sand and gravel (FILL) Compact Brown Moist		2	SS	30															
321.2																				
1.4	Sand, some gravel, trace silt, trace organics (FILL) Loose to compact Brown Wet		3	SS	16															
			4	SS	9															
			5	SS	9															
318.9																				
3.7	SILT and SAND, trace gravel, trace clay, containing clayey silt seams Loose Brown Wet		6	SS	10															
			7	SS	8															
317.0																				
5.6	SAND, trace gravel, trace to some silt Compact Brown Wet		8	SS	11															
315.4																				
7.2	Silty SAND, trace to some clay Loose Grey Wet		9	SS	4															
314.4																				
8.2	END OF BOREHOLE																			
	NOTE: 1. Water level at a depth of 1.6 m below ground surface (Elev. 321.0 m) upon completion of drilling.																			

+³, ×³: Numbers refer to Sensitivity ○ 3% STRAIN AT FAILURE

PROJECT 11-1111-0149		RECORD OF BOREHOLE No B1-02		SHEET 1 OF 2		METRIC	
W.P. 5265-07-01		LOCATION N 5035127.1 ; E 324448.4		ORIGINATED BY ID			
DIST HWY 592		BOREHOLE TYPE 203 mm O.D. Hollow Stem Augers and NW Casing		COMPILED BY AV			
DATUM Geodetic		DATE May 15, 2013		CHECKED BY TVA			

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT					PLASTIC NATURAL LIQUID LIMIT MOISTURE LIMIT CONTENT			UNIT WEIGHT γ kN/m ³	REMARKS & GRAIN SIZE DISTRIBUTION (%)				
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	"N" VALUES			SHEAR STRENGTH kPa					WATER CONTENT (%)				GR	SA	SI	CL	
								20	40	60	80	100	W _p	W	W _L						
322.5	GROUND SURFACE																				
0.0	Asphalt (90 mm)		1	SS	20																
	Sand and gravel (FILL)		2	SS	16/0.20																
	Compact																				
	Brown		3	SS	12																
	Moist to wet		4	SS	19																
319.5																					
3.0	SILT and SAND, trace to some clay		5	SS	5																
	Loose		6	SS	8																
	Brown becoming grey below a depth of 3.7 m		7	SS	4																
	Wet																				
316.9																					
5.6	CLAYEY SILT, trace sand		8	SS	3																
	Soft to firm																				
	Grey		9	SS	5																
	Wet																				
314.3																					
8.2	SAND and GRAVEL, trace to some silt																				
	Dense		10	SS	37/0.15																
	Grey		3	RC	REC 63%																
	Wet																				
	Artesian condition encountered when advanced casing to a depth of 9.1 m, water level recorded at 0.3 m above ground surface.																				
	Cobbles encountered between depths of 9.5 m and 10.4 m.																				
	Cobbles and boulders encountered between depths of 10.7 m and 12.2 m.		11	SS	40/0.08																
			4	RC	REC 63%																
			12	SS	34/0.15																
	Artesian condition encountered when advanced casing to a depth of 12.8 m, water level recorded at 0.5 m above ground surface.																				
	Cobbles encountered between depths of 13.1 m and 13.4 m.		5	RC	REC 65%																
308.8																					
13.7	Sandy GRAVEL, trace silt		13	SS	16																
	Compact to dense																				
	Grey		6	RC	NR																
	Wet																				


Continued Next Page

+³, ×³: Numbers refer to Sensitivity ○ 3% STRAIN AT FAILURE

GTA-MTO 001 11-1111-0149.GPJ GAL-GTA.GDT 12/20/13


PROJECT 11-1111-0149				RECORD OF BOREHOLE No B1-02				SHEET 2 OF 2				METRIC							
W.P. 5265-07-01				LOCATION N 5035127.1 ; E 324448.4				ORIGINATED BY ID											
DIST HWY 592				BOREHOLE TYPE 203 mm O.D. Hollow Stem Augers and NW Casing				COMPILED BY AV											
DATUM Geodetic				DATE May 15, 2013				CHECKED BY TVA											
SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT					PLASTIC LIMIT NATURAL MOISTURE CONTENT LIQUID LIMIT			UNIT WEIGHT γ kN/m ³	REMARKS & GRAIN SIZE DISTRIBUTION (%)		
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	"N" VALUES			SHEAR STRENGTH kPa					W _p	W	W _L				
	--- CONTINUED FROM PREVIOUS PAGE ---						20	40	60	80	100								
							○ UNCONFINED + FIELD VANE ● QUICK TRIAXIAL × REMOULDED					WATER CONTENT (%)							
							20	40	60	80	100	20	40	60					
302.7	Artesian condition encountered when advanced casing to a depth of 14.3 m, water level recorded at 0.6 m above ground surface.		6	RC	NR														
	Cobbles encountered between depths of 14.8 m and 15.2 m.		14	SS	45/0.15														
	Artesian condition encountered when advanced casing to a depth of 15.8 m, water level recorded at 0.8 m above ground surface.																		
			15	SS	50/0.15														
	Cobbles encountered between depths of 18.4 m and 19.8 m.		7	RC	REC 49%														
19.8	END OF BOREHOLE																		
	Dynamic Cone Penetration Test (DCPT)																		
297.1																			
25.4	END OF DCPT Refusal to Further Penetration (30 Blows / 0.13 m)																		
	NOTES: 1. Artesian conditions encountered during drilling: Date Depth (m) W.L. Water/Casing Elev. (m) 05/15/13 -0.3/9.1 322.8 05/16/13 -0.5/12.8 323.0 05/16/13 -0.6/14.3 323.1 05/16/13 -0.8/15.8 323.3 NR - Not Recorded																		

PROJECT 11-1111-0149		RECORD OF BOREHOLE No B1-03		SHEET 1 OF 2		METRIC	
W.P. 5265-07-01		LOCATION N 5035139.4 ; E 324447.6		ORIGINATED BY ID			
DIST HWY 592		BOREHOLE TYPE 120 mm O.D. Hollow Stem Augers and NW Casing		COMPILED BY GRL/AV			
DATUM Geodetic		DATE June 3, 2013		CHECKED BY TVA			



Continued Next Page

+ 3, X 3: Numbers refer to Sensitivity ○ 3% STRAIN AT FAILURE

PROJECT 11-1111-0149				RECORD OF BOREHOLE No B1-03				SHEET 2 OF 2				METRIC				
W.P. 5265-07-01				LOCATION N 5035139.4 ; E 324447.6				ORIGINATED BY ID								
DIST _____ HWY 592				BOREHOLE TYPE 120 mm O.D. Hollow Stem Augers and NW Casing				COMPILED BY GRL/AV								
DATUM Geodetic				DATE June 3, 2013				CHECKED BY TVA								
SOIL PROFILE		SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT					PLASTIC LIMIT NATURAL MOISTURE CONTENT LIQUID LIMIT			UNIT WEIGHT γ kN/m ³	REMARKS & GRAIN SIZE DISTRIBUTION (%) GR SA SI CL
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE			"N" VALUES	SHEAR STRENGTH kPa					W _p W W _L			
--- CONTINUED FROM PREVIOUS PAGE ---							20 40 60 80 100 ○ UNCONFINED + FIELD VANE ● QUICK TRIAXIAL × REMOULDED 20 40 60 80 100					20 40 60 WATER CONTENT (%)				
303.6	END OF BOREHOLE (Loss of water in casing)					307										
					306											
					305											
					304											
18.9	END OF DCPT Refusal to Further Penetration (137 Blows / 0.3 m) NOTES: 1. Borehole terminated upon loss of water head in drill string. 2. Artesian condition encountered upon completion of DCPT and removal of the penetration cone, water flowing from ground surface. 3. Water level in open borehole measured at a depth of 1.1 m below ground surface (Elev. 321.4 m) upon completion of drilling. 4. A dynamic cone penetration test was advanced 1.5m north of Borehole B1-03 to confirm refusal. * Split-spoon sampler bouncing on wood pieces; N-value not representative of soil relative density.															

PROJECT 11-1111-0149			RECORD OF BOREHOLE No B1-05				SHEET 2 OF 2		METRIC								
W.P. 5265-07-01			LOCATION N 5035139.6 ; E 324452.1				ORIGINATED BY ID										
DIST HWY 592			BOREHOLE TYPE 120 mm O.D. Hollow Stem Augers and NW Casing				COMPILED BY GRL/AV										
DATUM Geodetic			DATE June 4 to 6, 2013				CHECKED BY TVA										
SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT					PLASTIC LIMIT W _p	NATURAL MOISTURE CONTENT W	LIQUID LIMIT W _L	UNIT WEIGHT γ kN/m ³	REMARKS & GRAIN SIZE DISTRIBUTION (%) GR SA SI CL
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	"N" VALUES			SHEAR STRENGTH kPa									
	--- CONTINUED FROM PREVIOUS PAGE ---																
	SAND and GRAVEL, trace to some silt, containing clayey silt seams to a depth of 5.2 m Compact to dense Brown Wet	[Pattern]	14	SS	35												
	Artesian condition noted at a depth of 15.2 m, water flowing from around the casing.		5	RC	REC 55%												
	Cobbles encountered between depths of 16.2 m and 16.8 m.																
	Cobbles encountered between depths of 17.8 m and 18.3 m.		6	RC	REC 52%												
			15	SS	23												
	Artesian condition encountered at a depth of 22.3 m, water level recorded at 0.4 m above ground surface.																
299.0	END OF BOREHOLE		16	SS	36												
23.5	NOTES: 1. Water level in open borehole at a depth of 1.1 m below ground surface (Elev. 321.4 m) during drilling, measured on June 4, 2013. 2. Artesian conditions encountered during drilling: Date Depth (m) W.L. Water/Casing Elev. (m) 06/05/13 -*/5.2 -* 06/05/13 -0.4/9.8 322.9 06/06/13 -*/15.2 -* 06/06/13 -0.4/22.3 322.9 * Water flowing around casing. 3. water level in open borehole at a depth of 0.3 m above ground surface (Elev. 322.8 m) upon completion of drilling.																



APPENDIX B

Laboratory Test Results and Bedrock Core Photographs

Boreholes B1-03, B1-04 and B1-05




Borehole B1-03 Sample 3

Borehole B1-05 Sample 3

Borehole B1-04 Sample 3


REVISION DATE: April 13, 2011 BY: TVA Project 09-1111-6014

PROJECT		Little East River Bridge No.1 Highway 592 GWP 5265-07-00; WP 5265-07-01			
TITLE		Wood Pieces Photograph – B1-02, B1-04 and B1-05 Highway 592			
		PROJECT No. 11-1111-0149		FILE No. ----	
		DESIGN	AV	AUG 13	SCALE NTS
		CADD	--		REV.
		CHECK	TZ	AUG 13	FIGURE B1
		REVIEW	JMAC	AUG 13	

GRAIN SIZE DISTRIBUTION

Sand to Gravelly Sand (Fill)

FIGURE B2



SILT AND CLAY SIZES		FINE	MEDIUM	COARSE	FINE	COARSE	COBBLE
FINE GRAINED		SAND SIZE			GRAVEL SIZE		SIZE

LEGEND

SYMBOL	BOREHOLE	SAMPLE	ELEVATION(m)
●	B1-05	2	321.4
■	B1-04	3A	320.8
◆	B1-01	4	320.0
▲	B1-03	5	319.1

Project Number: 11-1111-0149

Checked By: AV


Golder Associates

Date: 21-Oct-13

GRAIN SIZE DISTRIBUTION

Organic Sand

FIGURE B3



SILT AND CLAY SIZES		FINE	MEDIUM	COARSE	FINE	COARSE	COBBLE
FINE GRAINED		SAND SIZE			GRAVEL SIZE		SIZE

LEGEND

SYMBOL	BOREHOLE	SAMPLE	ELEVATION(m)
•	B1-05	4	319.9

Project Number: 11-1111-0149

Checked By: AV


Golder Associates

Date: 21-Oct-13

GRAIN SIZE DISTRIBUTION

Silt and Sand to Sand

FIGURE B4



SILT AND CLAY SIZES	FINE	MEDIUM	COARSE	FINE	COARSE	COBBLE
FINE GRAINED	SAND SIZE			GRAVEL SIZE		SIZE

LEGEND

SYMBOL	BOREHOLE	SAMPLE	ELEVATION(m)
●	B1-02	6	318.4
■	B1-01	7	317.7
◆	B1-01	8	316.2
▲	B1-01	9	314.7

Project Number: 11-1111-0149

Checked By: AV


Golder Associates

Date: 07-Aug-13

GRAIN SIZE DISTRIBUTION

Clayey Silt

FIGURE B5



SILT AND CLAY SIZES		FINE	MEDIUM	COARSE	FINE	COARSE	COBBLE
FINE GRAINED		SAND SIZE			GRAVEL SIZE		SIZE

LEGEND


SYMBOL	BOREHOLE	SAMPLE	ELEVATION(m)
●	B1-03	7	317.6
■	B1-02	9	314.6

Project Number: 11-1111-0149

Checked By: AV

Golder Associates

Date: 07-Aug-13



Ministry of Transportation

Ontario

PLASTICITY CHART


Clayey Silt

Figure No. B6


Project No. 11-1111-0149

Checked By: AV

Boreholes B1-02 and B1-05




Scale

PROJECT		Little East River Bridge No.1 Highway 592 GWP 5265-07-00; WP 5265-07-01			
TITLE		Cobbles and Boulders Photograph – B1-02 and B1-05 Highway 592			
		PROJECT No. 11-1111-0149		FILE No. ----	
		DESIGN	AV	AUG 13	SCALE NTS
		CADD	--	--	REV.
		CHECK	TVA	AUG 13	FIGURE B7
		REVIEW	JMAC	AUG 13	

GRAIN SIZE DISTRIBUTION

Sand and Gravel to Sandy Gravel

FIGURE B8



SILT AND CLAY SIZES	FINE	MEDIUM	COARSE	FINE	COARSE	COBBLE
FINE GRAINED	SAND SIZE			GRAVEL SIZE		SIZE

LEGEND

SYMBOL	BOREHOLE	SAMPLE	ELEVATION(m)
●	B1-04	10	313.1
■	B1-05	12	310.0
◆	B1-02	12	310.2
▲	B1-02	14	307.1
▽	B1-05	15	303.9
○	B1-04	7	317.6

Project Number: 11-1111-0149

Checked By: AV

Golder Associates

Date: 07-Aug-13

At Golder Associates we strive to be the most respected global company providing consulting, design, and construction services in earth, environment, and related areas of energy. Employee owned since our formation in 1960, our focus, unique culture and operating environment offer opportunities and the freedom to excel, which attracts the leading specialists in our fields. Golder professionals take the time to build an understanding of client needs and of the specific environments in which they operate. We continue to expand our technical capabilities and have experienced steady growth with employees who operate from offices located throughout Africa, Asia, Australasia, Europe, North America, and South America.

Africa	+ 27 11 254 4800
Asia	+ 86 21 6258 5522
Australasia	+ 61 3 8862 3500
Europe	+ 356 21 42 30 20
North America	+ 1 800 275 3281
South America	+ 55 21 3095 9500

solutions@golder.com
www.golder.com

Golder Associates Ltd.
6925 Century Avenue, Suite #100
Mississauga, Ontario, L5N 7K2
Canada
T: +1 (905) 567 4444

