



**FOUNDATION INVESTIGATION REPORT
for
HIGHWAY 400 BAYFIELD STREET STORM DRAIN
INSTALLATION AND CULVERT EXTENSION
RETAINER ASSIGNMENT – TASK NO. 2013-E-0039-002
BARRIE, ONTARIO
G.W.P. 2100-13-00**

PREPARED FOR MINISTRY OF TRANSPORTATION OF ONTARIO

PETO MacCALLUM LTD.
165 CARTWRIGHT AVENUE
TORONTO, ONTARIO
M6A 1V5
Phone: (416) 785-5110
Fax: (416) 785-5120
Email: toronto@petomaccallum.com

Distribution:

- 3 cc: MTO Project Manager + 1 digital copy (PDF Format)
- 1 cc: Foundation Investigation Report only
MTO Project Manager + 1 digital copy (PDF Format)
- 1 cc: MTO, Pavements and Foundations Section
+ 1 digital copy (PDF Format) and Drawing (AutoCAD)
- 1 cc: Foundation Investigation Report only
MTO, Pavements and Foundations Section
+ 1 digital copy (PDF Format)
and Drawing (AutoCAD)
- 1 cc: PML Toronto

PML Ref.: 14TF010
Index No.: 010FIR
GEOCRES No.: 31D-582
November 17, 2014



TABLE OF CONTENTS

1. INTRODUCTION	1
2. SITE DESCRIPTION AND GEOLOGY	1
3. INVESTIGATION PROCEDURES	2
4. SUMMARIZED SUBSURFACE CONDITIONS.....	3
4.1 Pavement Structure.....	4
4.2 Topsoil	4
4.3 Fill.....	4
4.4 Clayey Silt.....	5
4.5 Sand.....	5
4.6 Sand Till	6
4.7 Groundwater	6
5. CLOSURE	7

Figures B-GS-1 to B-GS-5 – Grain Size Distribution Charts

Figure B-PC-1 and B-PC-2 – Atterberg Limit Test Results

Explanation of Terms Used in Report

Record of Borehole Sheets

Drawing B-1 and B-2 – Borehole Locations and Soil Strata

FOUNDATION INVESTIGATION REPORT
for
Highway 400 Bayfield Street Storm Drain
Installation and Culvert Extension
Retainer Assignment – Task No. 2013-E-0039-002
Barrie, Ontario
GWP 2100-13-00

1. INTRODUCTION

This report summarizes the results of a foundation investigation carried out on Highway 400 near Bayfield Street for the installation of a new storm sewer, replacement of an existing storm sewer and extension of an existing culvert. The site is located in the City of Barrie, Ontario. The study was carried out by Peto MacCallum Ltd. (PML) for the Ministry of Transportation of Ontario (MTO).

The purpose of this report is to summarize the subsurface stratigraphy encountered at the site of the proposed works during the investigation.

2. SITE DESCRIPTION AND GEOLOGY

The site lies on the west side of Highway 400 between the Highway 400 southbound E/W-S ramp at Bayfield Street and Sunnidale Road in the City of Barrie. Land use in the vicinity of the site includes the Highway 400 transportation corridor, a stormwater control facility with a large berm west of the transportation corridor and dense stands of trees beyond the berm to the west. A channel from the stormwater control facility extends between the existing box culvert under Highway 400 and the stormwater control facility culvert outlet.

The local topography is undulating but generally governed by the Highway 400 transportation corridor. The ground surface is generally slopes downwards from the north to the south and also slopes downwards both east and west of the existing Highway 400 embankment. West of Highway 400 ditch line the ground slopes upwards towards the top of the large berm.



The project site is located within the physiographic region known as the Simcoe Uplands. The Simcoe Uplands comprise a series of broad, rolling glacial till plains (locally sand till), separated by steep-sided flat floored valleys.

3. INVESTIGATION PROCEDURES

The field work for this study was carried out on July 13, 2014 and comprised 4 boreholes drilled to depths of 3.4 to 3.5 m for the proposed storm drain installation (BH's 2 to 5 inclusive), and 2 boreholes drilled to depths of 9.6 and 19.1 m for the proposed culvert extension and storm sewer replacement (BH's 1 and 1A). The locations of the boreholes are shown on appended Drawings B-1 and B-2.

The borehole locations were strategically located to provide soils data for the proposed works while minimizing the impact on the existing Highway 400 traffic. The borehole locations and elevations were surveyed in the field by Rudy Mak Surveying. All elevations in this report are expressed in metres.

The boreholes were advanced using continuous flight solid or hollow stem augers advanced with a track or truck-mounted D-50 drill rig supplied and operated by a specialist drilling contractor, working under the full-time supervision of a PML field technician.

Standard penetration tests and dynamic cone penetration test were conducted to assess the strength characteristics of the substrata. Soil samples were recovered from the boreholes at regular 0.75 and 1.5 m intervals following standard penetration testing. Soils were identified in accordance with MTO soil classification manual procedures.

The groundwater conditions in the boreholes were assessed during drilling by visual examination of the soil, the sampler and drill rods as the samples were retrieved.

The boreholes were backfilled with a bentonite/grout mixture, where required, in accordance with the MTO guidelines and MOE Reg. 903 for borehole abandonment procedures.



The recovered soil samples were returned to our laboratory in Toronto for detailed visual examination, laboratory testing and classification. The laboratory testing program included the following tests:

- Natural moisture content determinations (46)
- Grain size distribution analyses (11)
- Atterberg limit test (3)

The figures prepared to present the results of the laboratory grain size distribution analyses and Atterberg Limit Test are presented in Figures B-GS-1 to B-GS-5 and B-PC-1 to B-PC-2, respectively. The test results are summarized on the Record of Borehole sheets.

4. SUMMARIZED SUBSURFACE CONDITIONS

Reference is made to the appended Record of Borehole sheets 1A and 1 to 5 for details of the subsurface conditions including soil classifications, inferred stratigraphy, standard penetration test data, dynamic cone penetration test data and groundwater observations. The results of laboratory grain size distribution analyses, Atterberg limit test and moisture content determinations are also shown on the Record of Borehole sheets.

The borehole locations and stratigraphic profile prepared from the borehole data are shown on Drawings B-1 and B-2. The boundaries between soil strata have been established at the borehole locations only. Between and beyond the boreholes, these boundaries are assumed and may vary.

In summary, the subsurface stratigraphy revealed in borehole 1A drilled at the culvert extension location, comprised a 1.4 m thick surficial silty sand and topsoil layer over a 3.3 m thick compact sand deposit, above a 4.9 m thick very stiff clayey silt deposit. At the embankment location, directly east of the proposed culvert extension, borehole 1 revealed a 10 m thick compact to dense sand fill layer, above a 2.5 m thick very stiff clayey silt layer, overlying an approximately 7.6 m thick compact to very dense sand deposit. At the location of the culvert extension, the slope is covered by large boulders with diameters in the order of 1 m.



Boreholes 2 to 5, drilled for the proposed storm drain along the Hwy 400 west shoulder generally revealed pavement structure (locally topsoil in borehole 5) over sand or sand till to the 3.4 to 3.5 m exploration depth.

Details of the soil stratigraphy are provided below:

4.1 Pavement Structure

The pavement structure encountered in boreholes 1 to 4 which were drilled through Highway 400 and the Highway 400 E/W-S ramp, included 150 and 250 mm of asphaltic concrete, underlain by 520 to 650 mm of sand and gravel.

4.2 Topsoil

A 100 mm thick layer of topsoil was encountered at the surface at BH#5 and extended to elevation 259.9. A 400 mm thick layer of topsoil was also encountered beneath the silty sand fill at 1.0 m (elevation 244.1) at BH#1A that extended to a for a thickness of 1.4 m (to elevation 243.7).

4.3 Fill

A 0.7 to 9.1 m thick fill unit was encountered beneath the pavement structure at depths of 0.7 and 0.9 m (elevation 254.7 and 251.5) in boreholes 2 and 1, respectively. The fill was also contacted beneath the topsoil at a depth of 0.1 m (elevation 259.9) in borehole 5 and surficially in borehole 1A. The fill unit extended for a thickness of approximately 10.0 m (elevation 242.4) in borehole 1 and for thicknesses ranging from 0.5 m to 1.4 m (elevation 244.1 to 259.5) in boreholes 1A, 2 and 5. The fill was typically loose to compact, with SPT-'N' values ranging from 7 to 28. However the fill was locally very loose and dense in borehole 1 and 1A. The fill was moist to wet with moisture contents of 5 to 23%. Clayey silt layers, topsoil layers, cobbles and boulders and organic inclusions were noted within the fill. The results of an Atterberg Limit Test performed on a sample



of the fill is presented on Figure B-PC-1 and the results of grain size distribution analyses performed on 4 samples of the fill are presented on Figures B-GS-1 and B-GS-2.

4.4 Clayey Silt

A 2.5 and 4.9 m thick clayey silt deposit was contacted beneath the fill at depth of 10.0 m (elevation 242.4) in borehole 1 and beneath the sand at a depth of 4.7 m (elevation 240.4) in borehole 1A. The clayey silt extended to a depth of 12.5 m (elevation 239.9) in borehole 1 and to a depth of greater than 9.6 m (below elevation 235.5), which was the termination depth in borehole 1A. The clayey silt was typically very stiff (locally hard at the bottom of borehole 1A) with SPT-'N' values of ranging from 17 to 27.

The results of grain size distribution analyses and Atterberg Limit Tests performed on two samples of the clayey silt are presented on Figures B-GS-3 and B-PC-2, respectively. Atterberg Limit Testing indicated that the clayey silt had liquid limits ranging from 25 to 28, plastic limits ranging from 14 to 15, and plasticity indices ranging from 11 to 13. The moisture content of the clayey silt was between the plastic limit and liquid limit with moisture contents ranging from 18 to 24%.

4.5 Sand

A 2.1 to 6.6 m thick sand deposit was contacted beneath the clayey silt at a depth of 12.5 m (elevation 239.9) in borehole 1, beneath the topsoil at a depth of 1.4 m (elevation 243.7) in borehole 1A and beneath the fill at a depth of 1.4 m (elevation 254.0) in borehole 2. The sand extended to the clayey silt at 4.7 m (elevation 240.4) in borehole 1A and to the 3.5 and 19.1 m (elevation 251.9 and 233.3) exploration depth in boreholes 2 and 1, respectively. The sand was loose to very dense with SPT-'N' values of 8 blows to 83 blows for 23 cm. The material was wet in boreholes 1 and 1A (moisture contents ranging from 18 to 23%) and moist in borehole 2 (moisture contents ranging from 3 to 6%). The results grain size distribution analyses performed on 3 samples of the sand are presented on Figure B-GS-4.



4.6 Sand Till

A 2.7 to 3.0 m thick sand till layer was contacted beneath the pavement structure at depths of 0.5 and 0.7 m (elevations 256.1 to 259.5) in boreholes 3 to 5 that extended to depths of 3.4 to 3.5 m (elevation 253.4 to 256.5, which was the borehole exploration depth). The till was typically compact to very dense, although locally loose in the upper portion of the layer in borehole 5, with SPT-'N' values typically between 21 and 106. The till was moist, having moisture contents of 3 to 14%. Cobbles and boulders were noted within the layer. The results of grain size distribution analyses performed on 3 samples of the layers are presented on Figure B-GS-5.

4.7 Groundwater

In the process of augering, water strikes were observed at depths of 1.5 and 8.8 m (elevation 243.6) and in boreholes 1A and 1 respectively. Upon completion of augering, groundwater was measured at a depth of 1.5 m (elevation 243.6) in boreholes 1A.

The water level in the stormwater drainage channel at the location of the proposed culvert extension and adjacent to borehole 1A was at elevation 243.7 on July 13, 2014.

The groundwater levels at the site are subject to seasonal fluctuation.




5. CLOSURE

Mr. A. Lo and Mr. P. Portela carried out the field investigation for this study under the supervision of Mr. A. DeSira, MEng, P.Eng. Walker Drilling supplied the drill rig for the subsurface exploration. The laboratory testing of the selected samples was carried out in the PML laboratory in Toronto.

This Foundation Investigation report was prepared by Mr. A. DeSira, MEng, P.Eng., and reviewed by Mr. D. Dundas, P.Eng. Mr. C. M. P. Nascimento, P. Eng., Project Manager and MTO Designated Principal Contact conducted a quality review of the report.

Yours very truly

Peto MacCallum Ltd.




David Dundas, P.Eng.
Senior Engineer, Geotechnical Services



Carlos Nascimento, P.Eng.
Project Manager and
MTO Designated Principal Contact

AD/CN:ad-mi-nk




LEGEND		
BH	SAMPLE	SYMBOL
1	2	—
1	11	- - -
2	2	- · - ·

SILT & CLAY				FINE		MEDIUM		COARSE		GRAVEL		COBBLES	UNIFIED	
				SAND										
CLAY	FINE		MEDIUM		COARSE	FINE		MEDIUM		COARSE	GRAVEL		COBBLES	M.I.T.
CLAY			SILT			V. FINE		FINE	MED.	COARSE	GRAVEL			U.S. BUREAU
						SAND								

GRAIN SIZE DISTRIBUTION
 SAND, some silt, trace to some clay, trace to some gravel
 (FILL)

FIG No.	B-GS-1
HWY:	400
W.P. No.	2100-13-00






LEGEND		
BH	SAMPLE	SYMBOL
1	8	—

SILT & CLAY				FINE SAND			MEDIUM SAND		COARSE SAND		GRAVEL			COBBLES	UNIFIED
CLAY	FINE SILT		COARSE SILT	FINE SAND		MEDIUM SAND		COARSE SAND		GRAVEL			COBBLES	M.I.T.	
CLAY		SILT		V. FINE SAND	FINE SAND	MED. SAND	COARSE SAND		GRAVEL				U.S. BUREAU		

GRAIN SIZE DISTRIBUTION
SANDY CLAYEY SILT, trace gravel (CL-ML)
(FILL)

FIG No.	B-GS-2
HWY:	400
W.P. No.	2100-13-00






LEGEND		
BH	SAMPLE	SYMBOL
1A	7	—
1A	8	- - -

SILT & CLAY				FINE SAND			MEDIUM SAND		COARSE SAND		GRAVEL		COBBLES	UNIFIED
CLAY	FINE SILT		MEDIUM SILT	COARSE SILT	FINE SAND	MEDIUM SAND	COARSE SAND	GRAVEL			COBBLES	M.I.T.		
CLAY	SILT			V. FINE SAND	FINE SAND	MED. SAND	COARSE SAND	GRAVEL				U.S. BUREAU		



GRAIN SIZE DISTRIBUTION
 CLAYEY SILT, trace to some sand (CL)

FIG No.	B-GS-3
HWY:	400
W.P. No.	2100-13-00




SILT & CLAY				FINE SAND		MEDIUM SAND		COARSE SAND		GRAVEL		COBBLES	UNIFIED
CLAY	FINE SILT		COARSE SILT	FINE SAND	MEDIUM SAND	COARSE SAND		GRAVEL			COBBLES	M.I.T.	
CLAY		SILT		V. FINE SAND	FINE SAND	MED. SAND	COARSE SAND	GRAVEL				COBBLES	U.S. BUREAU

GRAIN SIZE DISTRIBUTION

SAND, trace to some gravel, trace to some silt, trace clay



FIG No.	B-GS-4
HWY:	400
W.P. No.	2100-13-00




LEGEND		
BH	SAMPLE	SYMBOL
4	3	—————
5	2	- - - - -
5	5	- · - · - ·

SILT & CLAY				FINE SAND		MEDIUM SAND		COARSE SAND		GRAVEL		COBBLES	UNIFIED
CLAY	FINE SILT		COARSE SILT	FINE SAND	MED. SAND	COARSE SAND		GRAVEL			COBBLES	M.I.T.	
CLAY		SILT		V. FINE SAND	FINE SAND	MED. SAND	COARSE SAND	GRAVEL					U.S. BUREAU

GRAIN SIZE DISTRIBUTION
 SAND, some silt, some clay, trace gravel
 (TILL)


FIG No.	B-GS-5
HWY:	400
W.P. No.	2100-13-00





PLASTICITY CHART
 SANDY CLAYEY SILT, trace gravel (CL-ML)
 (FILL)

FIG No.	B-PC-1
HWY:	400
W.P. No.	2100-13-00



PLASTICITY CHART
 CLAYEY SILT, trace to some sand (CL)

FIG No.	BR-PC-2
HWY:	400
W.P. No.	2100-13-00

EXPLANATION OF TERMS USED IN REPORT

N VALUE: THE STANDARD PENETRATION TEST (SPT) N VALUE IS THE NUMBER OF BLOWS REQUIRED TO CAUSE A STANDARD 51mm O.D. SPLIT BARREL SAMPLER TO PENETRATE 0.3m INTO UNDISTURBED GROUND IN A BOREHOLE WHEN DRIVEN BY A HAMMER WITH A MASS OF 63.5kg, FALLING FREELY A DISTANCE OF 0.76m. FOR PENETRATIONS OF LESS THAN 0.3m N VALUES ARE INDICATED AS THE NUMBER OF BLOWS FOR THE PENETRATION ACHIEVED. AVERAGE N VALUE IS DENOTED THUS \bar{N} .

DYNAMIC CONE PENETRATION TEST: CONTINUOUS PENETRATION OF A CONICAL STEEL POINT (51mm O.D. 60° CONE ANGLE) DRIVEN BY 475 J IMPACT ENERGY ON 'A' SIZE DRILL RODS. THE RESISTANCE TO CONE PENETRATION IS MEASURED AS THE NUMBER OF BLOWS FOR EACH 0.3m ADVANCE OF THE CONICAL POINT INTO THE UNDISTURBED GROUND.

SOILS ARE DESCRIBED BY THEIR COMPOSITION AND CONSISTENCY OR DENSENESS.

COMPOSITION: SECONDARY SOIL COMPONENTS ARE DESCRIBED ON THE BASIS OF PERCENTAGE BY MASS OF THE WHOLE SAMPLE AS FOLLOWS:

PERCENT BY MASS	0-10	10-20	20-30	30-40	>40
	TRACE	SOME	WITH	ADJECTIVE (SILTY)	AND (AND SILT)

CONSISTENCY: COHESIVE SOILS ARE DESCRIBED ON THE BASIS OF THEIR UNDRAINED SHEAR STRENGTH (c_u) AS FOLLOWS:

c_u (kPa)	0-12	12-25	25-50	50-100	100-200	>200
	VERY SOFT	SOFT	FIRM	STIFF	VERY STIFF	HARD

DENSENESS: COHESIONLESS SOILS ARE DESCRIBED ON THE BASIS OF DENSENESS AS INDICATED BY SPT N VALUES AS FOLLOWS:

N (BLOWS/0.3m)	0-5	5-10	10-30	30-50	>50
	VERY LOOSE	LOOSE	COMPACT	DENSE	VERY DENSE

ROCKS ARE DESCRIBED BY THEIR COMPOSITION AND STRUCTURAL FEATURES AND / OR STRENGTH.

RECOVERY: SUM OF ALL RECOVERED ROCK CORE PIECES FROM A CORING RUN EXPRESSED AS A PERCENT OF THE TOTAL LENGTH OF THE CORING RUN.

MODIFIED RECOVERY: SUM OF THOSE INTACT CORE PIECES, 100mm* IN LENGTH EXPRESSED AS A PERCENT OF THE LENGTH OF THE CORING RUN. THE ROCK QUALITY DESIGNATION (R Q D), FOR MODIFIED RECOVERY, IS:

R Q D (%)	0-25	25-50	50-75	75-90	90-100
	VERY POOR	POOR	FAIR	GOOD	EXCELLENT

JOINTING AND BEDDING:

SPACING	50mm	30-300mm	0.3m-1m	1m-3m	>3m
JOINTING	VERY CLOSE	CLOSE	MOD. CLOSE	WIDE	VERY WIDE
BEDDING	VERY THIN	THIN	MEDIUM	THICK	VERY THICK

ABBREVIATIONS AND SYMBOLS

FIELD SAMPLING

S S	SPLIT SPOON	T P	THINWALL PISTON
W S	WASH SAMPLE	O S	OSTERBERG SAMPLE
S T	SLOTTED TUBE SAMPLE	R C	ROCK CORE
B S	BLOCK SAMPLE	P H	T W ADVANCED HYDRAULICALLY
C S	CHUNK SAMPLE	F M	T W ADVANCED MANUALLY
T W	THINWALL OPEN	F S	FOIL SAMPLE
F V	FIELD VANE		

STRESS AND STRAIN

u_w	kPa	PORE WATER PRESSURE
l_u	1	PORE PRESSURE RATIO
σ	kPa	TOTAL NORMAL STRESS
σ'	kPa	EFFECTIVE NORMAL STRESS
τ	kPa	SHEAR STRESS
$\sigma_1, \sigma_2, \sigma_3$	kPa	PRINCIPAL STRESSES
ϵ	%	LINEAR STRAIN
$\epsilon_1, \epsilon_2, \epsilon_3$	%	PRINCIPAL STRAINS
E	kPa	MODULUS OF LINEAR DEFORMATION
G	kPa	MODULUS OF SHEAR DEFORMATION
μ	1	COEFFICIENT OF FRICTION

MECHANICAL PROPERTIES OF SOIL

m_v	kPa^{-1}	COEFFICIENT OF VOLUME CHANGE
C_c	1	COMPRESSION INDEX
C_s	1	SWELLING INDEX
C_{α}	1	RATE OF SECONDARY CONSOLIDATION
c_v	m^2/s	COEFFICIENT OF CONSOLIDATION
H	m	DRAINAGE PATH
T_v	1	TIME FACTOR
U	%	DEGREE OF CONSOLIDATION
σ'_{v0}	kPa	EFFECTIVE OVERBURDEN PRESSURE
σ'_p	kPa	PRECONSOLIDATION PRESSURE
τ_f	kPa	SHEAR STRENGTH
c'	kPa	EFFECTIVE COHESION INTERCEPT
ϕ'	-°	EFFECTIVE ANGLE OF INTERNAL FRICTION
c_u	kPa	APPARENT COHESION INTERCEPT
ϕ_u	-°	APPARENT ANGLE OF INTERNAL FRICTION
τ_R	kPa	RESIDUAL SHEAR STRENGTH
τ_r	kPa	REMOULDED SHEAR STRENGTH
S_l	1	SENSITIVITY = $\frac{c_u}{\tau_r}$

PHYSICAL PROPERTIES OF SOIL

ρ_s	kg/m^3	DENSITY OF SOLID PARTICLES	n	1, %	POROSITY	e_{max}	1, %	VOID RATIO IN LOOSEST STATE
γ_s	kN/m^3	UNIT WEIGHT OF SOLID PARTICLES	w	1, %	WATER CONTENT	e_{min}	1, %	VOID RATIO IN DENSEST STATE
ρ_w	kg/m^3	DENSITY OF WATER	S_r	%	DEGREE OF SATURATION	I_D	1	DENSITY INDEX = $\frac{e_{max} - e}{e_{max} - e_{min}}$
γ_w	kN/m^3	UNIT WEIGHT OF WATER	w_L	%	LIQUID LIMIT	D	mm	GRAIN DIAMETER
ρ	kg/m^3	DENSITY OF SOIL	w_p	%	PLASTIC LIMIT	D_n	mm	n PERCENT - DIAMETER
γ	kN/m^3	UNIT WEIGHT OF SOIL	w_s	%	SHRINKAGE LIMIT	C_u	1	UNIFORMITY COEFFICIENT
ρ_d	kg/m^3	DENSITY OF DRY SOIL	I_p	%	PLASTICITY INDEX = $w_L - w_p$	h	m	HYDRAULIC HEAD OR POTENTIAL
γ_d	kN/m^3	UNIT WEIGHT OF DRY SOIL	I_L	1	LIQUIDITY INDEX = $\frac{w - w_p}{I_p}$	q	m^2/s	RATE OF DISCHARGE
ρ_{sat}	kg/m^3	DENSITY OF SATURATED SOIL	I_C	1	CONSISTENCY INDEX = $\frac{w_L - w}{I_p}$	v	m/s	DISCHARGE VELOCITY
γ_{sat}	kN/m^3	UNIT WEIGHT OF SATURATED SOIL	DTPL		DRIER THAN PLASTIC LIMIT	i	1	HYDRAULIC GRADIENT
ρ'	kg/m^3	DENSITY OF SUBMERGED SOIL	APL		ABOUT PLASTIC LIMIT	k	m/s	HYDRAULIC CONDUCTIVITY
γ'	kN/m^3	UNIT WEIGHT OF SUBMERGED SOIL	WTPL		WETTER THAN PLASTIC LIMIT	j	kN/m^2	SEEPAGE FORCE
e	1, %	VOID RATIO						

RECORD OF BOREHOLE No. 1

1 of 2

METRIC

G.W.P. 2100-13-00 **LOCATION** Co-ords. 4 917 125.1 N ; 288 637.8 E **ORIGINATED BY** A.L.
DIST Central **HWY** 400 **BOREHOLE TYPE** Continuous Flight Hollow Stem Augers **COMPILED BY** A.D.
DATUM Geodetic **DATE** July 13, 2014 **CHECKED BY** D.D.

SOIL PROFILE		SAMPLES			GROUND WATER CONDITIONS	DYNAMIC CONE PENETRATION RESISTANCE PLOT					PLASTIC LIMIT W _p	NATURAL MOISTURE CONTENT w	LIQUID LIMIT W _L	UNIT WEIGHT γ	REMARKS & GRAIN SIZE DISTRIBUTION (%)
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE		"N" VALUES	20	40	60	80					
						○ UNCONFINED + FIELD VANE ● QUICK TRIAXIAL × LAB VANE					WATER CONTENT (%)				GR SA SI CL
252.4	Ground Surface														
0.0	250mm asphalt over 650mm sand and gravel														
	(PAVEMENT FILL)														
251.5															
0.9	Sand, some silt some clay, trace gravel cobbles and boulders		1	SS	18						○				
	Dense to compact Brown/ grey Moist		2	SS	47						○				6 61 19 14
			3	SS	28						○				
	clayey silt layer		4	SS	14						○				
			5	SS	22						○				
	sand layer topsoil inclusions		6	SS	16						○				
	Black clayey silt seams/layer		7	SS	18						○				
			8	SS	17						○				3 48 31 18
			9	SS	33						○				
	Wet		10	SS	15						○				
			11	SS	3**						○				2 66 18 14
	Organic sand		12	SS	31						○				
	Black (FILL)														
242.4			13	SS	17						○				
10.0	Clayey silt, trace sand Very stiff Grey Moist		14	SS	18						○				
239.9			15	SS	22						○				
12.5	Sand some silt, trace clay Compact Grey Wet		16	SS	30						○				0 87 11 2

Cont'd

 +7, X⁵:

Numbers refer to Sensitivity

(% STRAIN AT FAILURE)

RECORD OF BOREHOLE No. 1

2 of 2

METRIC

G.W.P. 2100-13-00 **LOCATION** Co-ords. 4 917 125.1 N ; 288 637.8 E **ORIGINATED BY** A.L.
DIST Central **HWY** 400 **BOREHOLE TYPE** Continuous Flight Hollow Stem Augers **COMPILED BY** A.D.
DATUM Geodetic **DATE** July 13, 2014 **CHECKED BY** D.D.

SOIL PROFILE		SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT					PLASTIC LIMIT W _p	NATURAL MOISTURE CONTENT w	LIQUID LIMIT W _L	UNIT WEIGHT γ	REMARKS & GRAIN SIZE DISTRIBUTION (%)		
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE			'N' VALUES	20	40	60	80						100	20
237.4	Sand, some silt Compact Grey Wet (Cont'd.)	•••••	17	SS	11													
	Very dense	•••••	18	SS	83/23cm													
		•••••	19	SS	17**													
233.5	End of borehole	•••••																
18.9	Switched to dynamic cone penetration test																	
233.3	Probable sand																	
19.1	Very dense End of dynamic cone penetration test																	

* 2014 07 13
 Water level observed during drilling
 ** Low 'N' values due to possible hydraulic disturbance during drilling

RECORD OF BOREHOLE No. 1A

1 of 1

METRIC

G.W.P. 2100-13-00 **LOCATION** Co-ords. 4 917 133.1 N ; 288 616.7 E **ORIGINATED BY** F.P.
DIST Central **HWY** 400 **BOREHOLE TYPE** Continuous Flight Solid Stem Augers **COMPILED BY** A.D.
DATUM Geodetic **DATE** July 13, 2014 **CHECKED BY** D.D.

SOIL PROFILE		SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT					PLASTIC LIMIT W _p	NATURAL MOISTURE CONTENT w	LIQUID LIMIT W _L	UNIT WEIGHT γ	REMARKS & GRAIN SIZE DISTRIBUTION (%)							
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE			"N" VALUES	20	40	60	80						100	SHEAR STRENGTH kPa					
											○ UNCONFINED	+ FIELD VANE	● QUICK TRIAXIAL	× LAB VANE	WATER CONTENT (%)			GR	SA	SI	CL		
245.1	Ground Surface																						
0.0	Silty sand topsoil and clayey silt inclusions (FILL)		1	SS	1																		
244.1	Topsoil		2	SS	4																		
1.0																							
243.7																							
1.4	Sand, some gravel trace silt, trace clay Loose to Grey Wet compact		3	SS	18																		
			4	SS	29																		19 70 8 3
			5	SS	8																		
			6	SS	14																		
240.4	Clayey silt trace to some sand Very stiff Grey Moist		7	SS	20																		0 12 54 34
4.7																							
			8	SS	23																		0 4 54 42
			9	SS	27																		
	Hard																						
235.5			10	SS	61																		
9.6	End of borehole																						

* 2014 07 14

Water level observed during drilling

Water level measured after drilling

RECORD OF BOREHOLE No. 2

1 of 1

METRIC

G.W.P. 2100-13-00 **LOCATION** Co-ords. 4 917 249.8 N ; 288 705.0 E **ORIGINATED BY** F.P.
DIST Central **HWY** 400 **BOREHOLE TYPE** Continuous Flight Solid Stem Augers **COMPILED BY** A.D.
DATUM Geodetic **DATE** July 13, 2014 **CHECKED BY** D.D.

SOIL PROFILE		SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT					PLASTIC LIMIT W _p	NATURAL MOISTURE CONTENT w	LIQUID LIMIT W _L	UNIT WEIGHT γ	REMARKS & GRAIN SIZE DISTRIBUTION (%)		
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE			"N" VALUES	20	40	60	80						100	SHEAR STRENGTH kPa
255.4	Ground Surface																	
0.0	180mm asphalt over 520mm sand and gravel	▣	1	SS	14													
254.7	(PAVEMENT FILL)	▣																
0.7	Sand, some silt some gravel, trace clay	▣	2	SS	9										18	60	14	8
254.0	Compact Brown Moist to loose (FILL)	•••																
1.4	Sand, trace silt trace clay, trace gravel	•••	3	SS	17													
	Compact to Grey Moist very dense	•••																
		•••	4	SS	32													
		•••																
		•••	5	SS	58													
251.9	End of borehole																	
3.5	Refusal on probable bedrock																	
	* Borehole dry																	

RECORD OF BOREHOLE No. 3

1 of 1

METRIC

G.W.P. 2100-13-00 **LOCATION** Co-ords. 4 917 307.2 N ; 288 737.2 E **ORIGINATED BY** F.P.
DIST Central **HWY** 400 **BOREHOLE TYPE** Continuous Flight Solid Stem Augers **COMPILED BY** A.D.
DATUM Geodetic **DATE** July 13, 2014 **CHECKED BY** D.D.

SOIL PROFILE		SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT					PLASTIC LIMIT W _p	NATURAL MOISTURE CONTENT w	LIQUID LIMIT W _L	UNIT WEIGHT γ	REMARKS & GRAIN SIZE DISTRIBUTION (%)
ELEV. DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE			"N" VALUES	20	40	60	80					
256.8	Ground Surface															
0.0	150mm asphalt over 550mm sand and gravel (PAVEMENT FILL)		1	SS	21											
256.1	Sand, some silt some clay, trace gravel sand layers Compact to Grey Moist very dense		2	SS	21											
0.7			3	SS	79											
	(TILL)		4	SS	106											
	clayey silt layers		5	SS	60/15cm											
253.4	End of borehole															
3.4	* Borehole dry															


RECORD OF BOREHOLE No. 4

1 of 1


METRIC

G.W.P. 2100-13-00 **LOCATION** Co-ords. 4 917 371.3 N ; 288 771.9 E **ORIGINATED BY** F.P.
DIST Central **HWY** 400 **BOREHOLE TYPE** Continuous Flight Solid Stem Augers **COMPILED BY** A.D.
DATUM Geodetic **DATE** July 13, 2014 **CHECKED BY** D.D.

SOIL PROFILE		SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT					PLASTIC LIMIT W _p	NATURAL MOISTURE CONTENT w	LIQUID LIMIT W _L	UNIT WEIGHT γ	REMARKS & GRAIN SIZE DISTRIBUTION (%)
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE			"N" VALUES	20	40	60	80					
258.2	Ground Surface															
0.0	150mm asphalt over 550mm sand and gravel (PAVEMENT FILL)		1	SS	14											
257.5	Sand, some silt some clay, trace gravel Dense to Grey Moist very dense		2	SS	49											
0.7			3	SS	62											
	(TILL)		4	SS	65											9 69 12 10
			5	SS	90											
254.7	End of borehole															
3.5	* Borehole dry															



PLAN
SCALE
0 10 20m



PROFILE A - A
SCALE
HORIZONTAL 0 10 20m
VERTICAL 0 5 10m

LEGEND

- Borehole
- Borehole and cone
- Cone penetration test
- N Blows/0.3m (Std. Pen Test, 475 J/blow)
- CONE Blows/0.3m (60° Cone, 475 J/blow)
- W L at time of investigation June 2014
- Head
- ARTESIAN WATER Encountered
- PIEZOMETER

BH No	ELEVATION	COORDINATES NORTHINGS	EASTINGS
2	255.4	4 917 249.8	288 705.0
3	256.8	4 917 307.2	288 737.2
4	258.2	4 917 371.3	288 771.9
5	260.0	4 917 443.4	288 807.5

NOTE
The boundaries between soil strata have been established only at Borehole locations. Between Boreholes the boundaries are assumed from geological evidence.

- NOTES:
- THIS DRAWING SHOULD BE READ IN CONJUNCTION WITH RECORD OF BOREHOLES AND REPORT
 - THIS DRAWING IS FOR SUBSURFACE INFORMATION ONLY. SURFACE DETAILS AND FEATURES ARE FOR CONCEPTUAL ILLUSTRATION.
 - DIMENSIONS ARE IN METRES AND/OR MILLIMETRES UNLESS OTHERWISE SHOWN. STATIONS ARE IN KILOMETRES AND METRES.




Reference MTO Drawing:
Bayfield-Plan.dwg; and Base-Gray.dwg both undated

REVISIONS	DATE	BY	DESCRIPTION

Geocres No. 31D-582


HWY No	400	DIST	CENTRAL
SUBMTD	NA	CHECKED	AD
DATE	NOV. 18, 2014	SITE	
DRAWN	NA	CHECKED	DD
APPROVED	CN	DWG	B-1



LEGEND

- Borehole
- Borehole and cone
- Cone penetration test
- N Blows/0.3m (Std. Pen Test, 475 J/blow)
- CONE Blows/0.3m (60° Cone, 475 J/blow)
- W L at time of investigation June 2014
- Head
- ARTESIAN WATER Encountered
- PIEZOMETER

BH No	ELEVATION	COORDINATES NORTHINGS	EASTINGS
1	252.4	4 917 125.1	288 637.8
1A	245.1	4 917 133.1	288 616.7



- NOTES:
- THIS DRAWING SHOULD BE READ IN CONJUNCTION WITH RECORD OF BOREHOLES AND REPORT
 - THIS DRAWING IS FOR SUBSURFACE INFORMATION ONLY. SURFACE DETAILS AND FEATURES ARE FOR CONCEPTUAL ILLUSTRATION.
 - DIMENSIONS ARE IN METRES AND/OR MILLIMETRES UNLESS OTHERWISE SHOWN. STATIONS ARE IN KILOMETRES AND METRES.



NOTE
 The boundaries between soil strata have been established only at Borehole locations. Between Boreholes the boundaries are assumed from geological evidence.

REVISIONS	DATE	BY	DESCRIPTION

Reference MTO Drawing:
 Bayfield-Plan.dwg; and Base-Gray.dwg both undated

HWY No	400	DIST	NORTH BAY
SUBMTD	NA	CHECKED	AD
DATE	NOV. 12, 2014	SITE	
DRAWN	NA	CHECKED	DD
APPROVED	CN	DWG	B-2