

# 66-F-39

W.P. # 110-66-9

PROPOSED

COMMUTER STN.

PEDESTRIAN

UNDERPASS

SCARBOROUGH

MEMORANDUM

To: Mr. W. D. Ratz,  
Superintendent of Land Surveys,  
Right-of-Way Division,  
Admin. Bldg.  
Attn: Mr. B. Wright,  
Drafting Chief Inspector.

FROM: Foundation Section,  
Materials and Testing Division,  
Room 107, Lab. Bldg.

DATE: May 17, 1966

OUR FILE REF.

IN REPLY TO

JUN 1 1966

SUBJECT:

FOUNDATION INVESTIGATION REPORT  
For  
Proposed Commuter Station  
Pedestrian Underpass - Scarborough  
District #6 (Toronto)  
W.J. 66-F-39 -- W.P. 110-66-9

Attached, we are forwarding to you, our foundation investigation report on the subsoil conditions existing at the above structure site.

We believe that you will find the factual data and recommendations contained therein, adequate for your design requirements. Should additional information be required, please feel free to contact our Office.

AGS/MdeF  
Attach.

*Afternoon*  
A. G. Stermac,  
PRINCIPAL FOUNDATION ENGINEER

cc: Messrs. W. D. Ratz (4)  
J. C. Thatcher  
T. J. Kovich  
Foundations Office  
Gen. Files ✓

FOUNDATION INVESTIGATION REPORT  
For  
Proposed Commuter Station  
Pedestrian Underpass - Scarborough  
District #6 (Toronto)  
W.J. 66-F-39      --      W.P. 110-66-9

A request to investigate the foundation conditions at the location of the above proposed underpass, was received by this Section, from Mr. B. Wright, Chief Inspector of Surveys. Subsequently an investigation consisting of two sampled boreholes, was carried out at this site. Presented in this report are the field data and laboratory results, together with our recommendations pertaining to the structure foundations.

A thin layer of topsoil is underlain by a stratum of clayey silt with sand extending to about 47 ft. in both boreholes. In borehole #2, a thin layer of dense (32 to 34 blows/ft.) silty sand was encountered between 12 and 18 ft. The 'N' values for the clayey silt with sand stratum ranged at random from 14 blows/ft. to 52 blows/ft. Wherever possible, an attempt was made to carry out in-situ vane shear strength measurements. In general, these vary from 1760 p.s.f. to more than 2000 p.s.f. The undrained shear strength of this deposit, as determined in the laboratory, ranged in general, from 1400 p.s.f. to 1800 p.s.f. However, below approximate elev. 505, and above the silty sand deposit, the strength of the stratum ranged from 600 p.s.f. to 1100 p.s.f.

The clayey silt with sand stratum is underlain by a deposit of silty sand. Penetration into the deposit was about 5 ft. in both boreholes. Standard Penetration test (N) values vary from 41 blows/ft. to 85 blows/6 in., from which a relative density of dense to very dense may be estimated.

Water level observations in the boreholes were carried out during the time of the investigation. These show the water table to be about 2 ft. below the ground level in both boreholes.

cont'd. /2 .....

At the time of writing this report, design details pertaining to the proposed pedestrian underpass are not available. However, it was assumed that the future structure may be located some 11 ft. below the bottom of the tracks at approximate elev. 529<sup>+</sup>. At this elevation the subsoil consists of stiff clayey silt with sand on the north side of the tracks, and of dense silty sand on the south side of the tracks. A safe design load of 1 t.s.f. may be used for design purposes for the proposed structure. Since the structure may be partially founded in the silty sand stratum, a dewatering scheme may be required. Consideration should also be given to locating the structure at or below elev. 525 in order to avoid any major dewatering problems.

It should be noted that the recommendations given in this report are conditional only, and are subject to revision at a later date when and if new design information becomes available.

The field investigation, performed in April 1966, together with the preparation of this report, was undertaken by Mr. R. Magi, Project Foundation Engineer. The investigation was carried out under the general supervision of Mr. M. Devata, Senior Foundation Engineer, who also reviewed this report.

Equipment was owned and operated by Dominion Soil Investigation Ltd. of Toronto.

May 1966

APPENDIX I.

## RECORD OF BOREHOLE NO. 1

FOUNDATION SECTION

## MATERIALS &amp; TESTING DIVISION

JOB 66-F-39LOCATION See DWG 66-F-39AORIGINATED BY RMW.P. 110-66-9BORING DATE April 28, 1966COMPILED BY RMDATUM GeodeticBOREHOLE TYPE Penn AugerCHECKED BY AK

SOIL PROFILE			SAMPLES			ELEV. SCALE	DYNAMIC PENETRATION RESISTANCE BLOWS / FOOT		LIQUID LIMIT — <u>WL</u> PLASTIC LIMIT — <u>WP</u> WATER CONTENT — <u>W</u>		BULK DENSITY P.C.F.	REMARKS	
ELEV. DEPTH	DESCRIPTION	STRAT. PLOT	NUMBER	TYPE	BLOWS / FOOT		SHEAR STRENGTH P.S.F. + Field Vane • Quick Triaxial		WATER CONTENT %				
544.6	Ground Level						500	1000	1500	2000	2500		
0													
	Clayey Silt with Sand		1	SS	17	540							
			2	SS	52								
			3	SS	51								
			4	SS	30	530							
			5	SS	17								
	Firm to Hard		6	TW	PH								
			7	TW	PH	520							
			8	TW	PH								
			9	SS	43								
			10	SS	31	510							
			11	TW	PH								
			12	SS	14								
498.6			13	TW	PH	500							
46	Silty Sand		14	SS	41								
493.1	Dense to V. Dense		15	SS	55/6"								
51.5	End of Borehole												

20  
15 — 5 Strain at Failure  
10

W.L. Elev  
542.7

## MATERIALS &amp; TESTING DIVISION

## RECORD OF BOREHOLE NO. 2

FOUNDATION SECTION



JOB 66-F-39LOCATION See DWG 66-F-39AORIGINATED BY RMW.P. 110-66-9BORING DATE April 29, 1966COMPILED BY RMDATUM GeodeticBOREHOLE TYPE Penn AugerCHECKED BY HR

SOIL PROFILE			SAMPLES			ELEV. SCALE	DYNAMIC PENETRATION RESISTANCE BLOWS / FOOT					LIQUID LIMIT — WL PLASTIC LIMIT — WP WATER CONTENT — W			BULK DENSITY P.C.F.	REMARKS
ELEV. DEPTH	DESCRIPTION	STRAT. PLOT	NUMBER	TYPE	BLOWS / FOOT		SHEAR STRENGTH P.S.F. + Field Vane • Quick Triaxial					WATER CONTENT %				
543.9	Ground Level						500	1000	1500	2000	2500					
0	Clayey Silt with Sand		1	SS	19	540										
			2	SS	35											
			3	SS	47											
531.9	Silty Sand		4	SS	34	530										
12	Dense		5	SS	32											
525.9			6	SS	34	520										
18	Stiff to Hard		7	SS	30											
			8	SS	29	510										
			9	SS	16											
			10	Tw	PH											
			11	SS	20	500										
496.9			12	SS	60/6"											
47	Silty Sand															
492.4	Very Dense															
51.5	End of Borehole															

W.L. Elev = 541.9

Percent Strain at Failure

20  
15 — 5  
10



SCALE : 1 inch = 20 feet

REF NO: M-4115



DEPARTMENT OF HIGHWAYS  
MATERIALS and  
TESTING  
DIVISION

PROPOSED PEDESTRIAN UNDERPASS  
SCARBOROUGH COMMUTER STATION  
CANADIAN NATIONAL RAILWAYS

W.P.110-66-9

DIST: 6

JOB: 66-F-39

DATE 26 MAY, 1966

APPROVED

*W. Davata*

DRAWING NO. 66-F-39 A



## ABBREVIATIONS USED IN THIS REPORT

### PENETRATION RESISTANCE

STANDARD PENETRATION RESISTANCE 'N' :- THE NUMBER OF BLOWS REQUIRED TO ADVANCE A STANDARD SPLIT SPOON SAMPLER 12 INCHES INTO THE SUBSOIL, DRIVEN BY MEANS OF A 140 POUND HAMMER FALLING FREELY A DISTANCE OF 30 INCHES.

DYNAMIC PENETRATION RESISTANCE :- THE NUMBER OF BLOWS REQUIRED TO ADVANCE A 2 INCH, 60 DEGREE CONE, FITTED TO THE END OF DRILL RODS, 12 INCHES INTO THE SUBSOIL, THE DRIVING ENERGY BEING 350 FOOT POUNDS PER BLOW.

### DESCRIPTION OF SOIL

THE CONSISTENCY OF COHESIVE SOILS AND THE RELATIVE DENSITY OR DENSENESS OF COHESIONLESS SOILS ARE DESCRIBED IN THE FOLLOWING TERMS:-

<u>CONSISTENCY</u>	<u>'N' BLOWS / FT.</u>	<u>c LB. / SQ. FT.</u>	<u>DENSENESS</u>	<u>'N' BLOWS / FT.</u>
VERY SOFT	0 - 2	0 - 250	VERY LOOSE	0 - 4
SOFT	2 - 4	250 - 500	LOOSE	4 - 10
FIRM	4 - 8	500 - 1000	COMPACT	10 - 30
STIFF	8 - 15	1000 - 2000	DENSE	30 - 50
VERY STIFF	15 - 30	2000 - 4000	VERY DENSE	> 50
HARD	> 30	> 4000		

### TYPE OF SAMPLE

S.S.	SPLIT SPOON	T.W.	THINWALL OPEN
W.S.	WASHED SAMPLE	T.P.	THINWALL PISTON
S.B.	SCRAPER BUCKET SAMPLE	O.S.	OESTERBERG SAMPLE
A.S.	AUGER SAMPLE	F.S.	FOIL SAMPLE
C.S.	CHUNK SAMPLE	R.C.	ROCK CORE
S.T.	SLOTTED TUBE SAMPLE		
	P.H. SAMPLE ADVANCED HYDRAULICALLY		
	P.M. SAMPLE ADVANCED MANUALLY		

### SOIL TESTS

Qu	UNCONFINED COMPRESSION	L.V.	LABORATORY VANE
Q	UNDRAINED TRIAXIAL	F.V.	FIELD VANE
Qcu	CONSOLIDATED UNDRAINED TRIAXIAL	C	CONSOLIDATION
Qd	DRAINED TRIAXIAL	S	SENSITIVITY

# ABBREVIATIONS USED IN THIS REPORT

## SOIL PROPERTIES

$\gamma$	UNIT WEIGHT OF SOIL (BULK DENSITY)
$\gamma_s$	UNIT WEIGHT OF SOLID PARTICLES
$\gamma_w$	UNIT WEIGHT OF WATER
$\gamma_d$	UNIT DRY WEIGHT OF SOIL (DRY DENSITY)
$\gamma'$	UNIT WEIGHT OF SUBMERGED SOIL
G	SPECIFIC GRAVITY OF SOLID PARTICLES $G = \frac{\gamma_s}{\gamma_w}$
e	VOID RATIO
n	POROSITY
w	WATER CONTENT
$S_r$	DEGREE OF SATURATION
$w_L$	LIQUID LIMIT
$w_p$	PLASTIC LIMIT
$I_p$	PLASTICITY INDEX
s	SHRINKAGE LIMIT
$I_L$	LIQUIDITY INDEX = $\frac{w - w_p}{I_p}$
$I_C$	CONSISTENCY INDEX = $\frac{w_L - w}{I_p}$
$e_{max}$	VOID RATIO IN LOOSEST STATE
$e_{min}$	VOID RATIO IN DENSEST STATE
$I_D$	DENSITY INDEX = $\frac{e_{max} - e}{e_{max} - e_{min}}$
	RELATIVE DENSITY $D_r$ IS ALSO USED
h	HYDRAULIC HEAD OR POTENTIAL
q	RATE OF DISCHARGE
v	VELOCITY OF FLOW
i	HYDRAULIC GRADIENT
k	COEFFICIENT OF PERMEABILITY
j	SEEPAGE FORCE PER UNIT VOLUME
$m_v$	COEFFICIENT OF VOLUME CHANGE = $\frac{-\Delta e}{(1+e)\Delta\sigma}$
$c_v$	COEFFICIENT OF CONSOLIDATION
$C_c$	COMPRESSION INDEX = $\frac{\Delta e}{\Delta \log_{10} \sigma}$
$T_v$	TIME FACTOR = $\frac{c_v t}{d^2}$ (d, DRAINAGE PATH)
U	DEGREE OF CONSOLIDATION
$\tau_f$	SHEAR STRENGTH
$c'$	EFFECTIVE COHESION
$\phi'$	EFFECTIVE ANGLE OF SHEARING RESISTANCE, OR FRICTION
$c_u$	APPARENT COHESION
$\phi_u$	APPARENT ANGLE OF SHEARING RESISTANCE, OR FRICTION
$\mu$	COEFFICIENT OF FRICTION
$S_s$	SENSITIVITY

## GENERAL

$\pi$	= 3.1416
e	BASE OF NATURAL LOGARITHMS 2.7183
$\log_e a$ OR $\ln a$	NATURAL LOGARITHM OF a
$\log_{10} a$ OR $\log a$	LOGARITHM OF a TO BASE 10
t	TIME
g	ACCELERATION DUE TO GRAVITY
V	VOLUME
W	WEIGHT
M	MOMENT
F	FACTOR OF SAFETY

## STRESS AND STRAIN

u	PORE PRESSURE
$\sigma$	NORMAL STRESS
$\sigma'$	NORMAL EFFECTIVE STRESS ( $\bar{\sigma}$ IS ALSO USED)
$\tau$	SHEAR STRESS
$\epsilon$	LINEAR STRAIN
$\gamma$	SHEAR STRAIN
$\nu$	POISSON'S RATIO ( $\mu$ IS ALSO USED)
E	MODULUS OF LINEAR DEFORMATION (YOUNG'S MODULUS)
G	MODULUS OF SHEAR DEFORMATION
K	MODULUS OF COMPRESSIBILITY
$\eta$	COEFFICIENT OF VISCOSITY

## EARTH PRESSURE



d	DISTANCE FROM TOP OF WALL TO POINT OF APPLICATION OF PRESSURE
$\delta$	ANGLE OF WALL FRICTION
K	DIMENSIONLESS COEFFICIENT TO BE USED WITH VARIOUS SUFFIXES IN EXPRESSIONS REFERRING TO NORMAL STRESS ON WALLS
$K_0$	COEFFICIENT OF EARTH PRESSURE AT REST

## FOUNDATIONS

B	BREADTH OF FOUNDATION
L	LENGTH OF FOUNDATION
D	DEPTH OF FOUNDATION BENEATH GROUND
N	DIMENSIONLESS COEFFICIENT USED WITH A SUFFIX APPLYING TO SPECIFIC GRAVITY, DEPTH AND COHESION ETC. IN THE FORMULA FOR BEARING CAPACITY
$k_s$	MODULUS OF SUBGRADE REACTION

## SLOPES

H	VERTICAL HEIGHT OF SLOPE
D	DEPTH BELOW TOE OF SLOPE TO HARD STRATUM
$\beta$	ANGLE OF SLOPE TO HORIZONTAL



A — A

SCALE : 1 inch = 20 feet

REF NO. M-4115



ONTARIO

DEPARTMENT OF HIGHWAYS  
MATERIALS and  
TESTING  
DIVISION

PROPOSED PEDESTRIAN UNDERPASS  
SCARBOROUGH COMMUTER STATION  
CANADIAN NATIONAL RAILWAYS

W.P.110-66-9

DIST. 6

JOB.66-F-39

DATE 26 MAY, 1966

APPROVED

*[Signature]*

DRAWING NO. 66-F-39 A