

DOCUMENT MICROFILMING IDENTIFICATION

GEOCRES No. 30M13-137

DIST. 6 REGION

W.P. No. 528-91-01

(formerly 612-89-00)

CONT. No. 93-72

W. O. No.

STR. SITE No.

HWY. No. 400

LOCATION thwy 400 from Hwy 7 to N of
Langstaff Rd. — H.M.L Poles

No of PAGES -

=====

OVERSIZE DRAWINGS TO BE INCLUDED WITH THIS REPORT.

REMARKS:

G.I.-30 SEPT. 1976

memorandum



FILE COPY

To: Mr. V. F. Boehnke
Head, Structural Section
4th Floor, Atrium Tower
Central Region

Date: 1992 03 09

Att: Mr. Dennis Wong

From: Foundation Design Section
Room 315, Central Building
Downsview, Ontario

Re: Proposed High Mast Lighting
Highway 400/Highway 7 to North of Langstaff Road
W.P. 528-91-01
Central Region
District 6, Toronto *CONT 93-72*

GEOGRES NO 30M13-137

The attached report provides recommendations for the 22 proposed high mast light poles (P2 through P23) to be located at the above-captioned site.

We believe that this report is adequate for your present purposes. However, should you have any questions regarding it, please do not hesitate to contact this office.

John A. Blair

J. A. Blair, P.Eng.
Project Foundation Engineer

For

D.H. Dundas, P.Eng.
Sr. Foundation Engineer

Distribution

V.F. Boehnke (3)
G. Cautillo
J. Cullen (2)
A. Wittenberg
K.G. Bassi
S. J. Dunham
E. A. Joseph
I. Harrod (Cover Only)
F. Bacchus (Cover Only)
✓ File Copy

FOUNDATION INVESTIGATION REPORT
For
Proposed High Mast Lighting
Highway 400/Highway 7 to North of Langstaff Road
W.P. 528-91-01
Central Region
District 6, Toronto

GEOCRES No 30M13-137

INTRODUCTION

At the request of the Central Region, Structural Section, a foundation investigation was carried out at the above-captioned site between January 6 and 13, 1992 for 22 proposed high mast light poles (P2 through P23) to be located along Highway 400 between Highway 7 and Rutherford Road and shown on Drawing No. 5289101-A (Sheets 1 to 4).

SITE DESCRIPTION AND GEOLOGY

The site is located along Highway 400 between approximately 200 m north of Highway 7 to about 700 m north of Langstaff Road, in the Town of Vaughan, Regional Municipality of York. The topography of the area is generally flat with a slight increase in elevation towards the north. Drainage is generally towards the southeast.

Physiographically, the site is located in the Peel Plain which, consists of a level-to-undulating tract of clayey soils which covers parts of York, Peel and Halton counties. In this area, the soil is known to consist of glacial till. However, in much of the Peel Plain, the till has been modified by a veneer of clay which, when deep enough, is clearly seen to be varved. It is thought that the clay veneer was deposited in a temporary lake impounded between higher land to the north and the ice lobe in the Ontario basin (Reference: Chapman and Putnam, "The Physiography of Southern Ontario"; 3rd Edition, 1984).

PROCEDURES

The fieldwork was carried out between January 6 and 13, 1992 and consisted of a total of twelve (12) sampled boreholes (including 5 under Ref. No.'s W.P. 527-91-01(A) and W.P. 527-91-01(B)) which were advanced to depths of from 7.6 to 11.1 m. Most of the boreholes were advanced using continuous flight, solid stem augers driven by a bombardier-mounted drilling rig equipped with standard soil sampling equipment. However, one of the boreholes (BH7), was drilled along the centreline of the highway using a truck-mounted drilling rig.

Groundwater levels were measured in several of the open boreholes immediately upon completion of sampling and most were left open for subsequent measurements. Piezometers were installed in three of the boreholes, in order to measure the long term groundwater conditions.

Generally, the locations of the boreholes were staked in the field, and their elevations determined by the Central Region Surveys and Plans Office. However, since Borehole 7 was located close to the centreline of Highway 400, its location and elevation was determined by our field representative.

The soil samples, which were obtained in the field, were examined in the laboratory by visual and tactile methods. Moisture content and Atterberg Limits tests were carried out on selected soil samples.

SUBSURFACE CONDITIONS

The subsurface conditions, at the boreholes, generally consist of a surficial layer of topsoil and/or fill from 0.1 to 2.1 m thick, which, at most locations, is underlain by a layer (up to 3 m thick) of silty clay. The silty clay is, in turn, underlain by a heterogeneous mixture of clayey silt, some sand with a trace of gravel (glacial till). Silt to silty sand deposits occur in random zones within the till, although major ones appear to be confined to certain elevations. The groundwater table was found to be at or close to the original ground surface (ie. prior to construction of Highway 400) or elevations respectively ranging from 208.1 to 203.5 m at the north and south ends of the area of investigation.

Details of the subsurface information obtained from this investigation are included on the borehole logs at the back of this report. Selected borehole logs from two previous investigations (W.P. 164-79-04/05 and W.O. 89-11001) are included in the Appendix.

Brief descriptions of the individual soil strata and the groundwater conditions encountered in the boreholes are given below.

Topsoil

In the ditches or flatter areas adjacent to the Highway 400 embankment (ie. Boreholes 4, 6, 8, 10 and 11), a surficial layer of dark brown to black, soft to firm, topsoil, up to 0.5 m thick was encountered in the boreholes.

Distinct topsoil or organic silty clay layers, 0.8 and 0.3 m thick, were also found beneath the granular and other embankment fills at Boreholes 5 and 7, respectively.

Pavement Structure

A thin layer (230 mm thick) of asphalt was contacted at the ground surface at Borehole 7.

Sand to sand and gravel (Fill), from 0.2 to 0.9 m thick, was found beneath the asphalt at Borehole 7 and contacted at the ground surface at Boreholes 1 to 3, 5, 7, and 9. Penetration resistances or 'N-values' in this fill ranged from 5 to 11 blows/0.3 m, indicating generally loose, (although occasionally compact) conditions.

Silty Clay (Fill)

At several locations (Boreholes 1, 2, 3, 5, 7, 9, and 14) the granular fill was found to be underlain by a silty clay deposit containing topsoil enclosures from .4 to 1.7 m thick (ie. to depths of 0.5 to 1.9 m). This material represents the lower portion of the embankment fills.

At Borehole 4, the surficial layer of topsoil noted above was found to be underlain by a thin (0.1 to 0.2 m thick) layer of a similar silty clay material containing topsoil enclosures. This material has also been referred to as fill, since it appears that these soils have been disturbed by past farming activity which has resulted in topsoil enclosures becoming entrained into it.

'N'-values of 2 to 10 blows/0.3 m indicate that the silty clay fills vary from soft to stiff consistency, although they can generally be considered firm.

Silty Clay

Beneath the fill materials described above, Boreholes 1 and 5 to 11 contacted a brown to grey, silty clay layer from 0.2 to 2.9 m thick. This layer extended to depths 1.4 to 3.7 m (or elevations of 202.3 to 206.2 m).

'N'-values measured in this silty clay layer ranged from 5 to 15 blows/0.3 m indicating soils of generally firm to stiff consistency.

Heterogeneous Mixture of Clayey Silt, some Sand, trace Gravel
(Glacial Till)

A heterogenous mixture of brown to grey, clayey silt with some sand and a trace of gravel with occasional cobbles and boulders, from 5.0 m up to at least 8.2 m thick, was encountered in all of the boreholes, at depths of 0.6 to 3.7 m (or elevations of 201.7 to 207.4 m).

Visual examination of this soil indicates that it is likely to be of glacial origin and therefore, may be considered to be a glacial till.

'N'-values measured during Standard Penetration Testing ranged from 11 to 50 blows/0.08 m indicating soils of stiff to hard consistency.

Silt to Fine Sand

Cohesionless layers and zones of silt to fine sand were encountered within the clayey silt till at various depths. Although they were often found to be thin (ie. less than 0.5 m thick) and discontinuous, major ones appeared in several boreholes.

Major seams or zones of silt to fine sand with occasional clayey silt interbeds were generally found below elevations of 197 to 199 m south of Borehole 3, between elevations of 201 and 203 m at Boreholes 5 to 9, between elevations of 204 to 206 m at Boreholes 9 to 11 and below elevations of 199 to 202 m at Boreholes 10 and 11.

At Borehole 4, a major cohesionless zone (at least 6.0 m thick) was found below an elevation of 203 m and, with the exception of a small intrusion of clayey silt till, extended to the maximum depth explored in that borehole. Cohesionless zones, which were encountered at Boreholes 1, 3 and 10, at depths of 8.6 to 9.6 m, also extended to the maximum depth explored in those boreholes (ie. indicating thicknesses of greater than 1.5 to 2.5 m).

'N'-values ranged from 11 to 53 blows/0.3 m indicating compact to very dense conditions in these cohesionless zones.

Groundwater Conditions

The groundwater levels, when measured in the open boreholes, immediately upon completion of sampling, were found to be from the ground surface to depths of 7.4 m. However, water levels, measured in the open boreholes at least 24 hours after completion of sampling ranged from the ground surface to depths of 2.2 m (or elevations of 203.5 to 208.1 m).

Groundwater levels, measured in the three piezometers installed at the site ranged from depths of about 0.1 to 0.4 m (or elevations of 205 to 207.3 m)

It appears that the groundwater table is at or slightly below the original ground surface (ie. prior to the construction of the Highway 400 embankment) and generally slopes with the ground surface towards the south from elevations of 208.1 at Borehole 9 to 203.5 m at Borehole 2, respectively.

DISCUSSIONS AND RECOMMENDATIONS

General

It is proposed to construct the 22 high mast light poles, listed in Table I, at the locations shown on Drawing No. 1228700-A.

During this investigation, seven (7) of the boreholes (Boreholes 1 to 5, 9 and 14), which were drilled under this reference number (ie. W.P. 528-91-01), provided information for 14 of the proposed high mast light poles. Information for two more proposed high mast lights was obtained from five (5) more boreholes (Boreholes 6 to 8, 10 and 11), which were drilled during the same time period, for two culverts under Ref. No.'s. W.P. 527-91-01(A) and W.P. 527-91-01(B).

Subsurface information for the remaining 6 high mast light poles was obtained from boreholes drilled during two previous investigations (ie. W.P. 164-79-04/05, dated September, 1985 and W.O. 89-11001, dated February, 1989).

Design

The loads from these high mast light poles may be transferred to the subsoil by means of a cast-in-place concrete caisson.

Caissons should be founded at the maximum elevation needed to provide the required lateral resistance. The design of the caissons should be in accordance with the method outlined in the following papers for both cohesive and cohesionless soils:

Brohms, B. B. Lateral Resistance of Piles in Cohesive Soil
Journal of the Soil Mechanics and Foundation Division, ASCE
Vol. 90, No. SM2, Paper 3285, March 1964.

Brohms, B. B. Lateral Resistance of Piles in Cohesionless Soil,
Journal of the Soil Mechanics and Foundation Division,
ASCE Vol. 90, No. SM3, Paper 3909, May 1964.

Based on the boreholes drilled during this and the previous investigations, the calculated parameters to be used for the design of each of the 22 high mast light poles are outlined in Table II and include:

For Cohesionless Soils: The Angle of Internal Friction ϕ (degrees)

For Cohesive Soils: The Unconfined Compressive Strength q_u (KPa)

Bulk Unit Weight: γ (kN/m³)

It should be noted, that soils within 1.2 m of the finished ground surface are within the frost zone and should not be included in the calculation for lateral resistance.

It should also be noted that the stratigraphy at all of the proposed high mast light locations have been based on stratigraphical projections from surrounding boreholes drilled during this and previous investigations. Therefore, the elevations shown on Table II can only be considered approximate.

It appears that the grade at high mast pole P15, is to be raised by 1.5 m. In this and similar areas, it is recommended that the following design parameters may be applied to fill materials placed and compacted to at least 95 percent of its Standard Proctor Maximum Dry Density:

$$\phi = 28 \text{ degrees}$$

$$\gamma = 20 \text{ kN/m}^3$$

Construction Considerations

Caissons will encounter random, saturated cohesionless zones below the groundwater table. Although such conditions are likely to cause difficulties at any of the high mast pole locations, the following locations and elevations are likely to be the most susceptible to such problems:

<u>High Mast Pole #</u>	<u>Elevation (m)</u>
P2	Below 192
P5	Below 194.5
P6	Below 195
P9	Below 197.5


<u>High Mast Pole #</u>	<u>Elevation</u> <u>(m)</u>
P10	Below 199
P11	Below 201.5
P12	Between 200.5 and 203.0 and Below 199.5
P13	Below 199.0
P14	Below 199.5
P16	Below 199.0
P17	Between 203.5 and 201.5
P18	Between 203.5 and 201.3
P19	Between 203.5 and 201.5
P20	Between 202.5 and 201.5
P21	Between 206.5 and 205.5 and Between 203 and 201
P22	Between 206.5 and 205.5 (and possibly between 203.0 and 201.0)

A copy of the special provisions for the construction of the caisson foundations for the high mast light poles is provided in the Appendix.

MISCELLANEOUS

The field investigation was supervised by Mr. J. Blair using equipment owned and operated by Malone's Soil Samples Inc.

This report was written by Mr. J. Blair, Project Foundation Engineer, reviewed by Mr. D. Dundas, Senior Foundation Engineer and approved by Mr. M. Devata, Chief Foundation Engineer.



John A. Blair

J. A. Blair, P.Eng.
Project Foundation Engineer

M. Devata

M. Devata, P.Eng.
Chief Foundation Engineer

Table I

High Mast Light Pole Locations
Highway 400 and Langstaff Road

<u>Pole #</u>	<u>Northing</u>	<u>Easting</u>	Ground Surface Existing <u>(m)</u>	Elevations Proposed <u>(m)</u>
P2	4 850 270.2	301 556.9	201.0	200.9
P3	4 850 388.5	301 536.7	202.2	202.1
P4	4 850 516.6	301 514.7	203.5	203.5
P5	4 850 647.7	301 492.3	204.5	204.5
P6	4 850 785.7	301 468.7	205.1	205.1
P7	4 850 923.7	301 445.0	205.6	205.5
P8	4 851 060.7	301 421.5	206.1	206.0
P9	4 851 196.8	301 398.2	206.5	206.5
P10	4 851 331.8	301 375.1	207.1	207.0
P11	4 851 467.3	301 351.9	207.6	207.6
P12	4 851 604.3	301 328.4	207.9	207.9
P13	4 851 723.1	301 308.1	207.1	207.3
P14	4 851 860.1	301 284.7	206.9	206.9
P15	4 851 876.5	301 149.4	209.7	211.2
P16	4 851 807.4	301 379.9	205.1	205.1
P17	4 851 922.2	301 377.5	205.0	205.5
P18	4 851 970.9	301 170.3	205.8	205.8
P19	4 852 002.5	301 260.3	207.3	207.1
P20	4 852 145.0	301 235.9	207.6	207.6
P21	4 852 292.8	301 210.6	208.1	208.1
P22	4 852 439.7	301 185.4	208.8	208.8
P23	4 852 588.1	301 163.5	209.3	209.3

TABLE II
Design Parameters for
High Mast Light Poles
Highway 400 and Langstaff Road
W.P. 528-91-01

Pole #	Approximate Ground Surface Elev.		Soil Boundary Elevation		Cohesive/ Non-Cohesive	Design Parameters			Assumed Water level	Closest Boreholes
	Existing (m)	Ultimate (m)	Upper (m)	Lower (m)		Degrees ϕ	kPa q_u	kN/m ³ γ		
P2	201.0	200.9	201.0	199.5	Non-Cohesive	30		20	199.5	C8, C10 (WP 164-79-04/05)
			199.5	197.0	Cohesive		100	19.5		
			197.0	192.0	Cohesive		500	21.0		
			<192.0		Non-Cohesive	36		20		
P3	202.2	202.1	202.2	200	Non-Cohesive	30		20	200.0	C10, C11 (WP 164-79-04/05)
			200	198.5	Cohesive		100	19.5		
			198.5	192.5	Cohesive		500	21		
			<192.5		Non-Cohesive	36		21		
P4	203.5	203.5	203.5	202.3	Non-Cohesive	30		20	201.0	C11 (WP 164-79-04/05)
			202.3	201.0	Cohesive		50	17		
			201.0	198.5	Cohesive		200	19.5		
			<198.5		Cohesive		500	21.0		
P5	204.5	204.5	204.5	203.5	Non-Cohesive	30		20	202.5	C11 (WP 164-79-04/05)
			203.5	202.0	Cohesive		50	17		
			202.0	198.5	Cohesive		250	20		
			198.5	194.7	Cohesive		400	21.0		
P6	205.1	205.1		<194.7	Non-Cohesive	36		21.0	202.2	1
			205.1	204.0	Non-Cohesive	30		20		
			204.0	203.0	Cohesive		50	17		
			203.0	199.0	Cohesive		250	20		
P6	205.1	205.1	199	195.0	Cohesive		400	21	202.2	1, 2
			<195		Non-Cohesive	36		20		

TABLE II
Design Parameters for
High Mast Light Poles
Highway 400 and Langstaff Road
W.P. 528-91-01

Pole #	Approximate Ground Surface Elev.		Soil Boundary Elevation		Cohesive/ Non-Cohesive	Design Parameters			Assumed Water Level	Closest Boreholes
	Existing (m)	Ultimate (m)	Upper (m)	Lower (m)		Degrees ϕ	kPa q_u	kN/m ³ γ		
P7	205.6	205.5	205.5	204.5	Non-Cohesive	30		20	203.0	2, 1
			204.5	203.5	Cohesive		50	17		
			203.5	201.0	Cohesive		250	20		
			201.0	196.0	Cohesive		500	21		
			<196		Non-Cohesive	36		20		
P8	206.1	206.0	206.1	204.8	Non-Cohesive	30		20	204.0	2, 3
			204.8	203.8	Cohesive		50	17		
			203.8	201.5	Cohesive		250	20		
			201.5	196.5	Cohesive		500	21		
			<196.5		Non-Cohesive	36		20		
P9	206.5	206.5	205.5	205.0	Non-Cohesive	30		20	204.5	3, 2
			205.0	202	Cohesive		200	20		
			202	197.5	Cohesive		400	21		
			<197.5		Non-Cohesive	36		20		
P10	207.1	207.0	207.1	205.5	Non-Cohesive		30	20	205.0	3, 4
			205.5	202.5	Cohesive		250	20		
			202.5	199.0	Cohesive		400	21		
			<199.0		Non-Cohesive	36		20		
P11	207.6	207.6	207.6	206.4	Non-Cohesive	30		20	205.5	4, 3
			206.4	205.5	Cohesive		50	17		
			205.5	203.5	Cohesive		250	20		
			203.5	201.5	Cohesive		500	21		
			<201.5		Non-Cohesive	34		20		

TABLE II
Design Parameters for
High Mast Light Poles
Highway 400 and Langstaff Road
W.P. 528-91-01


Pole #	Approximate Ground Surface Elev.		Soil Boundary Elevation		Cohesive/ Non-Cohesive	Design Parameters			Assumed Water level	Closest Boreholes
	Existing (m)	Ultimate (m)	Upper (m)	Lower (m)		Degrees ϕ	kPa q_u	kN/m ³ γ		
P12	207.9	207.9	207.9	206.5	Non-Cohesive	30		20	205.5	4, 5
			206.5	205.0	Cohesive		50	13		
			205.0	203.0	Cohesive		250	20		
			203.0	200.5	Non-Cohesive	34		20		
			200.5	199.5	Cohesive		400	21		
			<199.5		Non-Cohesive	33		20		
P13	207.1	207.3	207.1	206.1	Non-Cohesive	30		20	205.5	5, 4
			206.1	205	Cohesive		20	10		
			205	204	Cohesive		150	19		
			204	202	Cohesive		250	20		
			202	199	Cohesive		400	21		
			<199		Non-Cohesive	33		20		
P14	206.9	206.9	206.9	206.5	Non-Cohesive	30		20	205.5	5, 7
			206.5	205	Cohesive		20	10		
			205.0	204	Cohesive		150	19		
			204	201.5	Cohesive		250	20		
			201.5	198.5	Cohesive		400	21		
			<198.5		Non-Cohesive	33		20		
P15	209.7	211.2	209.7	208.5	Non-Cohesive	30		20	205.0	1, 2 (W.O. 89-11001)
			208.5	206.5	Cohesive		50	17		
			206.5	203.5	Cohesive		150	20		
			203.5	201.5	Non-Cohesive	30		19		
			<201.5		Cohesive		500	21		

TABLE II
Design Parameters for
High Mast Light Poles
Highway 400 and Langstaff Road
W.P. 528-91-01

Pole #	Approximate Ground Surface Elev.		Soil Boundary Elevation		Cohesive/ Non-Cohesive	Design Parameters			Assumed Water level	Closest Boreholes
	Existing (m)	Ultimate (m)	Upper (m)	Lower (m)		Degrees ϕ	kPa qu	kN/m ³ γ		
P16	205.1	205.1	205.1	203.9	Cohesive		100	20	204.5	5 (W.O. 89-11001) 5
			203.9	199.0	Cohesive		250	20		
			<199		Non-Cohesive	32		20		
P17	205.0	205.5	205.0	203.5	Cohesive		100	19	203.5	5 (W.O. 89-11001) 5
			203.5	201.5	Non-Cohesive	32		19		
			<201.5		Non-Cohesive	34		20		
P18	205.8	205.8	205.8	203.5	Cohesive		150	19	205.5	2 (W.O. 89-11001) 5
			203.5	201.3	Non-Cohesive	34		20		
			<201.3		Cohesive		400	21		
P19	207.3	207.1	207.3	206.0	Non-Cohesive	29		18	205.0	4 (W.O. 89-1001) 7
			206.0	204.5	Cohesive		50	17		
			204.5	203.5	Cohesive		150	19		
			203.5	201.5	Non-Cohesive	34		20		
			<201.5		Cohesive		400	21		
P20	207.6	207.6	207.6	206.5	Non-Cohesive	30		18	205.5	7, 9
			206.5	205.0	Cohesive		50	17		
			205.0	204.0	Cohesive		100	19		
			204.0	202.5	Cohesive		250	20		
			202.5	201.5	Non-Cohesive	35		21		
			<201.5		Cohesive		400	21		


TABLE II
Design Parameters for
High Mast Light Poles
Highway 400 and Langstaff Road
W.P. 528-91-01

Pole #	Approximate Ground Surface Elev.		Soil Boundary Elevation		Cohesive/ Non-Cohesive	Design Parameters			Assumed Water level	Closest Boreholes
	Existing (m)	Ultimate (m)	Upper (m)	Lower (m)		Degrees ϕ	kPa q_u	kN/m ³ γ		
P21	208.1	208.1	208.1	207	Non-Cohesive	30		20	207.0	9, 7
			207.0	206	Cohesive		50	17		
			206	203	Cohesive		250	21		
			203	201	Non-Cohesive	30		19.5		
			<201		Cohesive		400	21		
P22	208.8	208.8	208.8	207.8	Non-Cohesive	30		20	207.0	9, 14
			207.8	207.0	Cohesive		50	17		
			207.0	206.5	Cohesive		150	19		
			206.5	201.5	Cohesive		250	20		
			<201.5		Cohesive		500	21		
P23	209.3	209.3	209.3	207.5	Non-Cohesive	28		20	207.5	14, 9
			207.5	206.5	Cohesive		150	19		
			206.5	203.0	Cohesive		250	21		
			<203.0		Cohesive		400	21		




LEGEND

●	Borehole (This Investigation)
⊙	Borehole + Cone (This Investigation)
⊙	Borehole + Cone (W P 527-91-01)
●	Borehole (W P 164-79-04/05)
⊙	Borehole (W O 89-11001)
●	Proposed High Mast Light Poles




LEGEND

●	Borehole (This Investigation)
⊕	Borehole + Cone (This Investigation)
⊕	Borehole + Cone (W P 527-91-01)
⊙	Borehole (W P 164-79-04/05)
⊙	Borehole (W O 89-11001)
●	Proposed High Mast Light Poles



●	Borehole (This Investigation)
⊕	Borehole + Cone (This Investigation)
⊕	Borehole + Cone (W P 527-91-01)
⊙	Borehole (W P 164-79-04/05)
⊙	Borehole (W O 89-11001)
●	Proposed High Mast Light Poles



LEGEND

●	Borehole (This Investigation)
⊕	Borehole + Cone (This Investigation)
⊕	Borehole + Cone (W P 527-91-01)
●	Borehole (W P 164-79-04/05)
⊕	Borehole (W O 89-11001)
●	Proposed High Mast Light Poles

RECORD OF BOREHOLE No 1

1 OF 1 METRIC

W.P. 528-91-01(Formerly 612-89-00) LOCATION Co-ords: N 4 850 724.9; E 301 501.2 ORIGINATED BY JB
 DIST 5 HWY 400 BOREHOLE TYPE Solid Stem COMPILED BY JB
 DATUM Geodetic DATE 92 01 13 CHECKED BY DD

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT		PLASTIC NATURAL LIQUID LIMIT MOISTURE CONTENT LIMIT			UNIT WEIGHT 7 kN/m ³	REMARKS & GRAIN SIZE DISTRIBUTION (%) GR SA SI CL
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	'N' VALUES			SHEAR STRENGTH kPa		WATER CONTENT (%)				
204.3	Ground Surface							20 40 60 80 100						
0.0	Gravelly Sand Loose, Dark Grey (Fill)		1	SS	5		204	UNCONFINED	+	FIELD VANE				
203.4	Silty Clay - Organic, Dark Grey, Stiff, (Fill)		2	SS	15		203	QUICK TRIAXIAL	x	LAB VANE				
0.9	Silty Clay Trace Sand Brown		3	SS	19		202							
202.6	V. Stiff		4	SS	18		201							
1.7	Heterogeneous Mixture of Clayey Silt, Some Sand, Trace Gravel Occasional Cobbles and Boulders		5	SS	20		200							
	Brown Grey		6	SS	36		199							
	Very Stiff to Hard		7	SS	16		198							
	(Glacial Till)		8	SS	35		197							
	Very Sandy		9	SS	44		196							
	Silty Clay Layer		10	SS	40		195							
194.7	Sandy Silt to Silty Sand						194							
9.6	Occ. Clayey Silt Layers Very Dense													
193.2			11	SS	53									
11.1	End of Borehole • W.L. Not Stabilized													

RECORD OF BOREHOLE No 2

1 OF 1

METRIC

W.P. 528-91-01 (Formerly 612-89-00) LOCATION Co-ords: N 4 850 990.0; E 301 414 ORIGINATED BY JB
 DIST 6 HWY 400 BOREHOLE TYPE Solid Stem COMPILED BY JB
 DATUM Geodetic DATE 92 01 10 CHECKED BY DD

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT	PLASTIC LIMIT W _P	NATURAL MOISTURE CONTENT W	LIQUID LIMIT W _L	UNIT WEIGHT γ	REMARKS & GRAIN SIZE DISTRIBUTION (%) GR SA SI CL
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	'N' VALUES			20 40 60 80 100					
205.7	Ground Surface												
0.0	Grovelly Sand (Fill)												
	Silty Clay Contains Topsoil Brown to Dark Brown (Fill)		1	SS	8		205						
203.9			2	SS	10		204						
1.8	Heterogeneous Mixture of Clayey Silt, Some Sand, Trace Gravel Occasional Cobbles and Boulders		3	SS	14		203						
			4	SS	17		202						
	Sandy Brown, Stiff to Very Stiff Grey, Hard		5	SS	26		201						
	(Glacial Till)		6	SS	66		200						
			7	SS	55		199						
	Silty Sand Layer		8	SS	50		198						
	Random Silty Sand Layers		9	SS	58		197						
196.4		10	SS	70									
9.3	End of Borehole • W.L. on 92 01 13												

RECORD OF BOREHOLE No 3

1 OF 1 METRIC

W.P. 528-91-01 (Formerly 612-89-00) LOCATION Co-ords: N 4 851 269.3; E 301 406.2 ORIGINATED BY JB
 DIST 6 HWY 400 BOREHOLE TYPE Solid Stem COMPILED BY JB
 DATUM Geodetic DATE 92 01 13 CHECKED BY DD

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT		PLASTIC LIMIT W _p	NATURAL MOISTURE CONTENT W	LIQUID LIMIT W _L	UNIT WEIGHT γ	REMARKS & GRAIN SIZE DISTRIBUTION (%)
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	'N' VALUES			20 40 60 80 100	20 40 60 80 100					
206.6	Ground Surface													
0.0	Sand, Some Gravel Brown, Loose to Compact (Fill)		1	SS	11		206							
205.2	Silty Clay - Organic Dark Brown, Firm, (Fill)		2	SS	7		205							
1.4	Heterogeneous Mixture of Clayey Silt, Some Sand, Trace Gravel Occasional Cobbles and Boulders		3	SS	16		204							
			4	SS	17		203							
			5	SS	21		202							
			6	SS	22		201							
			7	SS	36		200							
			8	SS	29		199							
			9	SS	52		198							
188.0			10	SS	57		197							
8.6	Silt Trace of Clay Dense to Very Dense		11	SS	36		196							
195.5														
11.1	End of Borehole * W.L. Not Stabilized													

RECORD OF BOREHOLE No 4

1 OF 1

METRIC

W.P. 528-91-01(Formerly 612-89-00) LOCATION Co-ords: N 4 851 528.5; E 301 300.6 ORIGINATED BY JB
 DIST 6 HWY 400 BOREHOLE TYPE Solid Stem COMPILED BY JB
 DATUM Geodetic DATE 92 01 10 CHECKED BY DD

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT		PLASTIC LIMIT W _p	NATURAL MOISTURE CONTENT W	LIQUID LIMIT W _L	UNIT WEIGHT 7 kN/m ³	REMARKS & GRAIN SIZE DISTRIBUTION (%) GR SA SI CL
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	'N' VALUES			20 40 60 80 100	20 40 60 80 100					
206.1	Ground Surface													
0.0	0.5 m Topsoil Silty Clay Occasional Root Fibres (Fill)		1	SS	6									
205.5														
0.6	Heterogeneous Mixture of Clayey Silt, Some Sand, Trace Gravel (Glacial Till)		2	SS	16									
			3	SS	17									
	Very Stiff													
	Hard													
	Brown													
	Grey		4	SS	80									
202.6	Occasional Cobbles and Boulders		5	SS	43									
3.5	Sandy Silt to Silty Fine Sand													
			6	SS	31									
	Compact to Dense													
			7	SS	18									
200.2	Heterogeneous Mixture of Clayey Silt, Some Sand, Trace Gravel Occasional Cobbles and Boulders Hard (Glacial Till)		8	SS	71	/17cm								
5.9														
199.1	Sand and Silt to Silty Fine Sand													
7.0			9	SS	26									
	Compact													
196.5			10	SS	14									
9.6	End of Borehole													
	- W.L. on 92 01 13													

RECORD OF BOREHOLE No 5

1 OF 1 METRIC

W.P. 528-91-01(Formerly 612-89-00) LOCATION Co-ords: N 4 851 794.8; E 301 313.6 ORIGINATED BY JB
 DIST 6 HWY 400 BOREHOLE TYPE Solid Stem COMPILED BY JB
 DATUM Geodetic DATE 92 01 06 CHECKED BY DD

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT					PLASTIC UNIT W _p	NATURAL MOISTURE CONTENT W	LIQUID UNIT W _L	UNIT WEIGHT γ kN/m ³	REMARKS & GRAIN SIZE DISTRIBUTION (%) GR SA SI CL
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	'N' VALUES			20	40	60	80	100					
206.8	Ground Surface																
0.0	Gravelly Sand Brown, Loose, (Fill)																
205.8	Silty Clay Containing Traces of Topsoil Dark Brown, Stiff, (Fill)		1	SS	10												
1.1	Topsoil																
205.0	Brownish Grey to Dark Brown		2	SS	8												
1.9	Greenish Grey to Brown																
203.9	Silty Clay, Trace Sand Stiff		3	SS	8												
3.0			4	SS	13												
	Sand Layer		5	SS	24												
	Brown Grey		6	SS	15												
	Occasional Sandy Silt Layers		7	SS	15												
	Heterogeneous Mixture of Clayey Silt, Some Sand, Trace Gravel Occasional Cobbles and Boulders Very Stiff to Hard (Glacial Till)		8	SS	20												
198.9			9	SS	37												
8.0	Silty Sand to Sandy Silt																
197.3	Compact to Dense		10	SS	17												
9.6	End of Borehole																
	• W.L. on 92 01 07																
	> Greater Than																

RECORD OF BOREHOLE No 6

1 OF 1

METRIC

W.P. 527-91-01(A)(prev. 612-89-00) LOCATION Co-ords: N 4 852 049.1; E 301 208.7 ORIGINATED BY JB
DIST 6 HWY 400 BOREHOLE TYPE Solid Stem COMPILED BY JB
DATUM Geodetic DATE 92 01 09 CHECKED BY DD

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT		NATURAL MOISTURE CONTENT			UNIT WEIGHT 7 kN/m ³	REMARKS & GRAIN SIZE DISTRIBUTION (%) GR SA SI CL
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	'N' VALUES			20 40 60 80 100	20 40 60 80 100	W _p	W	W _L		
205.7														
0.0	Topsail Dark Brown to Black Soft		1	SS	2									
205.2														
0.5	Root Fibres		2	SS	5									
	Silty Clay to Clayey Silt Some Sand, Trace Gravel		3	SS	11									
	Firm to Very Stiff		4	SS	7									
202.3	Silty Sand Layer Brown		5	SS	34									
3.4	Heterogeneous Mixture of Clayey Silt, Some Sand, Trace Gravel		6	SS	45									
	Sandy		7	SS	39									
	Occasional Cobbles and Boulders		8	SS	25									
	Very Stiff to Hard (Glacial Till)		9	SS	28									
	Occasional Silty Clay Zones		10	SS	33									
	Sandy		11	SS	76									
194.6			12	SS	38									
11.1	End of Borehole													
	92 01 13 * GROUND WATER CONDITIONS													
	PIEZO. NO.	GROUND WATER ELEVATION (Metres)												
	1	205.4												
	> Greater Than													

RECORD OF BOREHOLE No 7

1 OF 1

METRIC

W.P. 527-91-01(A)(Prev. 612-89-00) LOCATION Co-ords: N 4 852 057; E 301 248.5 ORIGINATED BY JB
 DIST 6 HWY 400 BOREHOLE TYPE Solid Stem COMPILED BY JB
 DATUM Geodetic DATE 92 01 06 CHECKED BY DD

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT		PLASTIC LIMIT W _p	NATURAL MOISTURE CONTENT W	LIQUID LIMIT W _L	UNIT WEIGHT γ	REMARKS & GRAIN SIZE DISTRIBUTION (%)
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	'N' VALUES			20 40 60 80 100	20 40 60 80 100					
207.3	Ground Surface													
0.0	230 mm Asphalt 130 mm Granular 'A'						207							
	Sand													
	Brown, Loose, (Fill)		1	SS	7		206						17.6	
	Silty Clay													
	Containing Topsoil													
	Grey to Black, Firm, (Fill)		2	SS	7		205						19.0	
205.2	Topsoil, Black, Firm													
2.1	Silty Clay		3	SS	3		204						22.1	
	Traces of Organics													
	Brownish Grey to Grey		4	SS	9		203							
203.6	Soft to Stiff													
3.7	Brown to Brownish Grey		5	SS	12		202							
	Grey		6	SS	23		201						22.8	
	Sandy		7	SS	49		200							
	Heterogeneous Mixture of Clayey Silt, Some Sand, Trace Gravel		8	SS	50		199							
	Occasional Cobbles and Boulders													
	Hard		9	SS	35		198							
	(Glacial Till)													
187.7			10	SS	39									
9.6	• W.L. not stabilized													

RECORD OF BOREHOLE No 8

1 OF 1 METRIC

W.P. 527-91-01(A)(Prev. 612-89-00) LOCATION Co-ords: N 4 852 064.0; E 301 285.5 ORIGINATED BY JB
 DIST 6 HWY 400 BOREHOLE TYPE Solid Stem COMPILED BY JB
 DATUM Geodetic DATE 92 01 07 CHECKED BY DP

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT		PLASTIC LIMIT W _p	NATURAL MOISTURE CONTENT W	LIQUID LIMIT W _L	UNIT WEIGHT 7 kN/m ³	REMARKS & GRAIN SIZE DISTRIBUTION (%) GR SA SI CL
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	'N' VALUES			SHEAR STRENGTH kPa	WATER CONTENT (%)					
205.4	Ground Surface													
0.0	130 mm Topsoil													
	Silty Clay Some Sand		1	SS	9									
	Stiff to Very Stiff		2	SS	15									
203.3	Sandy													
2.1	Sandy Silt to Silty Sand Occ. Clayey Silt Layers		3	SS	14									
	Brown to Brownish Grey Grey		4	SS	18									
201.7	Compact													
3.7	Heterogeneous Mixture of Clayey Silt, Some Sand, Trace Gravel		5	SS	30									
	Occasional Cobbles and Boulders		6	SS	48									
	Very Stiff to Hard		7	SS	38									
	(Glacial Till)		8	SS	21									
			9	SS	21									
			10	SS	44									
			11	SS	60									
	Sandy													
194.5			12	SS	50									
10.9	End of Borehole													
	92 01 13 * GROUND WATER CONDITIONS													
	PIEZO. NO.													
	1													
	GROUND WATER ELEVATION (Metres)													
	205													

RECORD OF BOREHOLE No 9

1 OF 1 METRIC

W.P. 528-91-01(Formerly 612-89-00) LOCATION Co-ords: N 4 852 363.7; E 301 181.9 ORIGINATED BY JB
 DIST 6 HWY 400 BOREHOLE TYPE Solid Stem COMPILED BY JB
 DATUM Geodetic DATE 92 01 06 CHECKED BY DD

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT		PLASTIC LIMIT W _P	NATURAL MOISTURE CONTENT W	LIQUID LIMIT W _L	UNIT WEIGHT γ kN/m ³	REMARKS & GRAIN SIZE DISTRIBUTION (%) GR SA SI CL
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	'N' VALUES			SHEAR STRENGTH kPa						
208.4	Ground Surface							20 40 60 80 100						
0.0	Gravelly Sand Brown, (Fill)							○ UNCONFINED + FIELD VANE						
	Silty Clay Containing Topsail Dark Brown to Black, Stiff (Fill)		1	SS	10		208	● QUICK TRIAXIAL × LAB VANE						
			2	SS	10		207							
206.2	Silty Clay, Trace Sand, Brown, Stiff						206							
2.2	Silty Fine Sand Brown Compact		3	SS	19		205							
205.4							204							
3.0	Heterogeneous Mixture of Clayey Silt, Some Sand, Trace Gravel Occasional Cobbles and Boulders Brown		4	SS	18		203							
	Grey Occasional Sandy Silt Layers		5	SS	21		202							
	Very Stiff		6	SS	22		201							
203.2	(Glacial Till)						200							
5.2	Silty Fine Sand to Sand, Some Silt		7	SS	11		199							
	Compact		8	SS	15									
201.1														
7.3	Heterogeneous Mixture of Clayey Silt, Some Sand, Trace Gravel Occasional Cobbles and Boulders		9	SS	23									
	Very Stiff to Hard (Glacial Till)													
198.8			10	SS	79									
9.6	End of Borehole													
	* W.L. immediately upon completion of sampling													

RECORD OF BOREHOLE No 10

1 OF 1

METRIC

W.P. 527-91-01(B)(Prev. 612-89-00) LOCATION Co-ords: N 4 852 722.7; E 301 111.5 ORIGINATED BY JB
 DIST 5 HWY 400 BOREHOLE TYPE Solid Stem COMPILED BY JB
 DATUM Geodetic DATE 92 01 09 CHECKED BY DD

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT 20 40 60 80 100 SHEAR STRENGTH kPa ○ UNCONFINED + FIELD VANE ● QUICK TRIAXIAL × LAB VANE 20 40 60 80 100	PLASTIC LIMIT W _p	NATURAL MOISTURE CONTENT W	LIQUID LIMIT W _L	UNIT WEIGHT 7 kN/m ³	REMARKS & GRAIN SIZE DISTRIBUTION (%) GR SA SI CL
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	'N' VALUES								
207.4	Ground Surface												
0.0	Topsoil/Silty Clay (Fill)		1	SS	2		207						
206.9	Black to Brownish Grey, Soft												
0.5	Root Fibres												
	Silty Clay, Trace Sand		2	SS	8		206						
	Brown												
	Firm to Stiff												
205.6			3	SS	13		205						
1.8	Occasional Sandy Silt Layers												
	Brown		4	SS	18		204						
	Grey												
	Silty Clay Layer												
	Heterogeneous Mixture of Clayey Silt, Some Gravel, Trace Clay		5	SS	25		203						
			6	SS	19		202						
			7	SS	17		201						
			8	SS	14		200						
			9	SS	18		199						
			10	SS	21		198						
			11	SS	23		197						
			12	SS	13								
198.8													
8.6	Sandy Silt to Silty Fine Sand												
	Compact												
196.3													
11.1	End of Borehole												
	92 01 13												
	* GROUND WATER CONDITIONS												
	PIEZO. NO.												
	GROUND WATER ELEVATION (Metres)												
	1												
	207.3												
	> Greater Than												

RECORD OF BOREHOLE No 11

1 OF 1 METRIC

W.P. 527-91-01(B)(Prev. 612-89-00) LOCATION Co-ords: N 4 852 729.9; E 301 179.6 ORIGINATED BY JB
 DIST 6 HWY 400 BOREHOLE TYPE Solid Stem COMPILED BY JB
 DATUM Geodetic DATE 92 01 08 CHECKED BY DD

SOIL PROFILE			SAMPLES			GROUND WATER * CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT		PLASTIC LIMIT W _p		NATURAL MOISTURE CONTENT W		LIQUID LIMIT W _L		UNIT WEIGHT γ	REMARKS & GRAIN SIZE DISTRIBUTION (%)
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	"N" VALUES			20 40 60 80 100	20 40 60 80 100	10 20 30	10 20 30	10 20 30	10 20 30	10 20 30	10 20 30		
207.5	Ground Surface																
0.0	100 mm Topsoil																
	Silty Clay, Some Sand Traces of Root Fibres		1	SS	8												
206.1	Brown, Firm to Stiff																
1.4			2	SS	45												
	Brown to Brownish Grey Occasional Silty Sand to Sandy Silt Layers		3	SS	33												
	Heterogeneous Mixture of Clayey Silt, Some Sand, Trace Gravel		4	SS	29												
	Occasional Cobbles and Boulders		5	SS	24												
	Very Stiff to Hard (Glacial Till)		6	SS	26												
201.6			7	SS	33												
5.9			8	SS	13												
	Sandy Silt to Sand and Silt																
	Compact		9	SS	13												
198.9																	
8.6	Heterogeneous Mixture of Clayey Silt, Some Sand, Trace Gravel																
197.9	Hard (Glacial Till)		10	SS	45												
9.6	End of Borehole																
	* W.L. on 92 01 13																

RECORD OF BOREHOLE No 14

1 OF 1

METRIC

W.P. 528-91-01(Formerly 612-89-00) LOCATION Co-ords: N 4 852 517.0; E 301 190.7 ORIGINATED BY JB
 DIST 5 HWY 400 BOREHOLE TYPE Solid Stem COMPILED BY JB
 DATUM Geodetic DATE 92 01 07 CHECKED BY DD

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT					PLASTIC NATURAL LIQUID LIMIT MOISTURE CONTENT UNIT			REMARKS & GRAIN SIZE DISTRIBUTION (%)
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	'N' VALUES			20 40 60 80 100	20 40 60 80 100	20 40 60 80 100	20 40 60 80 100	20 40 60 80 100	W _p W W _L	WATER CONTENT (%)	UNIT WEIGHT γ	
208.8																
0.0	Gravelly Sand, Brown, Compact, (Fill)					*										
	Silty Clay, Traces of Topsoil						208									
	Soft to Firm, (Fill)															
207.4	Dark Brown															
1.4	Brown															
	Traces of Organics		1	SS	11		207									
	Heterogeneous Mixture of Clayey Silt, Some Sand, Trace Gravel						206									
			2	SS	23		205									
	Brown Grey															
	Occasional Cobbles and Boulders						204									
	Stiff to Hard						203									
	(Glacial Till)						202									
201.2			4	SS	38											
7.6	End of Borehole		5	CS												
	* W.L. not established															



WP NO _____ CONTRACT NO _____ DISTRICT NO _____ HWY NO _____

LOCATION _____ TYPE OF WORK _____

1. This S P is new (✓) ☐

This S P replaces No. _____

Remarks:

Explanation of Intent:

2.	Item No	Spec No	Title or Item Description
			CONCRETE FOOTINGS FOR HIGH MAST POLES

High Mast Pole Lighting foundations will consist of caissons as detailed in the Contract.

The Contractor shall refer to the Foundation Investigation and Design Report in the Contract Package for subsurface information for this project.

The Contractor is advised that zones of non-cohesive soil and near-surface groundwater levels should be anticipated and addressed in his construction proposal and costs. The Contractor is cautioned that non-cohesive soil is susceptible to disturbance under conditions of unbalanced hydrostatic head.

The Contractor is advised that occasional cobbles and boulders should be anticipated and addressed in his construction proposal and costs.

The Contractor is responsible for constructing caissons without disturbing the sides or bases of the caisson excavations. A fully detailed proposal, signed and sealed by a Professional Engineer licensed by the Association of Professional Engineers of Ontario is to be submitted to the Engineer a minimum of 4 weeks prior to commencement.

3.

Structural Section
Initiated by _____

Structural Section
Detailed by _____

Approved by _____



RECORD OF BOREHOLE No C 8

METRIC

W P 164-79-04/05

LOCATION Co-ords. N 4 850 173; E 301 521

ORIGINATED BY FS

DIST 6 HWY 400

BOREHOLE TYPE Solid Stem Augers, Cone Test

COMPILED BY FS

DATUM Geodetic

DATE 85 06 10

CHECKED BY

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT		PLASTIC NATURAL LIQUID LIMIT MOISTURE CONTENT LIMIT			UNIT WEIGHT γ	REMARKS & GRAIN SIZE DISTRIBUTION (%) GR SA SI CL
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	% VALUES			20 40 60 80 100	W _p W W _L	WATER CONTENT (%)				
198.1	Ground Surface													
0.0	Silty Clay trace to with Sand trace Gravel Very Stiff		1	SS	17		198							
			2	SS	25		197							
			3	SS	30		196							
	Hard		4	SS	34		195							
			5	SS	72		194							
							193							
	Silty Sand to Sandy Silt Very Dense		6	SS	189/15		192							
			7	SS	120		191							
							190							
189.1							189							
9.0	Sand some Silt trace Clay, Gravel		8	SS	185									
188.1	Very Dense													
9.6	End of Borehole													
	*groundwater level not established													

OFFICE REPORT ON SOIL EXPLORATION

*3, x3 : Numbers refer to
Sensitivity

20
15 \div 5 (%) STRAIN AT FAILURE
10



Ministry of
Transportation and
Communications
Ontario

RECORD OF BOREHOLE No C 10

METRIC

W P 164-79-04/05 LOCATION Co-ords. N A 830 297; E 301 587 ORIGINATED BY FS
DIST 6 HWY 400 BOREHOLE TYPE Solid Stem Auger, Cone Test COMPILED BY FS
DATUM Geodetic DATE 85 06 14 CHECKED BY SP

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT 20 40 60 80 100 SHEAR STRENGTH ○ UNCONFINED • FIELD VANE ● QUICK TRIAXIAL ■ LAB VANE	PLASTIC LIMIT W _p	NATURAL MOISTURE CONTENT W	LIQUID LIMIT W _L	UNIT WEIGHT γ	REMARKS & GRAIN SIZE DISTRIBUTION (%) GR SA SI CL	
ELEV. DEPTH	DESCRIPTION	STRAT. PLOT	NUMBER	TYPE	W VALUES									
200.0	Ground Surface													
0.0	Silty Clay trace to with Sand trace Gravel Firm		1	SS	7		199							
			2	TM	FE		198							3 29 41 25
	----- Hard		3	SS	37		197							
			4	SS	69		196							4 17 54 25
			5	SS	126		195							
			6	SS	105		194							1 19 55 25
							193							
192.2	Silty Sand to Sandy Silt Very Dense		7	SS	20	/15cm								
7.8	End of Borehole													
	*groundwater level not established													

3, 4, 5 : Numbers refer to
Sensitivity

20
15
10
% STRAIN AT FAILURE

OFFICE REPORT ON SOIL EXPLORATION



MINISTRY OF
Transportation and
Communications
Ontario

RECORD OF BOREHOLE No C 11

METRIC

W P 164-79-04/05

LOCATION Co-ords N 4 850 432; E 301 498

ORIGINATED BY FS

DIST 6 HWY 400

BOREHOLE TYPE Solid Stem Augers, Cone Test

COMPILED BY FS

DATUM Geodetic

DATE 85 06 10

CHECKED BY

SOIL PROFILE			SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT 20 40 60 80 100 SHEAR STRENGTH ○ UNCONFINED * FIELD VANE ● QUICK TRIAXIAL x LAB VANE	PLASTIC LIMIT W _p	NATURAL MOISTURE CONTENT W	LIQUID LIMIT W _L	UNIT WEIGHT γ	REMARKS & GRAIN SIZE DISTRIBUTION (%) GR SA SI CL
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE	W _v VALUES								
199.9	Ground Surface												
0.0	Silty Clay trace to with Sand trace Gravel												
	Very Stiff		1	SS	17								
	Hard		2	SS	60								
			3	SS	90								
			4	SS	100								
			5	SS	88								
			6	SS	100	/15cm							
192.4	Refusal due to probable boulder End of Borehole												

*3, *5 : Numbers refer to
Sensitivity
20
15
10
5 (%) STRAIN AT FAILURE

OFFICE REPORT ON SOIL EXPLORATION

RECORD OF BOREHOLE

SHEET 1

LOCATION SEE FIGURE 2

BORING DATE JAN.19,1988

DATUM GEODETTIC

SAMPLER HAMMER, 63.5kg, DROP, 760mm

PENETRATION TEST HAMMER, 63.5kg, DROP, 760mm



DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES		DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m		HYDRAULIC CONDUCTIVITY, K, CM/SEC		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION
		DESCRIPTION	STRATA PLOT ELEV. DEPTH (M)	NUMBER	TYPE	SHEAR STRENGTH Cu, kPa	nat.V. - + Q. - rem.V. - U. -	WATER CONTENT, PERCENT			
0		GROUND SURFACE	205.15								
		Soft to firm, mottled grey-brown SILTY CLAY, trace sand, occ. organics.	0.00	1	DO						Backfill
			203.65	2	DO						
		Firm to stiff, gray inter-layered SILTY CLAY, trace sand (TILL) and SILTY CLAY; some seams of silt, sandy silt and silty sand.	1.80	3	DO						
			202.25	4	DO						
		Compact, gray SANDY SILT, trace clay and gravel. TILL. Boulder at 2.9m depth.	2.90	5	DO						
			201.45	6	DO						
			3.70	8	DO						Bentonite Seal
				7	DO						Backfill
5		Stiff to hard, gray CLAYEY SILT, some sand, trace gravel. TILL.		8	DO						
				9	DO						
			106.35	10	DO						
		Stiff, gray CLAYEY SILT, trace sand with interlayers of SANDY SILT, trace clay and gravel.	8.80	11	DO						
			194.75	12	DO						
10		Compact gray SANDY SILT, trace sand and gravel. TILL. Seam of silty clay.	10.40	13	DO						
			193.55	14	DO						
		Dense, gray SILTY SAND, trace gravel with interlayers of CLAYEY SILT, some sand.	11.60	15	DO						
			192.05	16	DO						
			13.10	17	DO						
		Hard, gray stratified SILTY CLAY, CLAYEY SILT and SILT, fine sand partings throughout.		18	DO						
			186.95	19	DO						
			16.20	20	DO						
		Very loose, gray SILT, trace clay and sand.	16.20	21	DO						
			187.45	22	DO						
		Compact, to dense gray SAND, trace silt to SILTY SAND. (Sands blowing; 1.5m to 3m up augers at each sample depth prior to washing.)	17.70	23	DO						
				24	DO						
20		CONTINUED ON NEXT PAGE	185.15	25	DO						
			20.00	26	DO						

14-6 PERCENT AXIAL STRAIN AT FAILURE

DEPTH SCALE

1: 100

Golder Associates

LOGGED RF

CHECKED ASP

RECORD OF BOREHOLE

SHEET 2

LOCATION SEE FIGURE 2

BORING DATE JAN.19,1989

DATUM GEODETTIC

SAMPLER HAMMER, 63.5kg, DROP, 760mm

PENETRATION TEST HAMMER, 63.5kg, DROP, 760mm



DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES		DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m				HYDRAULIC CONDUCTIVITY, k, CM/SEC				ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION		
		DESCRIPTION	STRATA PLOT	ELEV. DEPTH (M)	NUMBER	TYPE	BLOWS/0.3M	SHEAR STRENGTH				WATER CONTENT, PERCENT					
								38	72	108	144	nat.V. - + Q. - @ rem.V. - @ U. - O	W				
20	CMSS POWER AUGER BORING 200mm DIA. HOLLOW STEM AUGER	CONTINUED FROM PREVIOUS PAGE		186.16													
				20.00													
		Compact to dense grey SAND, trace silt to SILTY SAND. (Sands blowing: 1.5m to 3m up augers at each sample depth prior to washing.)		18	50	43											
				19	50	26											
				20	50	62											
25		Very stiff to hard, grey SILTY CLAY, trace fine sand partings.	180.86														
			24.30	21	50	27											
		Hard, grey SILTY CLAY, trace sand, occ. fine gravel.	178.05														
			27.10	22	50	52											
				23	50	48											
30		END OF HOLE	174.64														
				30.61													
35		NOTE: Borehole continued below elevation 178.8m. at location of Borehole 1A; 7.6m. west of initial borehole; ground surface elevation 205.32m. Noted increase in auger resistance at about elevation 179.8 m.															
40																	

10-15 PERCENT AXIAL STRAIN AT FAILURE

DEPTH SCALE

1 : 100

Golder Associates

LOGGED RF

CHECKED ASP

RECORD OF BOREHOLE 2

SHEET 1

LOCATION SEE FIGURE 2

BORING DATE JAN.20,1989


DATUM GEODETIC

SAMPLER HAMMER, 83.5kg, DROP, 760mm

PENETRATION TEST HAMMER, 83.5kg, DROP, 760mm



DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES		DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m		HYDRAULIC CONDUCTIVITY, K, CM/SEC		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION
		DESCRIPTION	STRATA PLAT ELEV. DEPTH (M)	NUMBER	TYPE	BLWS/0.3M	SHEAR STRENGTH Cu, kPa nat.V. - + Q. - ● rem.V. - ● U. - ○	WATER CONTENT, PERCENT			
0	CMESS POWER AUGER BORING 200mm DIA. HOLLOW STEM AUGER	GROUND SURFACE	205.77	1	50 DO	18					
		Stiff, mottled gray-brown SILTY CLAY, trace sand, occ. gravel, trace organics.	0.00	2	50 DO	11					
			203.87	3	50 DO	10					
		Loose to compact, brown to gray SANDY SILT, trace clay and gravel. TILL.	2.10	4	50 DO	9					
			202.07	5	50 DO	16					
		Hard, interlayered CLAYEY SILT and SANDY SILT, numerous silt partings.	3.70	6	50 DO	30					
			201.37	7	50 DO	58					
			4.40	8	50 DO	33					
		Hard, gray CLAYEY SILT, some sand, trace gravel. TILL.		9	50 DO	33					
			197.27	10	50 DO	20					
		Very stiff, gray stratified SILTY CLAY and CLAYEY SILT.	8.60	11	50 DO	21					
			195.07	12	50 DO	77					
		Dense to very dense, gray SANDY SILT, trace clay and gravel. TILL.	10.70	13	50 DO	73					
			190.87	14	50 DO	32					
15		Hard, stratified SILTY CLAY, trace sand, occ. gravel.	14.90								
		END OF HOLE	15.70								



10 - 6 PERCENT AXIAL STRAIN AT FAILURE

DEPTH SCALE

1: 100

Golder Associates

LOGGED RF

CHECKED ASP

RECORD OF BOREHOLE

4

SHEET 1

LOCATION SEE FIGURE 2

BORING DATE JAN.23,1989

DATUM GEODETIC

SAMPLER HAMMER, 83.5kg, DROP, 760mm

PENETRATION TEST HAMMER, 83.5kg, DROP, 760mm



DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES		DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m		HYDRAULIC CONDUCTIVITY, K, CM/SEC		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION
		DESCRIPTION	STRATA PLOT ELEV. DEPTH (M)	NUMBER	TYPE	BLOWS/0.3m	SHEAR STRENGTH C _u , kPa nat.V.- + Q.- ● rem.V.- ● U.- ○	WATER CONTENT, PERCENT w _p 10 20 30 40			
0	CMSS POWER AUGER BORING 200mm DIA. HOLLOW STEM AUGER	GROUND SURFACE	208.97								
		ASPHALT	208.72								
		Sand and gravel, FILL.	208.22	1	DO	15					
			0.53	2	DO	10					
		Loose to compact, brown sand, trace silt and gravel, FILL.		3	DO	6					
			204.97	4	DO	3					
		Soft, mottled brown silty clay, some organics, FILL.	2.00	5	DO	4					
			204.27	6	DO	14					
		Stiff, grey-brown SILTY CLAY, trace sand, occ. organics.	2.70	7	DO	11					
			203.27	8	DO	31					
		Compact to dense, grey SANDY SILT, trace clay and gravel. TILL.	3.70	9	DO	32					
			201.47								
		Dense, grey SILT, some sand, trace clay.	6.50	10	DO	25					
			199.67	11	DO	20					
5		Very stiff, grey CLAYEY SILT, some sand, trace gravel, TILL. Interlayers of stratified silt and clayey silt below 9.4m depth.	7.30	12	DO	3					
10			198.27	13	DO	22					
		Compact, grey SILTY SAND to SAND, trace silt.(Sands blowing.)	10.70	14	DO	2					
15											
20			186.97								
			20.00								
		CONTINUED ON NEXT PAGE									

CONTINUED ON NEXT PAGE

10-6 PERCENT AXIAL STRAIN AT FAILURE

DEPTH SCALE

1: 100

Golder Associates

LOGGED RF

CHECKED ASP

RECORD OF BOREHOLE

SHEET 2



LOCATION SEE FIGURE 2

BORING DATE JAN 23, 1989

DATUM GEODETIC

SAMPLER HAMMER, 63.8kg, DROP, 780mm

PENETRATION TEST HAMMER, 63.8kg, DROP, 780mm

DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES		DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m		HYDRAULIC CONDUCTIVITY, k, CM/SEC		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION
		DESCRIPTION	STRATA ELEV. DEPTH (M)	NUMBER	TYPE	BLOWS/0.3m	SHEAR STRENGTH CU, kPa	REL. V. - + Q. - ● rem. V. - ● U. - ○	WATER CONTENT, PERCENT		
20	OMEGA POWER AUGER BORING 200mm DIA. HOLLOW STEM AUGER	CONTINUED FROM PREVIOUS PAGE.	186.97 20.00								
		Very loose to compact, gray SILTY SAND to SAND, trace silt.									
25		Hard, gray CLAYEY SILT to SILTY CLAY, some sand, trace gravel, TILL	182.87 24.10	16	60 00	98					
		END OF HOLE	180.45 26.52	18	60 00	86					
30		NOTE: Soil description between elevation 194m and 183m based on recovery from auger									
35											
40											

Water level in
open hole at
elevation 204.8m
on completion of
drilling.

DEPTH SCALE

1 : 100

10 - 6 PERCENT AXIAL STRAIN AT FAILURE

Golder Associates

LOGGED RF

CHECKED ASP

RECORD OF BOREHOLE

SHEET 1

LOCATION SEE FIGURE 2

BORING DATE JAN.25,1989

DATUM GEODETIC

SAMPLER HAMMER, 63.5kg, DROP, 760mm

PENETRATION TEST HAMMER, 63.5kg, DROP, 760mm



DEPTH SCALE METRES	BORING METHOD	SOIL PROFILE		SAMPLES		DYNAMIC PENETRATION RESISTANCE, BLOWS/0.3m		HYDRAULIC CONDUCTIVITY, K, CM/SEC		ADDITIONAL LAB. TESTING	PIEZOMETER OR STANDPIPE INSTALLATION				
		DESCRIPTION	STRATA PLOT ELEV. DEPTH (M)	NUMBER	TYPE	SHEAR STRENGTH CU, kPa		WATER CONTENT, PERCENT							
						20	40	60	80	10	20	30	40		
0	CMSS POWER AUGER BORING 200mm DIA. HOLLOW STEM AUGER	GROUND SURFACE	205.68												
		Clayey TOPSOIL	205.22	1	50 DO	10									Backfill
			0.46	2	50 DO	8									
		Firm to very stiff, mottled gray-brown SILTY CLAY, trace sand.	203.38												
			2.30	3	50 DO	13									
		Compact, gray SANDY SILT, trace clay and gravel. TILL.	202.08	4	50 DO	13									Bentonite seal Backfill
			3.80	5	50 DO	19									
6		Compact, gray stratified SILTY SAND and SANDY SILT.	201.28	5	50 DO	19									
			4.40	6	50 DO	16									
		Compact, gray SANDY SILT, trace clay and gravel (clay content increasing with depth) TILL.	199.13	7	50 DO	28								Granular Filter	
		END OF HOLE	8.55												
10															
15															
20															
														Water level in piezometer at elevation 203.1m on Jan. 28, 1989.	



Water level in
piezometer at
elevation 203.1m
on Jan.28,1989.

DEPTH SCALE

1: 100

Golder Associates

LOGGED RF

CHECKED ASP

MEMORANDUM

(416)235-3731

To: V.F. Boehnke, P. Eng.
Head, Structural Section
Central Region

1994 07 04

Attn.: Dennis Wong, P. Eng.


From: Foundation Design Section
Room 315, Central Building
Downsview, Ontario

Re: Caisson Installation Procedures for
High Mast Lights (HML) Foundations
Hwy 400 from Hwy 7 to North of Langstaff Rd.
W.P. 612-89-00, Contract 93-72
Hwy 400, District 6, Toronto

We have reviewed the procedures for caisson installations in different types of soils, submitted by Anchor Shoring & Caissons Ltd. to Fellmore Electrical Contractors Ltd. for the above mentioned site.

The procedures in general is acceptable. Although, in HML foundations the sides of the caissons are more critical for the HML support than the base of the caissons, it is desirable that the loose material from the base of the caisson is properly removed.

The contractor has proposed that in case of high water table in non-cohesive soils a positive hydrostatic head will be maintained. Occasionally, bentonite slurry is used to effectively prevent any boiling at the base of the caisson. However, if required, this matter would be dealt at the time of construction.




K.S.Q. Ahmad, P. Eng.
Foundation Engineer

For

D. Dundas, P. Eng.
Chief Foundation Engineer (Acting)

METRIC
DIMENSIONS ARE IN METRES
AND/OR MILLIMETRES
UNLESS OTHERWISE SHOWN

CONT NO 93-72
WP NO 612-89-00
HWY 400/HWY 7 TO LANGSTAFF RD.
HIGH MAST LIGHTING
POLE FOOTINGS



NOTE: FOOTING NOT SHOWN FOR CLARITY.


SECTION 3
N.T.S.

FOOTING DATA

POLE No.	POLE LENGTH (m)	FOOTING DIA. (m)	EMBEDMENT LENGTH (m)	REINF. BARS "A" LENGTH (m) SIZE (M)	No. REQ'D	HEIGHT (m)	SPIRAL Q. DIA. (m)	No. OF BOLTS	TOTAL MASS OF STEEL (t)	VOLUME OF CONCRETE (m ³)	T/FTG ELEVATION
P2	30	1.22	8.200	8.875 30	12	8.775	1.080	8	0.90	15.26	202.000
P3	30	1.22	8.200	8.875 30	12	8.775	1.080	8	0.90	15.26	201.180
P4	30	1.22	8.200	8.875 30	12	8.775	1.080	8	0.90	15.26	204.530
P5	30	1.22	8.450	9.125 30	12	9.025	1.080	8	0.92	15.55	204.520
P6	30	1.22	7.950	8.625 30	12	8.525	1.080	8	0.88	14.97	206.000
P7	30	1.22	7.950	8.625 30	12	8.525	1.080	8	0.88	14.97	206.440
P8	30	1.22	8.200	8.875 30	12	8.775	1.080	8	0.90	15.26	207.060
P9	30	1.22	7.700	8.375 30	12	8.275	1.080	8	0.86	14.68	207.540
P10	30	1.22	7.700	8.375 30	12	8.275	1.080	8	0.86	14.68	208.070
P11	30	1.22	8.200	8.875 30	12	8.775	1.080	8	0.90	15.26	208.660
P12	30	1.22	8.950	9.625 30	12	9.525	1.080	8	0.96	16.14	208.890
P13	30	1.22	8.700	9.375 30	12	9.275	1.080	8	0.94	15.84	208.350
P14	30	1.22	8.450	9.125 30	12	9.025	1.080	8	0.92	15.55	207.850
P15	30	1.22	9.200	9.875 30	12	9.775	1.080	8	0.98	16.43	208.130
P20	30	1.22	8.700	9.375 30	12	9.275	1.080	8	0.94	15.84	208.610
P21	30	1.22	9.000	9.675 30	12	9.575	1.080	8	0.96	16.20	209.150
P22	30	1.22	7.700	8.375 30	12	8.275	1.080	8	0.86	14.68	209.930
P23	30	1.22	7.700	8.375 30	12	8.275	1.080	8	0.86	14.68	210.480

SECTION 1
N.T.S.

EQUALLY SPACED REINF. BARS "A"
FOR NUMBER OF REINF. BARS "A"
REFER TO TABLE (TYP).



SECTION 2
N.T.S.

DRAWING NOT TO BE SCALED
100 mm OR ORIGINAL DRAWING

QUANTITIES:

TOTAL MASS OF
REINF. STEEL = 16.33 (tonne)
TOTAL VOLUME
OF CONCRETE = 278.49 (m³)

NOTES:

- REINFORCING STEEL SHALL BE GRADE 400.
- BAR MARKS WITH SUFFIX "C" DENOTE COATED BARS.
- EACH ANCHORAGE ASSEMBLY SHALL BE PROVIDED WITH A WOODEN TEMPLATE.
- ANCHOR RODS ARE ROUND BAR, QUENCHED AND TEMPERED MEDIUM CARBON STEEL WITH MIN. YIELD OF 517 MPa. (MIN TENSILE STRENGTH OF 725 MPa.) AND SHALL SATISFY CHAIRPY V-NOTCH REQUIREMENTS OF 20 JOULES AT MINUS 30° C.
- ANCHOR BOLTS SHALL BE INSTALLED VERTICALLY. NO ADJUSTMENTS SHALL BE ALLOWED AFTER CONCRETE IS PLACED IN FOOTING.
- CLASS OF CONCRETE SHALL BE 30 MPa.
- FOR FINISHED GRADE ELEV., REFER TO GRADING DRAWINGS.
- CLEAR COVER TO REINFORCING STEEL SHALL BE 70 ± 20 mm.
- FOR NUMBER & ORIENTATION OF SLEEVES, REFER TO ELECTRICAL DRAWINGS.

APPLICABLE OPSD DRAWINGS
OPSD 2456-01



BAR MARK	NO. PER FOOTING	TOTAL NO.	BAR TYPE	LENGTH
A15001	5	90	400 LWP	3170
A15002C	14	252	400 LWP	2850
A15003C	7	126	400 LWP	4295
A15004C	20	360	STRAIGHT	1850

REVISIONS	DESCRIPTION	DATE	BY
1	DESIGN BY: CHW B. H. CODE: CHWDC 93	10-04-93	CHW
2	DRAWN BY: CHW B. H. DATE: APRIL 93	10-04-93	CHW
3	STRUCT. ENGINEER: H. N. WONG	10-04-93	H. N. WONG

METRIC
DIMENSIONS ARE IN METRES
AND/OR MILLIMETRES
UNLESS OTHERWISE SHOWN

QUANTITIES:

TOTAL MASS OF
REINF. STEEL = 2.41 (TONNE)
TOTAL VOLUME
OF CONCRETE = 47.10 (m³)

CONT No 93-72
WP No 612-89-00
HWY 400/HWY7 TO LANGSTAFF RD.
HIGH MAST LIGHTING
POLE FOOTINGS

SHEET
230

NOTES:


1. REINFORCING STEEL SHALL BE GRADE 400.
2. BAR MARKS WITH SUFFIX "C" DENOTE COATED BARS.
3. EACH ANCHORAGE ASSEMBLY SHALL BE PROVIDED WITH A WOODEN TEMPLATE.
4. ANCHOR RODS ARE ROUND BAR, QUENCHED AND TEMPERED MEDIUM CARBON STEEL WITH MIN. YIELD OF 517 MPa. (MIN TENSILE STRENGTH OF 725 MPa.) AND SHALL SATISFY CHAMPY V-NOTCH REQUIREMENTS OF 20 JOULES AT MINUS 30° C.
5. ANCHOR BOLTS SHALL BE INSTALLED VERTICALLY. NO ADJUSTMENTS SHALL BE ALLOWED AFTER CONCRETE IS PLACED IN FOOTING.
6. CLASS OF CONCRETE SHALL BE 30 MPa.
7. FOR FINISHED GRADE ELEV., REFER TO GRADING DRAWINGS.
8. CLEAR COVER TO REINFORCING STEEL SHALL BE TO ± 20 mm.
9. FOR NUMBER & ORIENTATION OF SLEEVES, REFER TO ELECTRICAL DRAWINGS.

APPLICABLE OPSD DRAWINGS
OPSD 2456-01




FOOTING DATA

POLE No.	POLE LENGTH (m)	FOOTING DIA. (m)	EMBEDMENT LENGTH (m)	REINF. BARS "A"		SPIRAL DIA. (m)	No. OF BOLTS	TOTAL MASS OF STEEL (+) (kg)	VOLUME OF CONCRETE (m ³)	T/FTG ELEVATION
				LENGTH (m)	SIZE (M)					
P15	30	1.22	9.000	8.625	25	12	8	0.54	10.52	206.150
P16	30	1.22	6.500	6.125	25	12	8	0.39	7.60	205.250
P17	30	1.22	8.000	7.625	25	12	8	0.48	9.35	205.650
P18	30	1.22	7.500	7.125	25	12	8	0.45	8.77	205.950
P24	30	1.22	9.300	8.925	25	12	8	0.56	10.87	198.550




TOP VIEW
N.T.S.



SECTION 1
N.T.S.

EQUALLY SPACED RODS.
FOR NUMBER OF RODS
REFER TO TABLE.



SECTION 2
N.T.S.



DETAIL OF 15M RINGS
PLACED AT THE TOP.
N.T.S.

DRAWING NOT TO BE SCALED
100 mm ON ORIGINAL DRAWING

REVISIONS	DESCRIPTION	DATE
1	DESIGN D.P. CHK B.H. CODE ORDC 03 LOGO	APRIL '13
2	DRAWN C.T. CHK D.R. SITE	STRUCT
3		SCHEME
4		DWG
5		1

memorandum



To: V.F. Boehnke
Head, Structural Section
4th Floor, Atrium Tower

Attn: Dennis Wong

From: Foundation Design Section
Room 315, Central Bldg.

Re: Concrete Culvert Extension at St. 19+938
Hwy. 400 Widening from Hwy. 7 Northerly
to North of Langstaff Road
W.P. 612-89-00; W.P. 527-91-01(B)
District 6, Toronto

Date: 1992 11 25

We have received the drawing for the concrete culvert extension at Station 14+938.

We have no comments to make at this time.

A handwritten signature in cursive script that reads "John A. Blair".

John A. Blair, P. Eng.
Project Foundation Engineer

for

D. Dundas, P. Eng.
Senior Foundation Engineer

DD/JAB/jb

METRIC
DIMENSIONS ARE IN METRES
AND/OR MILLIMETRES
UNLESS OTHERWISE SHOWN



DISTRICT : 6
CONT NO
WP NO 527-91-01
HWY 400 CULVERT
AT STA. 14+260
ROADWAY PROTECTION I
SHEET

- NOTES:
1. STRUCTURAL STEEL SHALL CONFORM TO CSA STANDARD CAN3-040.21-88T GRADE 300W.
 2. BOLTS SHALL CONFORM TO ASTM A325. BOLT THREADS SHALL BE COMPATIBLE WITH THE FERRULE INSERTS EMBEDDED IN THE CONCRETE.
 3. WELDING SHALL BE ACCORDING TO CSA STANDARD W59. WELDING SHALL BE PERFORMED BY WELDERS QUALIFIED UNDER CSA STANDARD W17.1-1983.
 4. TIMBER LAGGING AND SHEETING SHALL BE CONSTRUCTION GRADE FIR (GROUP B).



SUGGESTED SEQUENCE OF CONSTRUCTION:

- STAGE I
1. PLACE TEMPORARY CONCRETE BARRIERS AS SHOWN ON GRADING DRAWINGS.
 2. INSTALL SOLDIER PILES AND STAGE I ROADWAY PROTECTION.
 3. EXCAVATE AND CONSTRUCT CULVERT AND RETAINING WALLS.
 4. INSTALL STEEL POSTS, BENT PLATES, DEADMAN AND ROADWAY PROTECTION IN PREPARATION FOR STAGE II CONSTRUCTION AND BACKFILL.


- STAGE II
1. DIVERT TRAFFIC TO DETOURS 1 & 2 WITH TEMPORARY CONCRETE BARRIERS AS SHOWN.
 2. EXCAVATE AND REMOVE THE DESIGNATED PORTION OF ROADWAY PROTECTION AND SOLDIER PILES FROM STAGE I.
 3. CONSTRUCT CULVERT AND BACKFILL.
 4. REMOVE ROADWAY PROTECTION AND COMPLETE ROADWAY CONSTRUCTION.




SECTION D
N.T.S.




STAGE II CONSTRUCTION
1:1250



SECTION B
1:125



SECTION A
1:1100



DETAIL 2
1:110



DRAWING NOT TO BE SCALED
100 mm ON ORIGINAL DRAWING





BENT PLATE FABRICATION DETAILS

NOTE: LAGGING NOT SHOWN FOR CLARITY.

REVISIONS	DESCRIPTION	DATE	BY
1	DESIGN OF THE B.M. FOR THE CULVERT	11/00	11/00
2	DESIGN OF THE B.M. FOR THE CULVERT	11/00	11/00
3	DESIGN OF THE B.M. FOR THE CULVERT	11/00	11/00

DISTRICT : 6
 CONT NO
 WP NO 527-91-01
 HWY 400 CULVERT
 AT STA. 14+260
 ROADWAY PROTECTION II

METRIC
 DIMENSIONS ARE IN METRES
 AND/OR MILLIMETRES
 UNLESS OTHERWISE SHOWN



DETAIL 5
 1110

DRAWING NOT TO BE SCALED
 100 mm ON ORIGINAL DRAWING

REVISION	DESCRIPTION	DATE	BY
1	DESIGN	APRIL 92	DESIGNER
2	REVISED	APRIL 92	DESIGNER
3	REVISED	APRIL 92	DESIGNER
4	REVISED	APRIL 92	DESIGNER
5	REVISED	APRIL 92	DESIGNER

Structural Section
Central Region
1201 Wilson Avenue
Atrium Tower, 4th Floor
Downsview, Ontario, M3M 1J8

MINISTRY OF TRANSPORTATION

Telephone: 235-5512

m e m o r a n d u m

TO: Mr. M. Devata
Head, Foundation Design Section

DATE: September 30, 1992

Attn. Mr. D. Dundas, Sr. Foundation Engr.


RE: Hwy. 400 Widening
From Hwy 7 to north of Langstaff Road
High Mast Pole Foundations, WP 528-91-01
GWP 612-89-00, District 6

In the latest design from the consultant, the location for pole P15 has been changed. The old and new locations with relevant information are listed here for your reference:

Pole # and Sta. Hwy 400	Offset C Hwy 400	coordinates	
		Northing	Easting
Old P15 Sta. 14+100	130.5 Lt	4851,876.523	301,149.444
New P15 Sta. 14+090.5	107 Lt	4851,871.124	301,174.209

Pole # and Sta. Hwy 400	Original Ground	Final Ground	T/Footing Elev.
Old P15 Sta. 14+100	209.7	211.2	213.35
New P15 Sta. 14+090.5	206	206	206.15

The 2 locations were also plotted on a scale 1:100 design plate to show their relative positions in the field. In this area, apart from the foundation investigation for the original location for HMP# P15, there had been foundation investigations for the construction of Langstaff Road Underpass under Contract 87-60, WP 164-79-05. Copies of the Bore Hole Locations and Soil Strata are attached for your information.



I would appreciate you reviewing the situation as you may wish to update your recommendations.

Please call me if you need any further information or clarification. Thanks.

Dennis Wong

Dennis Wong
Sr. Structural Engineer
for:
V. F. Boehnke
Head, Structural Section

cc. Mr. J. Blair, FDS

METRIC

DIMENSIONS ARE IN METRES
AND/OR MILLIMETRES
UNLESS OTHERWISE SHOWN

PLATE No

CONT No

WP No 612-89-00

REMOVALS

STA 14+000 TO STA 14+350

Survey


Revised

SHEET

28

McCORMICK RANKIN

CONSULTING ENGINEERS



MEMORANDUM

(416)235-3731

To: Volker Boehnke
Head, Structural Section
4th Floor, Atrium Tower
1201 Wilson Avenue

1992 09 28

Attn: Dennis Wong


From: Foundation Design Section
Room 315, Central Building
Downsview, Ontario

Re: Triple Cell Concrete Culvert at Sta. 14 + 260
Hwy 400 Widening From Hwy 7 northerly to
North of Langstaff Road
GWP 612-89-00; W.P. 527-91-01
Highway 400, District 6, Toronto

This is in response to your memo dated August 31, 1992. We have reviewed the drawings showing a plan and typical cross sections for the erosion protection design at the above captioned site.

The design of erosion protection in general meet our recommendations. However, as recommended in our Foundation report, the thickness of rip-rap between station 9+848.8 to station 9+945 should be revised to 600mm.

In our opinion, erosion protection consisting of 600mm rip-rap could be used instead of concrete slabs between station 10+040.6 to Station 10+134.5.



K. Ahmad, P. Eng.
Foundation Engineer

For

D.H. Dundas, P. Eng.
Sr. Foundation Engineer

memorandum



To: V. Boehnke
Head, Structural Section
Central Region

Date: September 2, 1992

Attn: Mr. Dennis Wong

From: Foundation Design Section
Room 315, Central Building
Downsview, Ontario

Re: High Mast Pole Foundations for Hwy 400 Widening
From Hwy 7, Northerly to North of Langstaff Road
W.P. 612-89-00 (W.P. 528-91-01)

This memorandum is written in response to your letter of August 18, 1992.

We understand that it is now proposed to relocate one of the high mast light poles, installed under Contract No. 87-60 (W.P. 164-79-04). It appears that light pole EP10 will be moved about 33 m to the west of the existing location.

We have reviewed the information available to us and feel that the design information which was given in our report (Ref. No. W.P. 164-79-04 - dated September 13, 1990) for the original location would also be suitable for the revised one.

Should you have any questions regarding this letter, please do not hesitate to contact this office.

A handwritten signature in cursive script that reads "John A. Blair".

John A. Blair, P.Eng.
Project Foundation Engineer

for:

Dave Dundas, P.Eng.
Senior Foundation Engineer

Structural Section
Central Region
1201 Wilson Avenue
Atrium Tower, 4th Floor
Downsview, Ontario, M3M 1J8
Telephone: 235-5512

MINISTRY OF TRANSPORTATION

m e m o r a n d u m

TO: Mr. J. Reiffenstein
McCormick Rankin

DATE: August 18, 1992


RE: Culvert at Sta. 14 + 260
Granular Backfill Requirement
Hwy. 400 Widening From Hwy 7 to north of Langstaff Road
G.W.P. 612-89-00, District 6


The attached sketch shows the granular backfill requirement for the above mentioned culvert as per your request.

Please call me if you need any clarification or information.

Dennis Wong
Dennis Wong
Sr. Structural Engineer
for:
V. F. Boehnke
Head, Structural Section

cc. Mr. J. Blair, FDS





* GRANULAR SHALL BE
COMPACTED ACCORDING TO
OPSS 501.08.02

Structural Section
Central Region
1201 Wilson Avenue
Atrium Tower, 4th Floor
Downsview, Ontario, M3M 1J8
Telephone: 235-5512

MINISTRY OF TRANSPORTATION

m e m o r a n d u m

TO: Mr. M. Devata
Head, Foundation Design Section

DATE: August 18, 1992

Attn. Mr. D. Dundas, Sr. Foundation Engr.


RE: High Mast Pole Foundations for Hwy. 400 Widening
From Hwy 7 northerly to north of Langstaff Road
W.P. 528-91-01
G.W.P. 612-89-00, District 6

The design of the highway illumination system for the above project calls for the relocation of the last High Mast Pole which was installed in Contract 87-60 (WP 164-79-04) for the Hwy 400/7 Interchange.

Reasons for the proposed relocation were explained in a memorandum from the consultant, McCormick Rankin, to Mr. A. Silbiger, Head, Electrical Design, and copied to me. Copies of this memorandum and relevant drawings from the previous contract are attached with this memorandum for your easy reference.

I would appreciate if you could look into this situation and advise us as to the possible foundation conditions in the proposed location so that we can design the HMP Foundation and be included in the new contract for the above mentioned project.

Please call me if you need any clarification or information.


Dennis Wong
Sr. Structural Engineer
for:
V. F. Boehnke
Head, Structural Section

cc. Mr. J. Blair, FDS
Mr. B. Mondesir, Electrical design
Mr. M. Tedesco, McCormick Rankin

memorandum



To: Mr. V. F. Boeknke
Head, Structural Section
4th Floor, Atrium Tower
Central Region

Date: 1992 07 21

Att: Mr. Dennis Wong

From: Foundation Design Section
Room 315, Central Building
Downsview, Ontario

Re: Highway 400 Widening
From Hwy 7 to North of Langstaff Road
Roadway Protection Scheme For Culvert Construction
W.P. 612-89-00 / 527-91-01
District 6, Toronto

This letter summarizes our comments regarding the drawings for the above-captioned project, which were received by this office on July 7, 1992.

- 1) Drawing No. 1 - W.P. 527-91-01

Under Construction Notes:

It should be noted that, once the Engineer has approved the foundation soils, it is desirable to place a skim coat of concrete, wherever the soils are likely to be disturbed. This particularly refers to the retaining wall footings or any other foundations which are being placed directly on soil.

- 2) Drawing No. 3 - W.P. 527-91-01

For tiebacks, within the free-stressing zone, a note should be included which indicates that a bentonite slurry should be used to fill the annular space between the dywidag bar and the perimeter of the hole. This as well as the requirements for the bond zone and the testing of the installed anchors are shown in our Non-Standard Special Provision, which has been included with this letter.

- 3) Drawing No. 3 - W.P. 527-91-01

Although the fill, where the deadman anchors are to be placed, should be well-compacted, it is imperative that

special care be taken to ensure that the fill, within at least 1.0 m of the anchors is compacted to at least 100 percent Standard Proctor Maximum Dry Density (SPMDD).

- 4) Drawing No's 1 and 3 - W.P. 527-91-01 - Typographical errors, as shown on the accompanying drawings.

We also have the following additional comments:

- Since parts of the excavation for the culvert will lie within cohesionless sandy silt to silty sands, below the groundwater table, disturbance is likely due to the unbalanced hydrostatic head. In view of this, some form of dewatering scheme, such as an oversized excavation, should be adopted.
- It appears that several of the High Mast Light Pole Foundations will be partially placed within or on cohesionless sandy silt to silty sand deposits. As noted in our Report, a special provision should be included for the construction of caisson foundations, to prevent excessive disturbance of these soils, and a consequent loss of their frictional properties.
- We assume that drawings showing the erosion protection for the proposed channel and the proposed culvert extensions will be available for our review.

Should you have any questions regarding this letter, please do not hesitate to contact this office.

John A. Blair


John A. Blair, P. Eng.
Project Foundation Engineer

For

D. H. Dundas, P.Eng.
Sr. Foundation Engineer

Distribution

V. F. Boehnke (2)



CULVERT COMPLETED
ON STAGE I

TEMPORARY CONC.
BARRIER
OPSD 920.01
RELOCATED

SBL

STAGE II
CONSTRUCTION

STA. 14+260
HWY 400

HWY 400

ROADWAY
PROTECTION

NBL

CULVERT
COMPLETED
ON STAGE I

CULVERT

SK. 2

⊕ CULVERT

STA. 14 + 260
HWY 400

⊕
HWY 400


17 W30X179 SOLDIER PILES @ 21350 = 21,600

15250


⊕
ROADWAY
PROTECTION

GULVERT
CONSTRUCTED
IN STAGE I


SK 3



SK. 4



SK.5



SK. 6


1 1/2" (40mm) ϕ x 4" LONG NC MACHINE SCREWS
WITH MATCHING WASHERS TIGHTENED TO
1 1/2" TYPE EC-6 FW FERRULE INSERTS
EMBEDDED IN CONCRETE. EACH GROUP
OF INSERTS SHALL BE LOCATED EXACTLY
IN POSITION USING TIMBER TEMPLATE.
(TYP.)

Menu

To: Mr. J. Blair
Foundation Design Section

Date 1992-01-28

Re: Hwy 400 Widening from Hwy 7 to N. of
Langstaff Rd
Culvert elevations at end of extension



Dennis Wang

LOADS ON FOUNDATION

EB STRUCTURE

A262 → 292
→ 171 April

Structural Section
Central Region
1201 Wilson Avenue
Atrium Tower, 4th Floor
Downsview, Ontario, M3M 1J8
Telephone: 235-5512

MINISTRY OF TRANSPORTATION

m e m o r a n d u m

TO: Mr. M. Devata
Head, Foundation Design Section

DATE: December 11, 1991

Attn. Mr. D. Dundas, Sr. Foundation Engr.

RE: Hwy. 400 Widening
From Hwy 7 to north of Langstaff Road
G.W.P. 612-89-00, District 6

As requested, this memorandum will supplement the information you need regarding this project.

3-cell concrete box culvert:

About 80 m long to be constructed in two stages; on stage 1, traffic will be squeezed towards the centerline on the existing Hwy 400; two rows of roadway protection will be installed at locations shown on the E-plan; excavate and construct the two outside pieces of the culvert; backfill and complete the road surface to form the 'detour'; on stage 2, switch the traffic onto the 'detour' and excavate for the middle portion of the culvert using the roadway protection installed in stage 1 to retain earth; construct the middle portion of the culvert; backfill and complete the road construction.

Culvert extensions at Sta. 14+938 & 15+349:

Both existing culverts are 1.2 x .9 non-rigid type and the extensions are identical with the existing; extensions are on both sides of the culvert as a result of the road widening; normally granular backfill requirements as per OPSD 803.01; OPSD 803.01 is attached for your information; bedding, if required, will be according to Foundation Design Section's recommendations; extensions may be to a maximum of 14 m on either sides of the existing culvert depending on detail design; a plan showing existing road condition with marked up culvert extensions is attached for your information.

The foundation investigation work for the new culvert and culvert extensions mentioned above will be under WP 527-91-01 within the GWP 612-89-00.

High Mast Pole Foundations:

Generally, the pole heights are about 35 m; mostly located along centerline of Hwy 400; some located in the interchange areas to provide illumination to the interchange; previously, design of high mast pole foundations was according to B. Brom's paper as recommended by Foundation Design Section before; reinforced pored-in-place concrete caisson foundations of 1372mm (54") diam. will most likely be used for foundations; typical foundation depths for different subsoils are attached for your information; frost depth of 1.2 m will be added to these depths.

The above work will be under WP 528-89-01 within the GWP 612-89-00.

Memo reports will be sufficient for all the investigations mentioned above.

I hope the above memorandum will clarify some questions about this project. Please let me know if you need any further information.

Dennis Wong

Dennis Wong
Sr. Structural Engineer
for:
V. F. Boehnke
Head, Structural Section

cc. Mr. R. McCormick, McCormick Rankin
Mr. J. Blair, Foundation Design

3.7.3

High Mass Lighting**Typical Foundation Depths**

b) 35 m Pole with 12 Heads (1372 mm diameter)

Cohesionless Soils


		Required Depth (m)
Loose Sand ($\phi = 30^\circ$)	Above Water Table	8.50
	Below Water Table	10.25
Medium Sand ($\phi = 35^\circ$)	Above Water Table	5.75
	Below Water Table	6.50
Dense Sand ($\phi = 40^\circ$)	Above Water Table	5.50 *
	Below Water Table	5.50 *

Cohesive Soils


		Required Depth (m)
q_u	= 40 kPa	14.50
	60	10.75
	80	8.75
	100	7.50
	120	6.75
	140	6.00
	160	5.50 *

* It is recommended that the length of the pile is at least greater than 4 times the diameter of the pile to satisfy the lower limit of short piles.

**FROST LINE ABOVE
TOP OF CULVERT**




CROSS-SECTION




LONGITUDINAL SECTION

**FROST LINE BELOW
TOP OF CULVERT**



CROSS-SECTION



LONGITUDINAL SECTION

NOTES:

- A Backfill material to be granular as specified.
- B All dimensions are in millimetres unless otherwise shown.

LEGEND:

- d = Denotes depth of granular (roadbed)
- f = Denotes depth of frost treatment = (measured from profile grade)

ONTARIO PROVINCIAL STANDARD DRAWING

Date 1983 12 01 Rev

**GRANULAR BACKFILL
FOR NON RIGID FRAME OPEN OR
BOX CONCRETE CULVERT**

Date

OPSD - 803.01



Hwy 7 Underpass, looking south




Hwy 400, looking north



Langstaff Road Underpass underconstruction
City of Vaughan Contract T90-16



East Approach under construction




New 3-cell culvert under east approach

HWY 400 WIDENING FROM HWY 7 TO N. OF LANGSTAFF RD.
WP 612-89-00



New 3-cell culvert under Ramp 400S-Langstaff Rd. E-W




Gabion protection at outlet of existing culvert s. of Lanstaff Rd

HWY 400 WIDENING FROM HWY 7 TO N. OF LANGSTAFF RD.
WP 612-89-00



Outlet of existing culvert S. of Langstaff Rd.



Ramp 400S-Langstaff Rd. E-W under construction

HWY 400 WIDENING FROM HWY 7 TO N. OF LANGSTAFF RD.
WP 612-89-00



Close-up of existing culvert s. of Langstaff Rd.



Langstaff Rd. Underpass, looking south

HWY 400 WINNING FROM HWY 7 TO N. OF LONGSTAFF RD.
WP 612-89-00



Cuvert at Sta. 14+938, East end



Culvert at 14+938, West end

HWY 400 WINNING FROM HWY 7 TO N. OF L. STAFF RD.
WP 612-89-00



Cuvert at Sta. 15+349, East end



Culvert at 15+349, West end