



**FOUNDATION INVESTIGATION REPORT  
ASINN CREEK CULVERT REPLACEMENT  
HIGHWAY 599  
TOWNSHIP OF SKEY, THUNDER BAY DISTRICT  
AGREEMENT NO.: 4014-E-0023  
SITE NO.: 48W-314/C  
GEOCRES NO. 52G-12  
GWP: 6354-14-00**

**JANUARY 11, 2019  
GS-TB-020407**

**PREPARED FOR:**  
Ministry of Transportation  
Planning and Design  
Eastern Region Office  
1355 John Counter Blvd.,  
Kingston, ON K7L 5A3

**DST CONSULTING ENGINEERS INC.  
605 Hewitson Street, Thunder Bay, Ontario P7B 5V5  
Phone: 1-807-623-2929 Fax: 1-807-623-1792**

## Table of Contents

1. INTRODUCTION .....	1
2. SITE DESCRIPTION .....	1
3. REGIONAL GEOLOGY.....	3
4. INVESTIGATION PROCEDURES AND LABORATORY TESTING.....	4
5. DESCRIPTION OF SUBSURFACE CONDITIONS .....	6
5.1 Fill – Sand and Gravel to Sand .....	6
5.2 Topsoil.....	7
5.3 Sand- Upper Layer.....	7
5.4 Silt .....	7
5.5 Sand- Lower Layer.....	8
5.6 Groundwater.....	9
5.7 Chemical Test Results .....	9
6. MISCELLANEOUS .....	10
7. LIMITATIONS OF REPORT .....	11

## Appendices

LIMITATIONS OF REPORT .....	'A'
DESCRIPTION OF TERMS .....	'B'
DRAWINGS .....	'C'
ENCLOSURES .....	'D'
NON-SPECIAL STANDARD PROVISIONS (NSSP) .....	'E'
CHEMICAL TEST RESULTS .....	'F'

## List of Tables

Table 4-1 Details of Borehole Locations.....	5
Table 5-1 Summary of soil strata at the culvert location .....	6
Table 5-2 Summary of Particle Size Distribution - Fill - Sand and Gravel to Sand .....	7
Table 5-3 Summary of Particle Size Distribution - Sand .....	7
Table 5-4 Summary of Particle Size Distribution - Silt .....	8
Table 5-5: Summary of Atterberg Limits - Silt.....	8
Table 5-6 Summary of Particle Size Distribution - Sand .....	8

Table 5-7 Groundwater depth at completion of drilling .....9  
Table 5-8: Chemical Test Results – Soil Sample.....9  
Table 5-9: Chemical Test Results – Water sample..... 10

## List of Figures

Figure 2-1: Location of existing culvert at Highway 599 (looking west).....2  
Figure 2-2: Embankment slope condition .....3

**FOUNDATION INVESTIGATION REPORT  
ASINN CREEK CULVERT REPLACEMENT  
HIGHWAY 599  
TOWNSHIP OF SKEY, THUNDER BAY DISTRICT  
AGREEMENT NO.: 4014-E-0023  
SITE NO.: 48W-314/C  
GEOCRES NO.: 52G-12  
GWP: 6354-14-00**

**PART 1: FACTUAL INFORMATION**

**1. INTRODUCTION**

DST Consulting Engineers Inc. (DST) was retained by MTO under the direction of the prime consultant, Planmac Engineering Inc. (Planmac), to conduct a foundation investigation and provide a report for the proposed culvert replacement on Highway 599. This work was carried out under Agreement No.: 4014-E-0023. This report addresses the field investigation, laboratory test program, factual report on conditions (Part 1) and conditions for the proposed culvert replacement (Part 1).

This report was initially submitted to Planmac and MTO in March 2017. It has been re-issued, at the request of WSP on behalf of MTO, with revisions to accommodate its updated (90%) design, including revisions to both its Drawings (Borehole Location Plan and Borehole Location Plan Soil Strata).

This revised report supersedes the previous DST March 23, 2017 report.

**2. SITE DESCRIPTION**

The site is located on Highway 599, approximately 10.7 km North-East of Highway 17 (Latitude 49.4691, Longitude -91.5443), Station 12+464, in the Township of Skey, in the District of Thunder Bay. The Highway runs northeast to southwest across a short drainage channel flowing northwest from Little Sandbar Lake into Sandbar Lake. The drainage channel is broad and flat, being about 100m wide at the culvert location. The existing Asinn Creek occupies a narrow meandering path within the wider drainage channel. The twin culverts are aligned northwest to southeast and perpendicular to the Highway.

The existing 21.2 m long Corrugated Steel Pipe (CSP) twin culvert is approximately 2.40 m in diameter. The year of construction of the existing culvert is not known with certainty (Figure 2-1

and Figure 2-2). An inspection by others indicates medium corrosion above the waterline and severe corrosion below the waterline. It was also reported that both barrels have deformation under the roadway and debris build up in the north barrel.

Based on the Ontario Structure Inspection Manual (OSIM), the fill thickness at the culvert location is approximately 1.0 m and the height of the embankment is approximately 2.3 m with side slopes of approximately 2H: 1V. There is some erosion of the embankment fill between the culvert barrels at the inlet and outlet areas. This is reportedly due to a lack of protective vegetation cover over the fill material. (Figure 2-2). The wider drainage feature is vegetated with reeds and grasses, while the main channel is open water. The surrounding slopes adjacent to the wider drainage feature are forested.



Figure 2-1: Location of existing culvert at Highway 599 (looking west)



Figure 2-2: Embankment slope condition

### **3. REGIONAL GEOLOGY**

Geological information is available from published *Ontario Geological Survey Map #52GSW* by the *Ontario Ministry of Natural Resources* for the Skey area. The local area landform is identified as outwash plain, valley train. Outwash deposits include plains, fans, deltas, and valley trains of varying sizes, all consisting mainly of sand and gravel. Most outwash sediments were drained from the front of a melting glacier and accumulated in flooded lowlands and valley bottoms. Although most outwash deposits formed in proglacial positions, some accumulated over masses of stagnant glacier ice, resulting in pitted or kettled surfaces. Outwash landscapes that show abandoned channel scars, braid bars or deep kettle holes are commonly coarse in texture (i.e. gravelly and cobbly rather than sandy).

As indicated on the *Bedrock Geology of Ontario West Central Sheet Map 2542*, the soil at the site is underlain by intrusive rocks of Archaen age comprising of massive to foliated granodiorite to granite. Secondary intrusive dyke swarms comprising of Palaeoproterozoic age diabase/dolerite (23b Wabigoon swarm) are indicated to cut across the area trending north west to south east.

#### **4. INVESTIGATION PROCEDURES AND LABORATORY TESTING**

Site work was carried out on September 10<sup>th</sup> to September 11<sup>th</sup>, 2015 utilizing a CME 750 drill rig equipped for geotechnical drilling and operated by DST. A total of four boreholes were advanced to depths ranging from 12.2 m to 16.3 m. The minimum number and depth of the boreholes was specified by the Ministry of Transportation (MTO).

The borehole locations and stratigraphic sections are shown on the Borehole Location Plan and Drawings 1 and 2 in Appendix C. Borehole 1 was advanced north of the existing culvert at Station 12+471, 3.9 m left of centreline, and advanced to a depth of 14.9 m below existing surface. Borehole 2 was advanced north of the existing culvert at Station 12+474, 12.8 m right of centreline, and advanced to a depth of 12.2 m below existing surface. Borehole 3 was advanced south of the existing culvert at Station 12+456, 6.1 m right of centreline, and advanced to a depth of 16.3 m below existing surface. Borehole 4 was advanced south of the existing culvert at Station 12+458, 5.1 m left of centreline, and advanced to a depth of 14.9 m below surface.

The borehole locations were referenced to the MTO Station numbering system as indicated on the drawings provided by the Ministry. The ground surface elevations at the borehole locations were surveyed by DST personnel and referenced to benchmark 416.142 m N and W in root of 0.30Φ Balsam (N = 5482306.5 m, E = 192860.4 m) as indicated on the drawings provided by the Ministry. Table 4.1 summarizes the details of borehole locations and depths.

All boreholes were abandoned using suitable abandonment barrier as described in Ontario Regulation 903 and its amendments. Augured boreholes were decommissioned by backfilling from the bottom of the hole to the ground surface with bentonite chips.

The fieldwork was supervised on a full-time basis by DST personnel who located the boreholes in the field, arranged for clearance of subsurface utilities, supervised the drilling and in-situ testing operations, retrieved samples, logged the boreholes, and supervised the backfilling of boreholes and reinstatement of drilling locations. Soil samples were obtained from the auger flights and from the split spoon sampler used for the Standard Penetration Test (SPT). The SPT testing was carried out in accordance with the procedures described in ASTM D1586. The number of blows required to drive the sampler 300 mm is known as the standard penetration blow count (N) which provides an indication of the condition or consistency of the soil. The soil samples collected during drilling were identified in the field, placed in labelled containers and transported to DST's geotechnical testing laboratory in Thunder Bay for further analyses.

Classification and index tests were subsequently performed in the laboratory on samples collected from the boreholes to aid in the selection of engineering properties. Laboratory testing included chemical tests, natural moisture contents and particle size analyses on selected soil samples. A total of twenty-seven (27) natural moisture contents, nine (9) grain size particle analyses, five (5) hydrometer tests, one (1) Atterberg limits test and two (2) sets of chemical tests have been carried out for this assignment. Laboratory test results are presented in the Boreholes Logs and graphical plots attached in Appendix D (Enclosures).

Table 4-1 Details of Borehole Locations

Borehole ID	Station	Elevation (m)	Depth (m)	Offset (m)	Completion Details
Borehole 1	12+471	417.2	14.9	3.9 Lt	Borehole backfilled with bentonite chips to ground surface.
Borehole 2	12+474	415.8	12.2	12.8 Rt	Borehole backfilled with bentonite chips to ground surface.
Borehole 3	12+456	417.0	16.3	6.1 Rt	Borehole backfilled with bentonite chips to ground surface.
Borehole 4	12+458	416.9	14.9	5.1 Lt	Borehole backfilled with bentonite chips to ground surface.

## 5. DESCRIPTION OF SUBSURFACE CONDITIONS

The subsurface conditions presented below are based on the information obtained during power auger drilling and laboratory determination on selected samples.

The generalized stratigraphy of the existing embankment and outside the embankment footprint, based on the conditions encountered in the boreholes consists of the following:

- Embankment fill comprising loose sand and gravel.
- Topsoil encountered at the base of the embankment north of the culverts.
- Underlain by loose to occasionally compact sand (upper layer)
- Which is underlain by a silt layer with trace to some sand, clay and trace gravel.
- Underlying the silt layer is a loose to compact sand (lower layer) is encountered

The soil strata at the culvert location have been summarized in Table 5-1 and detailed descriptions are provided below.

Table 5-1 Summary of soil strata at the culvert location

Layer	Depth (m)	Elevation (m)	Comments
Fill	0.0 to 2.3	417.2 to 414.9	Borehole 1
	0.0 to 2.3	417.0 to 414.7	Borehole 3
	0.0 to 2.3	416.9 to 414.6	Borehole 4
Topsoil	0.0 to 0.20	415.8 to 415.6	Borehole 2
Sand (Upper Layer)	2.3 to 6.7	414.9 to 410.5	Borehole 1
	0.2 to 3.8	415.6 to 412.0	Borehole 2
	2.3 to 3.8	414.7 to 413.2	Borehole 3
	2.3 to 3.8	414.6 to 413.1	Borehole 4
Silt	6.7 to 12.2	410.5 to 405.0	Borehole 1
	3.8 to 12.2	412.0 to 403.6	Borehole 2
	3.8 to 8.8	413.2 to 408.2	Borehole 3
	3.8 to 12.2	413.1 to 404.7	Borehole 4
Sand (Lower Layer)	12.2 to 14.9	405.0 to 402.3	Borehole 1
	8.8 to 16.3	408.2 to 400.7	Borehole 3
	12.2 to 14.9	404.7 to 402.0	Borehole 4

### 5.1 Fill – Sand and Gravel to Sand

Fill – Sand and Gravel to Sand, some to trace Silt was encountered in Boreholes 1, 3 and 4 with thicknesses of up to 2.3 m (Elev. 417.2 to 414.9 m, Elev. 417.0 to 414.7 m and Elev. 416.9 to 416.1 m). The natural moisture contents of samples tested was found to range between 4 and 26 %. The laboratory test results are summarized in Table 5-2.

Table 5-2 Summary of Particle Size Distribution - Fill - Sand and Gravel to Sand

Laboratory Results – Particle Size Distribution	
Gravel %	1 to 43
Sand %	50 to 88
Fines %	7 to 12

## 5.2 Topsoil

Topsoil was encountered at surface in Borehole 2 with thicknesses of 0.2 m. It is likely that top soil or other organic soil may also extend outside the area of the embankment fill.

## 5.3 Sand- Upper Layer

Sand, trace to some Silt, trace Gravel was encountered in all four boreholes, Borehole 1, 2, 3 and 4, at the depth of 2.3 m, 0.2 m, 2.3 m and 2.3 m, with a thickness of 4.4 m (Elev. 414.9 to 410.5 m), 3.6 m (Elev. 415.6 to 412.0 m), 1.5 m (Elev. 414.7 to 413.2 m) and 3.0 m (Elev. 416.1 to 413.1 m) respectively. Organic matter was encountered within this material in Borehole 1, 2, and 3 at depths between 2.3 m to 4.6 m, 0.2 m to 3.8 m and 2.3 m to 3.8 m respectively.

SPT 'N' values vary from 1 to 16, indicating a very loose to compact condition. The natural moisture contents of the sand material vary from 10 to 55 %. The high natural moisture content in the sand layer is an indication of the organic matter encountered within this layer. The laboratory test results are summarized in Table 5-3.

Table 5-3 Summary of Particle Size Distribution - Sand

Laboratory Results – Particle Size Distribution	
Gravel %	0 to 2
Sand %	84 to 93
Fines %	7 to 14

## 5.4 Silt

Silt, some Sand to Sandy, trace to some Clay was encountered in all four boreholes, Borehole 1, 2, 3 and 4, at the depth of 6.7 m, 3.8 m, 3.8 m and 3.8 m, with a thickness of 5.5 m (Elev. 410.5 to 405.0 m), 8.4 m (Elev. 412.0 to 403.6 m), 5.0 m (Elev. 413.2 to 408.2 m) and 8.4 m (Elev. 413.1 to 404.7 m) respectively. However, the thickness of the silt layer was not proven at Borehole 2 as the borehole was terminated within this layer.

SPT 'N' values vary from 7 to 18, indicating a loose to compact condition or firm to stiff consistency. The natural moisture contents of the silt material vary from 19 to 40 %. Atterberg Limits test and hydrometer tests were carried out on samples from Boreholes 2, 3 and 4. The results of the Atterberg Limits test indicate that the silt is of low plasticity. Therefore, the silt layer can behave either as cohesionless or cohesive depending on the clay content as shown in the borehole logs. Plasticity charts are presented in Appendix D. The laboratory test results are summarized in Table 5-4 and Table 5-5 below.

Table 5-4 Summary of Particle Size Distribution - Silt

Laboratory Results – Particle Size Distribution	
Gravel %	0 to 2
Sand %	2 to 31
Silt %	69 to 85
Clay %	5 to 29

Table 5-5: Summary of Atterberg Limits - Silt

Laboratory Results – Atterberg Limits	
Liquid Limit %	25
Plastic Limit %	19
Plasticity Index %	6

### 5.5 Sand- Lower Layer

Sand and silt to some silt, with some Gravel, was encountered in Boreholes 1, 3 and 4, at depths of 12.2 m (Elev. 405.0 m), 8.8 m (Elev. 408.2 m) and 12.2 m (Elev. 404.7 m) respectively. The thickness of the sand layer was not proven as Boreholes 1, 2 and 3 were terminated within this layer.

SPT 'N' values vary from 5 to 33, indicating a loose to compact condition, with one value in the dense category. The natural moisture contents of the sand material vary from 11 to 22 %. The laboratory test results are summarized in Table 5-6.

Table 5-6 Summary of Particle Size Distribution - Sand

Laboratory Results – Particle Size Distribution	
Gravel %	12 to 24
Sand %	46 to 59
Fines %	17 to 42

## 5.6 Groundwater

Groundwater levels in the boreholes where seepage was noted were measured upon completion of borehole drilling and prior to backfilling of the borehole. This information is included on the Borehole Logs in Appendix D.

At the time of the field investigation groundwater was observed in all four boreholes on completion of drilling (See Table 5-7). The water level of the creek was recorded at an elevation 414.0 m during the field investigation. Therefore, it is assumed that the groundwater table at all borehole locations would be close to or slightly above this level. The interpreted groundwater table at the time of investigation is indicated on the borehole logs.

Given the permeable nature of the stratigraphy at this site, groundwater levels can be expected to vary as the river level varies both seasonally and with local precipitation events.

Table 5-7 Groundwater depth at completion of drilling

Borehole	Groundwater Depth (m)	Groundwater Elev. (m)
Borehole 1	2.1	415.1
Borehole 2	0.7	415.1
Borehole 3	1.9	415.1
Borehole 4	1.8	415.1

## 5.7 Chemical Test Results

Selected soil samples were submitted to ALS Laboratories Thunder Bay for chemical analyses (pH, sulphate, conductivity, resistivity and Chloride) to assess the potential for corrosion and sulphate attack on buried structures.

The results are presented below in Table 5-8 and 5-9 and discussed in Section 7.15. Copies of the Laboratory Certificate of Analyses are provided in Appendix 'F'.

Table 5-8: Chemical Test Results – Soil Sample

Sample ID	Moisture (%)	Sulphate (mg/kg)	Chloride (mg/kg)	pH	Conductivity (umhos/cm)	Resistivity (ohm - cm)
BH1 at 2.7 m depth	48	131	507	5.43	408	2450

Table 5-9: Chemical Test Results – Water sample

Sample ID	Sulphate (mg/L)	Chloride (mg/L)	pH	Conductivity (umhos/cm)	Resistivity (ohm - cm)
Creek sample	1.43	2.76	7.22	65.6	15244

## 6. MISCELLANEOUS

Site work was carried out from September 10<sup>th</sup> to September 11<sup>th</sup>, 2015 utilizing a CME 750 all-terrain drill rig operated by DST personnel. Fieldwork was supervised on a full-time basis by Mark Menei who located the boreholes in the field, performed sampling, in-situ testing and logged the boreholes. Soil samples retrieved during drilling were identified in the field, placed in labelled containers and transported to DST's laboratory in Thunder Bay for further analysis. Interpretation of the data and preparation of the report was completed by Selorm Danku, Geotechnical Engineer P.Eng., and approved by Mike Fabius, Senior Geotechnical Engineer, P. Eng.

## 7. LIMITATIONS OF REPORT

A description of limitations which are inherent in carrying out site investigation studies is given in Appendix 'A', and this forms an integral part of this report.

For DST CONSULTING ENGINEERS INC.

Prepared by:

Approved by:



Selorm Danku, P.Eng.  
Geotechnical Engineer



Mike Fabius, P.Eng.  
Senior Geotechnical Engineer

**APPENDIX 'A'**  
**LIMITATIONS OF REPORT**

# **LIMITATIONS OF REPORT**

## **GEOTECHNICAL STUDIES**

The data, conclusions and recommendations which are presented in this report, and the quality thereof, are based on a scope of work authorized by the Client. Note that no scope of work, no matter how exhaustive, can identify all conditions below ground. Subsurface and groundwater conditions between and beyond the testholes may differ from those encountered at the specific locations tested, and conditions may become apparent during construction which were not detected and could not be anticipated at the time of the site investigation. Conditions can also change with time. It is recommended practice that DST Consulting Engineers be retained during construction to confirm that the subsurface conditions throughout the site do not deviate materially from those encountered in the testholes. The benchmark and elevations used in this report are primarily to establish relative elevation differences between the testhole locations and should not be used for other purposes, such as grading, excavation, planning, development, etc.

The design recommendations given in this report are applicable only to the project described in the text and then only if constructed substantially in accordance with details stated in this report. Since all details of the design may not be known, we recommend that we be retained during the final stage to verify that the design is consistent with our recommendations, and that assumptions made in our analysis are valid.

Unless otherwise noted, the information contained herein in no way reflects on environmental aspects of either the site or the subsurface conditions.

The comments given in this report on potential construction problems and possible methods are intended only for the guidance of the designer. The number of testholes may not be sufficient to determine all the factors that may affect construction methods and costs, e.g. the thickness of surficial topsoil or fill layers may vary markedly and unpredictably. The contractors bidding on this project or undertaking the construction should, therefore, make their own interpretation of the factual information presented and draw their own conclusion as to how the subsurface conditions may affect their work.

Any results from an analytical laboratory or other subcontractor reported herein have been carried out by others, and DST Consulting Engineers Inc. cannot warranty their accuracy. Similarly, DST cannot warranty the accuracy of information supplied by the client.

**Appendix B**  
**DESCRIPTION OF TERMS**

## EXPLANATION OF TERMS USED IN REPORT

**SPT 'N' VALUE:** THE STANDARD PENETRATION TEST (SPT) N VALUE OF THE NUMBER OF BLOWS REQUIRED TO CAUSE A STANDARD 51 mm O.D. SPLIT BARREL SAMPLES TO PENETRATE 0.3 m INTO UNDISTURBED GROUND IN A BOREHOLE WHEN DRIVEN BY A HAMMER WITH A MASS OF 63.5 kg, FALLING FREELY A DISTANCE OF 0.76 m. FOR PENETRATION OF LESS THAN 0.3 m N VALUES ARE INDICATED AS THE NUMBER OF BLOWS FOR THE PENETRATION ACHIEVED. AVERAGE N VALUE IS DENOTED THUS  $\bar{N}$ .

**DYNAMIC CONE PENETRATION TEST (DCPT):** CONTINUOUS PENETRATION OF A CONICAL STEEL POINT (51 mm O.D. 60° CONE ANGLE) DRIVEN BY 475 J IMPACT ENERGY ON 'A' SIZE DRILL RODS. THE RESISTANCE TO CONE PENETRATION IS MEASURED AS THE NUMBER OF BLOWS FOR EACH 0.3 m ADVANCE OF THE CONICAL POINT INTO THE UNDISTURBED GROUND.

### **SOILS ARE DESCRIBED BY THEIR COMPOSITION AND CONSISTENCY OR DENSENESS**

#### **TEXTURAL CLASSIFICATION OF SOILS**

BOULDERS	COBBLES	GRAVEL	SAND	SILT	CLAY
GREATER THAN 200 mm	75 TO 200 mm	4.75 TO 75 mm	0.075 TO 4.75 mm	0.002 TO 0.075 mm	LESS THAN 0.002 mm

#### **COARSE GRAIN SOIL DESCRIPTION (50% GREATER THAN 0.075 mm)**

TERMINOLOGY	TRACE OR OCCASIONAL	SOME	WITH	ADJECTIVE (e.g. SILTY OR SANDY)	AND (e.g. SAND AND SILT)
	LESS THAN 10%	10 TO 20%	20 TO 30%	30 TO 40%	40 TO 60%

#### **CONSISTENCY\*: COHESIVE SOILS ARE DESCRIBED ON THE BASIS OF THEIR UNDRAINED SHEAR STRENGTH ( $C_u$ ) AND SPT 'N' VALUES AS FOLLOWS**

$C_u$ (kPa)	0 – 12	12 – 25	25 – 50	50 - 100	100 - 200	> 200
N (BLOWS / 0.3 m)	<2	2 - 4	4 - 8	8 - 15	15 - 30	>30
	VERY SOFT	SOFT	FIRM	STIFF	VERY STIFF	HARD

#### **DENSENESS: COHESIONLESS SOILS ARE DESCRIBED ON THE BASIS ON DENSENESS AS INDICATED BY SPT 'N' VALUES AS FOLLOWS**

N (BLOWS / 0.3 m)	0 – 5	5 – 10	10 – 30	30 – 50	> 50
	VERY LOOSE	LOOSE	COMPACT	DENSE	VERY DENSE

### **ROCKS ARE DESCRIBED BY THEIR COMPOSITION AND STRUCTURAL FEATURES AND/OR STRENGTH**

**RECOVERY:** SUM OF ALL RECOVERED ROCK CORE PIECES FROM A CORING RUN EXPRESSED AS A PERCENT OF THE TOTAL LENGTH OF THE CORING RUN

**MODIFIED RECOVERY:** SUM OF THOSE INTACT CORE PIECES, 100 mm+ IN LENGTH EXPRESSED AS A PERCENTAGE OF THE LENGTH OF THE CORING RUN.

THE **ROCK QUALITY DESIGNATION (R.Q.D)** FOR MODIFIED RECOVERY IS:

R.Q.D (%)	0 – 25	25 – 50	50 – 75	75 – 90	90 – 100
	VERY POOR	POOR	FAIR	GOOD	EXCELLENT


#### **LEGEND OF RECORDS FOR BOREHOLES: SYMBOLS AND ABBREVIATIONS FOR SAMPLE TYPE**

SS	SPLIT SPOON SAMPLE	WS	WASH SAMPLE
TW	THIN WALL SHELBY TUBE SAMPLE	AS	AUGER (GRAB) SAMPLE
PH	SAMPLER ADVANCED BY HYDRAULIC PRESSURE	TP	THIN WALL PISTON SAMPLE
WH	SAMPLER ADVANCED BY SELF STATIC WEIGHT	PM	SAMPLER ADVANCED BY MANUAL PRESSURE
SC	SOIL CORE	RC	ROCK CORE
	WATER LEVEL	$SENSITIVITY = \frac{UNDISTURBED\ SHEAR\ STRENGTH}{REMOLDED\ SHEAR\ STRENGTH}$	

\*HIERARCHY OF SOIL STRENGTH PREDICTION: **1) LABORATORY TRIAXIAL TESTING. 2) FIELD INSITU VANE TESTING. 3) LABORATORY VANE TESTING. 4) SPT VALUES. 5) POCKET PENETROMETER.**

# **Appendix C**

## **DRAWINGS**



HCP 101  
N 5482426.528  
E 192916.520



**METRIC**  
DIMENSIONS ARE IN METRES  
AND / OR MILLIMETRES UNLESS  
OTHERWISE SHOWN. STATIONS  
IN KILOMETERS + METERS

AG No 4014-E-0023  
WP No 6354-14-00  
SITE No 48C-0314/C0  
GEOCREs No 52G-12



**CULVERT  
REPLACEMENT ASSIN  
CREEK CULVERT**  
STA 12+422 TO STA 12+500  
Survey 13-06 Revised

SHEET  
1



**LEGEND**

	Borehole
--	----------

No.	Elev. (m)	MTM Zone 16		Survey	
		North (m)	East (m)	Station	Offset
BH1	417.2	5482275	410311	12+471	3.9 m LT
BH2	415.8	5482272	410325	12+474	12.8 m RT
BH3	417.0	5482258	410312	12+456	6.1 m LT
BH4	416.9	5482262	410304	12+458	5.1 m RT

REV	DATE	ISSUE	DRAWN BY	CHECKED	APPROVAL
1	21-Sep-15	DRAFT	MD	BV	MWB
2	2-Feb-16	DRAFT	EM	SD	MK
3	16-May-16	DRAFT	EM	POS	MK
4	01-Mar-17	DRAFT	LA	BV	MF
5	25-Oct-18	DRAFT	CS	SD	BV



**NOTE:**  
The boundaries between soil strata have been established only at borehole locations. Between boreholes the boundaries are assumed by interpolation and may not represent actual conditions.

PLAN MAP  
Scale 1:250  
0 5m 10m

**DST** consulting engineers  
DST Consulting Engineers Inc.  
605 Hewitson Street  
Thunder Bay, ON P7B 5V5  
Ph: (807) 623-2929  
Fx: (807) 623-1792  
Email: thunderbay@dstgroup.com



SANDBAR LAKE



PLAN MAP  
Scale 1:250  
0 5m 10m


**METRIC**  
DIMENSIONS ARE IN METRES  
AND / OR MILLIMETRES UNLESS  
OTHERWISE SHOWN. STATIONS  
IN KILOMETERS + METERS

AG No 4014-E-0023  
WP No 6354-14-00  
SITE No 48C-0314/CO  
GEOCREs No 52G-12




**CULVERT  
REPLACEMENT ASSIN  
CREEK CULVERT**  
STA 12+422 TO STA 12+500  
Survey 13-06 Revised  
**BOREHOLE LOCATIONS  
AND SOIL STRATA**


SHEET  
2




**KEY PLAN**  
1.0 km 0 1.0 km



**CROSS SECTION A - A'**  
Scale 1:250  
0 5m 10m



**CROSS SECTION B - B'**  
Scale 1:250  
0 5m 10m



**PROFILE LINE C**  
Scale 1:250  
0 5m 10m

**LEGEND**

- Borehole
- SPT (BLOWS/300 mm)
- Water level at completion of drilling
- Fill
- Organics
- Topsoil
- Till
- Bedrock
- Sand
- Silt
- Clay
- Sand & Gravel
- Boulders

No.	Elev. (m)	MTM Zone 16		Survey	
		North (m)	East (m)	Station	Offset
BH1	417.2	5482275	410311	12+471	3.9 m LT
BH2	415.8	5482272	410325	12+474	12.8 m RT
BH3	417.0	5482258	410312	12+456	6.1 m LT
BH4	416.9	5482262	410304	12+458	5.1 m RT

REV	DATE	ISSUE	DRAWN BY	CHECKED	APPROVAL
1	21-Sep-15	DRAFT	MD	BV	MWB
2	2-Feb-16	DRAFT	EM	SD	MK
3	8-May-16	DRAFT	EM	PDS	MK
4	13-Oct-16	DRAFT	EM	SD	MK
5	8-Dec-16	DRAFT	RW	PDS	MK
6	1-Mar-17	DRAFT	RW	BV	MF
7	25-Oct-18	DRAFT	CS	SD	BV

**NOTE:**  
The boundaries between soil strata have been established only at borehole locations. Between boreholes the boundaries are assumed by interpolation and may not represent actual conditions.

**DST** consulting engineers  
DST Consulting Engineers Inc.  
605 Hewitson Street  
Thunder Bay, ON P7B 5V5  
Ph: (807) 623-2929  
Fx: (807) 623-1792  
Email: thunderbay@dstgroup.com

**Appendix D**  
**ENCLOSURES**

**RECORD OF BOREHOLE No BH1**

1 OF 1

**METRIC**

W.P. GWP 6354-14-00 LOCATION ASINN CREEK ORIGINATED BY MM  
 DIST MTO HWY 599 BOREHOLE TYPE HOLLOW STEM AUGER - 80 mm ID / SOLID STEM AUGER COMPILED BY SA  
 DATUM Geodetic DATE 2015 09 11 CHECKED BY SD

SOIL PROFILE		SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT		PLASTIC LIMIT W <sub>p</sub>	NATURAL MOISTURE CONTENT W	LIQUID LIMIT W <sub>L</sub>	UNIT WEIGHT γ	REMARKS & GRAIN SIZE DISTRIBUTION (%)
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE			"N" VALUES	SHEAR STRENGTH kPa					
						20	40	60	80	100			GR SA SI CL
417.2	GROUND SURFACE		AS1	AS									
	FILL - SAND, SOME SILT, TRACE GRAVEL LOOSE BROWN		SS2	SS	9								
			SS3	SS	8								
414.9			SS4	SS	8								1 87 (12)
2.3	SAND, SOME SILT, TRACE GRAVEL LOOSE TO COMPACT BROWN TO GREY ORGANIC MATTER AT 2.3 m to 4.6 m		SS5	SS	6								Water level taken at 2.1 m at end of drilling
			SS6	SS	8								
			SS7	SS	8								
			SS8	SS	10								2 84 (14)
410.5			SS9	SS	8								
6.7	SANDY SILT, TRACE GRAVEL LOOSE GREY		SS10	SS	10								
			SS11	SS	9								
			SS12	SS	7								
407.0			SS13	SS	5								
10.2	SILT, SOME SAND LOOSE GREY		SS14	SS	8								
													0 15 (85)
405.0													
12.2	SAND, TRACE SILT LOOSE GREY												
402.3													
14.9	END OF BOREHOLE AT 14.9 m												

ONL\_MOT-HIGH VANES AC.-BH LOGS.GPJ DATA TEMPLATE.GDT 13/5/16

+<sup>3</sup>, X<sup>3</sup>: Numbers refer to Sensitivity ○ 3% STRAIN AT FAILURE

**RECORD OF BOREHOLE No BH2**

1 OF 1

**METRIC**

W.P. GWP 6354-14-00 LOCATION ASINN CREEK ORIGINATED BY MM  
 DIST MTO HWY 599 BOREHOLE TYPE HOLLOW STEM AUGER - 80 mm ID / SOLID STEM AUGER COMPILED BY SA  
 DATUM Geodetic DATE 2015 09 10 CHECKED BY SD

SOIL PROFILE		SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT					UNIT WEIGHT $\gamma$ kN/m <sup>3</sup>	REMARKS & GRAIN SIZE DISTRIBUTION (%)	
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE			"N" VALUES	SHEAR STRENGTH kPa						
						20	40	60	80	100	PLASTIC LIMIT $W_p$	NATURAL MOISTURE CONTENT $W$	LIQUID LIMIT $W_L$	
						50	100	150	200	250	WATER CONTENT (%)			GR SA SI CL
415.8	GROUND SURFACE													
415.6	TOPSOIL													
0.2	SAND, TRACE SILT VERY LOOSE TO COMPACT BROWN TO GREY		AS1	AS										
			SS2	SS	1									
			SS3	SS	11									
	ORGANIC		SS4	SS	5									
			SS5	SS	7									
412.0														
3.8	SANDY SILT LOOSE TO COMPACT GREY		SS6	SS	9									0 31 (69)
			SS7	SS	12									
			SS8	SS	10									
409.1														
6.7	SILT, SOME CLAY, TRACE SAND FIRM TO STIFF GREY													
	LOW PLASTICITY		SS9	SS	7									0 5 76 19
			SS10	SS	12									
			SS11	SS	13									
	TRACE CLAY		SS12	SS	15									2 20 73 5
403.6														
12.2	END OF BOREHOLE AT 12.2 m													

ONL\_MOT-HIGH VANES AC-BH LOGS.GPJ DATA TEMPLATE.GDT 13/5/16

+<sup>3</sup>, X<sup>3</sup>: Numbers refer to Sensitivity ○ 3% STRAIN AT FAILURE

RECORD OF BOREHOLE No BH3

1 OF 1

METRIC

W.P. GWP 6354-14-00 LOCATION ASINN CREEK ORIGINATED BY MM  
 DIST MTO HWY 599 BOREHOLE TYPE SOLID STEM AUGER COMPILED BY SA  
 DATUM Geodetic DATE 2015 09 10 CHECKED BY SD

SOIL PROFILE		SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT		PLASTIC LIMIT W <sub>p</sub>	NATURAL MOISTURE CONTENT W	LIQUID LIMIT W <sub>L</sub>	UNIT WEIGHT γ	REMARKS & GRAIN SIZE DISTRIBUTION (%)
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE			"N" VALUES	SHEAR STRENGTH kPa					
417.0	GROUND SURFACE						20 40 60 80 100						
	FILL - SAND AND GRAVEL, TRACE SILT LOOSE BROWN TO GREY		AS1	AS									43 50 (7)
			SS2	SS	9								
			SS3	SS	9								
414.7													0 88 (12) Water level taken at 1.9 m at end of drilling
2.3	SAND, TRACE SILT COMPACT GREY ORGANIC MATTER AT 23 m to 3.8 m		SS4	SS	10								
			SS5	SS	16								
413.2													
3.8	SILT, SOME SAND, TRACE TO SOME CLAY COMPACT GREY		SS6	SS	10								
			SS7	SS	14								0 12 80 8
			SS8	SS	15								
			SS9	SS	14								
408.2													
8.8	SILT AND SAND, SOME GRAVEL COMPACT TO DENSE GREY		SS10	SS	18								12 46 (42)
			SS11	SS									
			SS12	SS	26								
			SS13	SS	33								
			SS14	SS	24								
400.7													
16.3	SAND WITH GRAVEL, SOME SILT DENSE GREY		SS15	SS	27								24 59 (17)
	END OF BOREHOLE AT 16.3 m												

ONL\_MOT-HIGH VANES AC-BH LOGS.GPJ DATA TEMPLATE.GDT 13/5/16

+<sup>3</sup>, X<sup>3</sup>: Numbers refer to Sensitivity ○ 3% STRAIN AT FAILURE

**RECORD OF BOREHOLE No BH4**

1 OF 1

**METRIC**


W.P. GWP 6354-14-00 LOCATION ASINN CREEK ORIGINATED BY MM  
 DIST MTO HWY 599 BOREHOLE TYPE HOLLOW STEM AUGER - 80 mm ID / SOLID STEM AUGER COMPILED BY SA  
 DATUM Geodetic DATE 2015 09 10 CHECKED BY SD

SOIL PROFILE		SAMPLES			GROUND WATER CONDITIONS	ELEVATION SCALE	DYNAMIC CONE PENETRATION RESISTANCE PLOT					PLASTIC LIMIT W <sub>p</sub>	NATURAL MOISTURE CONTENT W	LIQUID LIMIT W <sub>L</sub>	UNIT WEIGHT γ	REMARKS & GRAIN SIZE DISTRIBUTION (%)						
ELEV DEPTH	DESCRIPTION	STRAT PLOT	NUMBER	TYPE			"N" VALUES	SHEAR STRENGTH kPa									WATER CONTENT (%)					
						20	40	60	80	100	50	100	150	200	250	20	40	60	GR	SA	SI	CL
416.9	GROUND SURFACE																					
	FILL - SAND AND GRAVEL		AS1	AS																		
416.1																						
0.8	SAND, TRACE SILT LOOSE BROWN TO GREY		SS2	SS	6																	
			SS3	SS	7																	
			SS4	SS	6																	
			SS5	SS	6																	
413.1	ORGANIC (WOOD FRAGMENTS)																					
3.8	SILT, SOME SAND, TRACE CLAY LOOSE TO COMPACT BROWN TO GREY		SS6	SS	8																	
			SS7	SS	9																	
			SS8	SS	13																	
			SS9	SS	15																	
			SS10	SS	18																	
406.7																						
10.2	SILT WITH CLAY, TRACE SAND STIFF TO VERY STIFF GREY		SS11	SS	14																	
			SS12	SS	19																	
404.7																						
12.2	SAND, TRACE SILT COMPACT GREY		SS13	SS	25																	
			SS14	SS	25																	
402.0																						
14.9	END OF BOREHOLE AT 14.9 m																					

ONL\_MOT-HIGH VANES AC-BH LOGS.GPJ DATA TEMPLATE.GDT 13/5/16

+<sup>3</sup>, X<sup>3</sup>: Numbers refer to Sensitivity ○ 3% STRAIN AT FAILURE

# UNIFIED SOIL CLASSIFICATION SYSTEM



Ministry of  
Transportation  
Ontario


**GRAIN SIZE DISTRIBUTION  
SOIL DESCRIPTION  
FILL - SAND AND GRAVEL**

**ENCLOSURE 5**

**DST REF. # GS-TB-020407**

**ASINN CREEK CULVERT**

# UNIFIED SOIL CLASSIFICATION SYSTEM



Ministry of  
Transportation  
Ontario


**GRAIN SIZE DISTRIBUTION  
SOIL DESCRIPTION  
SAND - UPPER LAYER**

**ENCLOSURE 6**

**DST REF. # GS-TB-020407**

**ASINN CREEK CULVERT**

## UNIFIED SOIL CLASSIFICATION SYSTEM




Ministry of  
Transportation  
Ontario

**GRAIN SIZE DISTRIBUTION**  
**SOIL DESCRIPTION**  
**SILT**

**ENCLOSURE 7**  
**DST REF. # GS-TB-020407**  
**ASINN CREEK CULVERT**





**PLASTICITY CHART  
SILT**



Ministry of  
Transportation  
Ontario

ENCLOSURE 9

DST REF. # GS-TB-020407

ASINN CREEK CULVERT

**Appendix E**

**NON-STANDARD SPECIAL  
PROVISION**

**GROUNDWATER - Item No. 1**

---

Non-Standard Special Provision

---

This special provision covers the groundwater level.

It should be noted that depending on the season, the amount of water flow through the creek may vary. The groundwater level at the site may also be subject to seasonal variations. The contractor should be prepared for this situation. The contractor should be aware of the high water table, the potential for surface water fluctuations. The contractor should take this into account when selecting an excavation method, and any subsequent dewatering methods.

**Appendix F**  
**CHEMICAL TEST**  
**RESULTS**



DST Thunder Bay  
ATTN: Selorm Danku  
DST Consulting Engineers Inc.  
1120 Premier Way , Suite 200  
Thunder Bay ON P7B 0A3

Date Received: 01-DEC-15  
Report Date: 10-DEC-15 07:58 (MT)  
Version: FINAL

Client Phone: 807-345-3620

## Certificate of Analysis

Lab Work Order #: L1708995  
Project P.O. #: NOT SUBMITTED  
Job Reference:  
C of C Numbers:  
Legal Site Desc:

Rikki Thomson  
Account Manager

[This report shall not be reproduced except in full without the written authority of the Laboratory.]

ADDRESS: 1081 Barton Street, Thunder Bay, ON P7B 5N3 Canada | Phone: +1 807 623 6463 | Fax: +1 807 623 7598  
ALS CANADA LTD Part of the ALS Group A Campbell Brothers Limited Company



## Reference Information

**Test Method References:**

ALS Test Code	Matrix	Test Description	Method Reference**
CL-WT	Soil	Chloride in Soil	EPA 300.0
EC-WT	Soil	Conductivity (EC)	EPA 9050A
A representative subsample is tumbled with de-ionized (DI) water. The ratio of water to soil is 2:1 v/w. After tumbling the sample is then analyzed by a conductivity meter.			
MOISTURE-WT	Soil	% Moisture	Gravimetric: Oven Dried
PH-WT	Soil	pH	MOEE E3137A
Soil samples are mixed in the deionized water and the supernatant is analyzed directly by the pH meter.			
RESISTIVITY-WT	Soil	Resistivity	MOECC E3138
Resistivity on a soil is a 2:1 extraction of DI water to soil. Sample is tumbled for 30 min. Conductivity of the extraction is taken and the inverse is calculated for resistivity.			
SO4-WT	Soil	Sulphate	EPA 300.0

\*\* ALS test methods may incorporate modifications from specified reference methods to improve performance.

*The last two letters of the above test code(s) indicate the laboratory that performed analytical analysis for that test. Refer to the list below:*

Laboratory Definition Code	Laboratory Location
WT	ALS ENVIRONMENTAL - WATERLOO, ONTARIO, CANADA

**Chain of Custody Numbers:**
**GLOSSARY OF REPORT TERMS**

*Surrogates are compounds that are similar in behaviour to target analyte(s), but that do not normally occur in environmental samples. For applicable tests, surrogates are added to samples prior to analysis as a check on recovery. In reports that display the D.L. column, laboratory objectives for surrogates are listed there.*

*mg/kg - milligrams per kilogram based on dry weight of sample*

*mg/kg wwt - milligrams per kilogram based on wet weight of sample*

*mg/kg lwt - milligrams per kilogram based on lipid weight of sample*

*mg/L - unit of concentration based on volume, parts per million.*

*< - Less than.*

*D.L. - The reporting limit.*

*N/A - Result not available. Refer to qualifier code and definition for explanation.*

*Test results reported relate only to the samples as received by the laboratory.*

*UNLESS OTHERWISE STATED, ALL SAMPLES WERE RECEIVED IN ACCEPTABLE CONDITION.*

*Analytical results in unsigned test reports with the DRAFT watermark are subject to change, pending final QC review.*



## Quality Control Report

Workorder: L1708995

Report Date: 10-DEC-15

Page 1 of 2

Client: DST Thunder Bay  
 DST Consulting Engineers Inc. 1120 Premier Way , Suite 200  
 Thunder Bay ON P7B 0A3

Contact: Selorm Danku

Test	Matrix	Reference	Result	Qualifier	Units	RPD	Limit	Analyzed
<b>CL-WT</b>	<b>Soil</b>							
Batch	R3327616							
<b>WG2226771-3</b>	<b>CRM</b>	<b>AN-CRM-WT</b>						
Chloride			102.9		%		70-130	08-DEC-15
<b>WG2226771-2</b>	<b>LCS</b>							
Chloride			95.9		%		70-130	08-DEC-15
<b>WG2226771-1</b>	<b>MB</b>							
Chloride			<20		mg/kg		20	08-DEC-15
<b>EC-WT</b>	<b>Soil</b>							
Batch	R3325981							
<b>WG2227671-1</b>	<b>MB</b>							
Conductivity			<4.0		umhos/cm		4	07-DEC-15
<b>MOISTURE-WT</b>	<b>Soil</b>							
Batch	R3325347							
<b>WG2226652-2</b>	<b>LCS</b>							
% Moisture			95.5		%		90-110	05-DEC-15
<b>WG2226652-1</b>	<b>MB</b>							
% Moisture			<0.10		%		0.1	05-DEC-15
<b>PH-WT</b>	<b>Soil</b>							
Batch	R3326423							
<b>WG2228014-1</b>	<b>LCS</b>							
pH			6.99		pH units		6.7-7.3	07-DEC-15
<b>SO4-WT</b>	<b>Soil</b>							
Batch	R3327616							
<b>WG2226771-3</b>	<b>CRM</b>	<b>AN-CRM-WT</b>						
Sulphate			110.5		%		60-140	08-DEC-15
<b>WG2226771-2</b>	<b>LCS</b>							
Sulphate			96.2		%		70-130	08-DEC-15
<b>WG2226771-1</b>	<b>MB</b>							
Sulphate			<20		mg/kg		20	08-DEC-15

# Quality Control Report

Workorder: L1708995

Report Date: 10-DEC-15

Page 2 of 2

## Legend:

---

Limit	ALS Control Limit (Data Quality Objectives)
DUP	Duplicate
RPD	Relative Percent Difference
N/A	Not Available
LCS	Laboratory Control Sample
SRM	Standard Reference Material
MS	Matrix Spike
MSD	Matrix Spike Duplicate
ADE	Average Desorption Efficiency
MB	Method Blank
IRM	Internal Reference Material
CRM	Certified Reference Material
CCV	Continuing Calibration Verification
CVS	Calibration Verification Standard
LCSD	Laboratory Control Sample Duplicate

## Hold Time Exceedances:

All test results reported with this submission were conducted within ALS recommended hold times.

ALS recommended hold times may vary by province. They are assigned to meet known provincial and/or federal government requirements. In the absence of regulatory hold times, ALS establishes recommendations based on guidelines published by the US EPA, APHA Standard Methods, or Environment Canada (where available). For more information, please contact ALS.

---

The ALS Quality Control Report is provided to ALS clients upon request. ALS includes comprehensive QC checks with every analysis to ensure our high standards of quality are met. Each QC result has a known or expected target value, which is compared against pre-determined data quality objectives to provide confidence in the accuracy of associated test results.

Please note that this report may contain QC results from anonymous Sample Duplicates and Matrix Spikes that do not originate from this Work Order.



DST Thunder Bay  
ATTN: Bernie Villegas  
DST Consulting Engineers Inc.  
605 Hewitson street  
Thunder Bay ON P7B 5V5

Date Received: 19-OCT-15  
Report Date: 21-OCT-15 10:30 (MT)  
Version: FINAL

Client Phone: 807-626-1310

## Certificate of Analysis

Lab Work Order #: L1689521  
Project P.O. #: NOT SUBMITTED  
Job Reference: GS-TB-020407  
C of C Numbers:  
Legal Site Desc:

Rikki Thomson  
Account Manager

[This report shall not be reproduced except in full without the written authority of the Laboratory.]

ADDRESS: 1081 Barton Street, Thunder Bay, ON P7B 5N3 Canada | Phone: +1 807 623 6463 | Fax: +1 807 623 7598  
ALS CANADA LTD Part of the ALS Group A Campbell Brothers Limited Company

## ALS ENVIRONMENTAL ANALYTICAL REPORT

Sample Details/Parameters	Result	Qualifier*	D.L.	Units	Extracted	Analyzed	Batch
L1689521-1 LOW RIVER - 48W-6C Sampled By: CLIENT on 15-OCT-15 @ 14:05 Matrix: WATER							
<b>Physical Tests</b>							
Conductivity (EC)	46.6		3.0	uS/cm		19-OCT-15	R3292437
pH	7.37		0.10	pH		19-OCT-15	R3292437
<b>Anions and Nutrients</b>							
Chloride (Cl)	0.47		0.10	mg/L		20-OCT-15	R3293233
Sulfate (SO4)	0.77		0.30	mg/L		20-OCT-15	R3293233
L1689521-2 WIGGLE CREEK -48W-312C Sampled By: CLIENT on 15-OCT-15 @ 15:30 Matrix: WATER							
<b>Physical Tests</b>							
Conductivity (EC)	42.0		3.0	uS/cm		19-OCT-15	R3292437
pH	7.11		0.10	pH		19-OCT-15	R3292437
<b>Anions and Nutrients</b>							
Chloride (Cl)	0.91		0.10	mg/L		20-OCT-15	R3293233
Sulfate (SO4)	1.13		0.30	mg/L		20-OCT-15	R3293233
L1689521-3 SAVANT LAKE - 48W-313C Sampled By: CLIENT on 15-OCT-15 @ 16:10 Matrix: WATER							
<b>Physical Tests</b>							
Conductivity (EC)	52.3		3.0	uS/cm		19-OCT-15	R3292437
pH	6.98		0.10	pH		19-OCT-15	R3292437
<b>Anions and Nutrients</b>							
Chloride (Cl)	2.25		0.10	mg/L		20-OCT-15	R3293233
Sulfate (SO4)	0.51		0.30	mg/L		20-OCT-15	R3293233
L1689521-4 GRAYSTONE LAKE -48W-189C Sampled By: CLIENT on 15-OCT-15 @ 17:13 Matrix: WATER							
<b>Physical Tests</b>							
Conductivity (EC)	31.1		3.0	uS/cm		19-OCT-15	R3292437
pH	7.14		0.10	pH		19-OCT-15	R3292437
<b>Anions and Nutrients</b>							
Chloride (Cl)	0.13		0.10	mg/L		20-OCT-15	R3293233
Sulfate (SO4)	1.21		0.30	mg/L		20-OCT-15	R3293233
L1689521-5 ASINN CREEK-48W-314C Sampled By: CLIENT on 15-OCT-15 @ 10:05 Matrix: WATER							
<b>Physical Tests</b>							
Conductivity (EC)	65.6		3.0	uS/cm		19-OCT-15	R3292437
pH	7.22		0.10	pH		19-OCT-15	R3292437
<b>Anions and Nutrients</b>							
Chloride (Cl)	2.76		0.10	mg/L		20-OCT-15	R3293233
Sulfate (SO4)	1.43		0.30	mg/L		20-OCT-15	R3293233

\* Refer to Referenced Information for Qualifiers (if any) and Methodology.

## Reference Information

**QC Samples with Qualifiers & Comments:**

QC Type Description	Parameter	Qualifier	Applies to Sample Number(s)
Method Blank	Chloride (Cl)	B	L1689521-1, -2, -3, -4, -5
Matrix Spike	Chloride (Cl)	MS-B	L1689521-1, -2, -3, -4, -5

**Sample Parameter Qualifier key listed:**

Qualifier	Description
B	Method Blank exceeds ALS DQO. All associated sample results are at least 5 times greater than blank levels and are considered reliable.
MS-B	Matrix Spike recovery could not be accurately calculated due to high analyte background in sample.

**Test Method References:**

ALS Test Code	Matrix	Test Description	Method Reference**
CL-L-IC-N-TB	Water	Chloride in Water by IC (Low Level) Inorganic anions are analyzed by Ion Chromatography with conductivity and/or UV detection.	EPA 300.1 (mod)
EC-TITR-TB	Water	Conductivity This analysis is carried out using procedures adapted from APHA Method 2510 "Conductivity". Conductivity is determined using a conductivity electrode.	APHA 2510 B
PH-TITR-TB	Water	pH This analysis is carried out using procedures adapted from APHA Method 4500-H "pH Value". The pH is determined in the laboratory using a pH electrode	APHA 4500-H
SO4-IC-N-TB	Water	Sulfate in Water by IC Inorganic anions are analyzed by Ion Chromatography with conductivity and/or UV detection.	EPA 300.1 (mod)

\*\* ALS test methods may incorporate modifications from specified reference methods to improve performance.

*The last two letters of the above test code(s) indicate the laboratory that performed analytical analysis for that test. Refer to the list below:*

Laboratory Definition Code	Laboratory Location
TB	ALS ENVIRONMENTAL - THUNDER BAY, ONTARIO, CANADA

**Chain of Custody Numbers:**
**GLOSSARY OF REPORT TERMS**

*Surrogates are compounds that are similar in behaviour to target analyte(s), but that do not normally occur in environmental samples. For applicable tests, surrogates are added to samples prior to analysis as a check on recovery. In reports that display the D.L. column, laboratory objectives for surrogates are listed there.*

*mg/kg - milligrams per kilogram based on dry weight of sample*

*mg/kg wwt - milligrams per kilogram based on wet weight of sample*

*mg/kg lwt - milligrams per kilogram based on lipid weight of sample*

*mg/L - unit of concentration based on volume, parts per million.*

*< - Less than.*

*D.L. - The reporting limit.*

*N/A - Result not available. Refer to qualifier code and definition for explanation.*

*Test results reported relate only to the samples as received by the laboratory.*

*UNLESS OTHERWISE STATED, ALL SAMPLES WERE RECEIVED IN ACCEPTABLE CONDITION.*

*Analytical results in unsigned test reports with the DRAFT watermark are subject to change, pending final QC review.*



## Quality Control Report

Workorder: L1689521

Report Date: 21-OCT-15

Page 1 of 3

Client: DST Thunder Bay  
 DST Consulting Engineers Inc. 605 Hewitson street  
 Thunder Bay ON P7B 5V5

Contact: Bernie Villegas

Test	Matrix	Reference	Result	Qualifier	Units	RPD	Limit	Analyzed
<b>CL-L-IC-N-TB</b>		<b>Water</b>						
Batch	R3293233							
<b>WG2196265-6</b>	<b>LCS</b>							
Chloride (Cl)			99.7		%		90-110	20-OCT-15
<b>WG2196265-5</b>	<b>MB</b>							
Chloride (Cl)			<0.10		mg/L		0.1	20-OCT-15
<b>EC-TITR-TB</b>		<b>Water</b>						
Batch	R3292437							
<b>WG2195669-2</b>	<b>LCS</b>							
Conductivity (EC)			97.8		%		90-110	19-OCT-15
<b>WG2195669-1</b>	<b>MB</b>							
Conductivity (EC)			<3.0		uS/cm		3	19-OCT-15
<b>PH-TITR-TB</b>		<b>Water</b>						
Batch	R3292437							
<b>WG2195669-2</b>	<b>LCS</b>							
pH			6.02		pH		5.9-6.1	19-OCT-15
<b>SO4-IC-N-TB</b>		<b>Water</b>						
Batch	R3293233							
<b>WG2196265-6</b>	<b>LCS</b>							
Sulfate (SO4)			98.7		%		90-110	20-OCT-15
<b>WG2196265-5</b>	<b>MB</b>							
Sulfate (SO4)			<0.30		mg/L		0.3	20-OCT-15

# Quality Control Report

Workorder: L1689521

Report Date: 21-OCT-15

Page 2 of 3

## Legend:

---

Limit	ALS Control Limit (Data Quality Objectives)
DUP	Duplicate
RPD	Relative Percent Difference
N/A	Not Available
LCS	Laboratory Control Sample
SRM	Standard Reference Material
MS	Matrix Spike
MSD	Matrix Spike Duplicate
ADE	Average Desorption Efficiency
MB	Method Blank
IRM	Internal Reference Material
CRM	Certified Reference Material
CCV	Continuing Calibration Verification
CVS	Calibration Verification Standard
LCSD	Laboratory Control Sample Duplicate

## Sample Parameter Qualifier Definitions:

---

Qualifier	Description
B	Method Blank exceeds ALS DQO. All associated sample results are at least 5 times greater than blank levels and are considered reliable.

---

# Quality Control Report

Workorder: L1689521

Report Date: 21-OCT-15

Page 3 of 3

## Hold Time Exceedances:

---

ALS Product Description	Sample ID	Sampling Date	Date Processed	Rec. HT	Actual HT	Units	Qualifier
-------------------------	-----------	---------------	----------------	---------	-----------	-------	-----------

---

## Legend & Qualifier Definitions:

EHTR-FM: Exceeded ALS recommended hold time prior to sample receipt. Field Measurement recommended.  
EHTR: Exceeded ALS recommended hold time prior to sample receipt.  
EHTL: Exceeded ALS recommended hold time prior to analysis. Sample was received less than 24 hours prior to expiry.  
EHT: Exceeded ALS recommended hold time prior to analysis.  
Rec. HT: ALS recommended hold time (see units).

## Notes\*:

Where actual sampling date is not provided to ALS, the date (& time) of receipt is used for calculation purposes.  
Where actual sampling time is not provided to ALS, the earlier of 12 noon on the sampling date or the time (& date) of receipt is used for calculation purposes. Samples for L1689521 were received on 19-OCT-15 09:25.

ALS recommended hold times may vary by province. They are assigned to meet known provincial and/or federal government requirements. In the absence of regulatory hold times, ALS establishes recommendations based on guidelines published by the US EPA, APHA Standard Methods, or Environment Canada (where available). For more information, please contact ALS.

---

The ALS Quality Control Report is provided to ALS clients upon request. ALS includes comprehensive QC checks with every analysis to ensure our high standards of quality are met. Each QC result has a known or expected target value, which is compared against pre-determined data quality objectives to provide confidence in the accuracy of associated test results.

Please note that this report may contain QC results from anonymous Sample Duplicates and Matrix Spikes that do not originate from this Work Order.